FINELITE®
Better Lighting

WELL & LEED Compatible Finelite Products

Fixture	Luminaire Construction	Red List Declared	Red List Approved	Downlight Meets Well Bulding Feature L04 Option 1 c		Downlight Meets LEED v5* Glare Control	
				Requirements at 80CRI	Requirements at 90CRI	Requirements at 80CRI	Requirements at 90CRI
E1	Steel	✓	N/A	N/A	N/A	N/A	N/A
E2	Aluminum	✓	N/A	Tailored to 371 lumens/ft	S/B	S	S/B
E3	Aluminum	✓	✓	N/A	N/A	N/A	N/A
HO4	Aluminum	✓	✓	S	S/B	S/B	S/B
HP-WG	Steel	✓	✓	N/A	N/A	N/A	N/A
HP-WS	Steel	✓	✓	N/A	N/A	N/A	N/A
HP-2 Acoustic	N/A	N/A	N/A	Tailored to 296 lumens/ft	S	S	S
HP-2 Micro Louver White	Aluminum	✓	✓	S/B/H/V	S/B/H/V	S/B/H/V	S/B/H/V
HP-2 Micro Louver Black	Aluminum	✓	✓	S/B/H/V	S/B/H/V	S/B/H/V	S/B/H/V
HP-2 F	Aluminum	✓	✓	Tailored to 296 lumens/ft	S	S	S/B
HP-2 RG LHE	Aluminum	✓	✓	S/B/H	S/B/H/V	S/B/H	S/B/H/V
HP-2 RG LHC	Aluminum	✓	✓	S	S/B	S/B/H	S/B/H/V
HP-2 Drop Lens	Aluminum	✓	✓	S	S/B	S	S/B
HP-2 RG WCB	Aluminum	✓	✓	S	S/B	S/B	S/B
HP-2 DSO	Aluminum	✓	✓	Tailored to 274 lumens/ft	S	Tailored to 274 lumens/ft	S
HP-2 Circle	Steel	✓	✓	S/B/H/V	S/B/H/V	S/B/H/V	S/B/H/V
HP-3	Aluminum	✓	✓	Tailored to 417 lumens/ft	S	S	S
HP-4 F	Aluminum	✓	✓	S/B	S/B/H	S/B	S/B/H
HP-4 LHE	Aluminum	✓	✓	S/B	S/B/H	S/B/H	S/B/H/V
HP-4 DSO	Aluminum	✓	✓	S	S/B	S/B	S/B/H
HP-4 RG	Aluminum	✓	✓	S/B	S/B	S/B	S/B/H
HP-4 DL	Aluminum	✓	✓	S/B	S/B/H	S/B/H	S/B/H/V
HP-4 LHC	Aluminum	✓	✓	S/B	S/B/H	S/B	S/B/H/V
HP-4 WCB	Aluminum	✓	✓	S/B	S/B	S/B	S/B/H
HP-4 Circle	Steel	✓	✓	S/B/H/V	S/B/H/V	S/B/H/V	S/B/H/V
HP-4 WL	N/A	N/A	N/A	S/B	S/B/H	S/B	S/B/H
HP-6	Aluminum	✓	✓	S/B/H	S/B/H/V	S/B/H	S/B/H/V
HPO	Aluminum	✓	✓	Tailored to 349 lumens/ft	S	S	S/B
HPR	Steel	✓	✓	S/B/H	S/B/H/V	S/B/H	S/B/H/V
HPT	Steel	✓	✓	S/B/H	S/B/H/V	S/B/H/V	S/B/H/V
HPW	Steel	✓	✓	N/A	N/A	N/A	N/A
HPX	Aluminum	✓	✓	Tailored to 340 lumens/ft	S	Tailored to 408 lumens/ft	S/B
S11 MF	Steel	✓	✓	N/A	N/A	N/A	N/A
S11 MP	Steel	✓	✓	N/A	N/A	N/A	N/A
S12	Steel	✓	✓	S/B/H/V	S/B/H/V	S/B/H/V	S/B/H/V
S16	Steel	✓	✓	S/B/H	S/B/H/V	S/B/H	S/B/H/V
S17	Steel	✓	✓	N/A	N/A	N/A	N/A
S18	Steel	✓	✓	S/B/H/V	S/B/H/V	S/B/H/V	S/B/H/V
S19	Aluminum	✓	✓	S/B/H/V	S/B/H/V	S/B/H/V	S/B/H/V

* Outputs that qualify for LEED V5 also qualify for LEED V4.1

Flicker: Our luminaires follow the recommendations outlined in IEEE Std. 1789-2015 and used components operate with a modulation frequency higher than 1250Hz under all dimming conditions. The components operate in the IEEE “NOEL” (No Observable Effect Level) specification range at all times.