Customer	Class	File Number
Brumall Manufacturing Corporation 7850 Division Dr., Mentor OH USA 44060	6223-02 WIRE CONNECTING DEVICES-Wire Connectors	026192_0_000

Multiple wire, pressure type, terminal block (power) connectors, for copper and aluminum conductors:

- Cat No ST-400, ST-400-01, large hole, one wire 600 MCM - 4, two wire 250 MCM, 1/0, small holes 2/0 - 14 and 3/0-14.
- Cat No BST-400, one wire 600 MCM - 4, two wire 250 MCM, - 1/0.
- Cat No 2-BST-400, one wire 600 MCM - 4, two wire, 250 MCM - 1/0.
- Cat No BS-600, SB-600, one wire, 600 MCM - 4, two wire 250 MCM - 1/0.
- Cat No 300-2, large hole, 300 MCM - 6 AWG, small hole, 2/0 - 14 AWG.
- Cat No SB-400, 600 MCM - 2 AWG.
- Cat No ST-125, large hole, 1/0-14, small hole, 2-14.
- Cat No ST-225, ST-225-01, large hole, 300 MCM - 6, small hole, 2/0-14.
- Cat No 300-3149, 4-14 copper, 4-12 aluminum.
- Cat No 300-3150, 4-14 copper, 4-12 aluminum.
- Cat No 300-3152, 4-14 copper, 4-12 aluminum.
- Cat No 2/0-2, large hole, 4-2/0 AWG, small hole, 2-14 AWG.
- Cat No 03419, large hole, 1/0-14, small hole, 4-14.
- Cat No A-6B, large hole, 2/0-14, small hole, 4-14.
- Cat No 5203-01, large hole, 3/0 - 6, small hole, 4-14.
- Cat Nos 800-12, 800-2-24, 800-3-36, 800-4-42, 800-4-48, 800-5-60, 800-6-63, main 800-300 MCM and tap 4-14 AWG copper, 4-12 AWG aluminum.
- Distribution block connectors, Series A-K1, A-P1, A-R1, A-V1.
- Cat Nos. 1012, 1018, 1024, 1030, 1036 and 1042

Neutral bar, pressure type connectors for copper and aluminum conductors:

- Cat No 4A-14, 4-14 copper, 4-12 aluminum.
- Cat No 1X-8, 4-14 copper, 4-12 aluminum.
- Cat No 1-2, 2-14 copper, 2-12 aluminum.
- Cat No, 1X-2, 2-14 copper, 2-12 aluminum.
- Cat No 1-0, 1/0-14 copper, 1/0-12 aluminum.
- Cat No 1X-0, 1/0-14 copper, 1/0-12 aluminum.
- Cat No 1-00, 2/0-14 copper, 2/0-12 aluminum.
- Cat No 1X-00, 2/0-14 copper, 2/0-12 aluminum.
- Cat No 1-250, 250 MCM - 2 AWG.
- Cat No 1X-250, 250 MCM - 2 AWG.
- Cat No 1-300, 300 MCM - 2 AWG.
- Cat No 1X-300, 300 MCM - 2 AWG.
- Neutral assemblies, Series SNB.

Terminal L-shaped lugs, pressure type, for copper conductors only:

- Cat Nos 6TC, 4TC, 14-4 AWG.
- Cat Nos 2TC, 14-2 AWG.
- Cat Nos 1/0TC, 14-1/0 AWG.
- Cat No 3/0TC, 3/0-6 AWG.
- Cat Nos 4/0TC, 2-4/0 AWG.
- Cat Nos 350TC, 6 AWG - 350 MCM.
- Cat Nos 500TC, 6 AWG - 500 MCM.
- Cat Nos 1000TC, 500 MCM - 1000 MCM.
- Cat No BS-400, one wire, 600 MCM - 4 AWG and two wire 250 MCM - 1/0.
- Cat No C-70, 2-8 AWG.
- Cat No C-35, 6-14 AWG, C125, 1/0-2 AWG, X-6, 6-14 AWG and X-4, 4-14 AWG.

Terminal, L-shaped lugs, pressure type, for copper and aluminum conductors:

- Cat Nos NB-4, NB-2, NB-2/0, NB-250, NB-350, NB-600, NB-750.
- Cat Nos 2-2T, 3-2T, 3-2L2, 3-2L4, 2-14 AWG copper, 2-12 AWG aluminum.
- Cat Nos 2-0T, 3-0T, 2-1/0T, 3-1/0L2, 3-1/0L4, 14-1/0 AWG copper, 12-1/0 AWG aluminum.
- Cat Nos 2-2/0T, 3-2/0T, 2/0TP-1, 2-2/0L2, 14-2/0 AWG copper, 12-2/0 AWG.
- Cat Nos 3-3/0L2, 3-3/0L4, 2-3/0T, 6 AWG 3/0 AWG.
- Cat Nos 2-250T, 3-250T, 4-250T, 250TP-1, 250TP-2, 2-250TP, 2-250L2, 3-250L2, 3-250L4, 4-250L4, 6 AWG - 250 MCM.
- Cat Nos 2-300TP, 300TP-2, 6 AWG - 300 MCM.
- Cat Nos 2-350T, 3-350T, 4-350T, 2-350TP, 2-350L2, 3-350L2, 3-350L4, 4-350L4, 6 AWG -350 MCM.
- Cat Nos 2-500T, 3-500T, 4-500T, 6 AWG - 500 MCM.
- Cat Nos 2-600T, 3-600T, 4-600T, 2-600TS, 2-600TP, 600T-4, 600T-3, 600T-2, 2-600L2, 3-600L2, 3-600L4, 4-600L4, 2 AWG - 600 MCM.
- Cat Nos 2-750T, 750T-2, 750T-3, 750T-4, 1/0 AWG - 750 MCM.
- Cat Nos 2-800T, 3-800T, 4-800T, 800T-2, 800T-3, 800T-4, 2-800L2, 3-800L2, 3-800LL2, 3-800LL4, 2-800L4, 3-800L4, 4-800L4, 4-800LL4, 300 MCM - 800 MCM.
- Cat Nos 2-1000T, 3-1000T, 4-1000T, 2-1000L2, 3-1000L2, 3-1000LL2, 3-1000L4, 3-1000LL4, 4-1000L4, 4-1000LL4, 500 MCM - 1000 MCM.
- Cat Nos 6T, 6TCA, 4T, 4TCA, 4-14 AWG copper, 4-12 AWG aluminum.
- Cat Nos 2T, 2TCA, 2ST, 2-14 AWG copper, 2-12 AWG aluminum.
- Cat Nos 0T, 0T-1, 0T-2, 1/0TCA, 0TA, 14-1/0 AWG copper, 12-1/0 AWG aluminum.
- Cat Nos 2/0T, 2/0TP, 2/0TA, 2/0TF, 2/0TB, 2/0TC, 2/0T1, T26, 2/0L2, 2/0LL2, 14-2/0 AWG copper, 12-2/0 AWG aluminum.
- Cat Nos 3/0T, T36, 3/0 TCA, 6 AWG, 3/0 AWG.
- Cat No 4/0 TCA, 2-4/0 AWG.
- Cat Nos 250T, 250TP, 250L2, 250T1, 250TA, 6 AWG - 250 MCM.
- Cat Nos 300T, 300TP, 6 AWG - 300 MCM.
- Cat Nos 350T, 350TCA, 350TP, 350T1, 350TB, 350L2, 350LL2, 6 AWG-350 MCM.
- Cat Nos 500T, 500T1, 500T2, 500T3, 500T4, 500TCA, 6 AWG - 500 MCM.
- Cat Nos 600T, 600TS, 600TP, 600L2, 2 AWG - 600 MCM.
- Cat Nos 750T, 1/0 AWG - 750 MCM.
- Cat Nos 800T, 800L2, 800LL2, 300 MCM - 800 MCM.
- Cat Nos 1000T, 1000TCA, 1000L2, 1000LL2, 500 MCM - 1000 MCM.

AL9Cu: Collar, pressure type connectors, for use with tangs, copper and aluminum conductors:

- Cat No BS-O, 1/0-14 copper, 1/0-12 aluminum.
- Cat No BS-2/0, torque rating "100 in-lbs", 2/0-14 AWG copper, 2/0-12 AWG aluminum.
- Cat No S-O, 1/0-14 copper, 1/0-12 aluminum.
- Cat No BS-300, 300 MCM - 6 AWG.
- Cat No S-300, 300 MCM - 6 AWG.
- Cat No BS-301, 300 MCM - 6 AWG.
- Cat No BS-302, 300 MCM - 6 AWG.
- Cat No SP90-4/E, 1/0-14 AWG copper, 3/0-12 AWG aluminum, torque rating "150 in-lbs".
- Cat No SP90-4/Y, 1-12 AWG copper, 2/0-10 AWG aluminum, torque rating, "100 in-lbs".
- Cat No ST600.

/lb