
BRYANT® Wiring Devices
for Industrial and Commercial Environments
Devices for Factory and Maintenance Use

EXTRA HEAVY-DUTY INDUSTRIAL PLUGS AND CONNECTORS Inches (mm)



Description	Color	Cord Diameter	15 A 125V	20A 125V
Black/white Nylon Plug	Black/White	.300-.655 (7.6-16.6)	**BRY5266NP**	**BRY5366NP**
Black/white Nylon Connector	Black/White	.300-.655 (7.6-16.6)	**BRY5269NC**	**BRY5369NC**
High visibility; nylon Plug	Yellow	.220-.660 (7.6-16.8)	**BRY5965Y**	**5364Y**
High visibility; nylon Connector	Yellow	.220-.660 (7.6-16.8)	**BRY5969Y**	**5369Y**



BRY5266NP



BRY5269NC

SPECIFICATION GRADE DUPLEX RECEPTACLES Inches (mm)

Description	Color	15 A 125V	20A 125V
Extra Heavy-Duty Industrial Specification Grade; Nylon construction; self-grounding; back and side wired	Black	**BRY5262BLK**	**BRY5362BLK**
	Blue	**BRY5262BU**	**BRY5362BU**
	Brown	**BRY5262**	**BRY5362**
	Gray	**BRY5262GRY**	**BRY5362GRY**
	Ivory	**BRY5262I**	**BRY5362I**
	Red	**BRY5262RED**	**BRY5362RED**
	White	**BRY5262W**	**BRY5362W**
Commercial Specification Grade; Smooth nylon face; self-grounding; side wired	Almond	**CRS15AL**	**CRS20AL**
	Black	**CRS15BLK**	**CRS20BLK**
	Brown	**CRS15**	**CRS20**
	Gray	**CRS15GRY**	**CRS20GRY**
	Ivory	**CRS15I**	**CRS20I**
	Light Almond	**CRS15LA**	**CRS20LA**
	White	**CRS15W**	**CRS20W**



BRY5262I



CRS15BLK

LOCKING PLUGS AND CONNECTORS

NEMA	Rating	Plug	Connector	Triple-Gripper® Plug	Triple-Gripper® Connector	Receptacle Single	Receptacle Duplex
L5-15	15A 125V			**4721NP**	**4732NC**	—	**4700DR**
L5-20	20A 125V			**70520NP**	**70520NC**	**70520FR**	—
L5-30	30A 125V			**70530NP**	**70530NC**	**70530FR**	—
L6-20	20A 250V			**70620NP**	**70620NC**	**70620FR**	—
L6-30	30A 250V			**70630NP**	**70630NC**	**70630FR**	—
L14-30	30A 125/250V			**71430NP**	**71430NC**	**71430FR**	—



70520NP



70520NC



70520FR



4700DR

PLUGBOX® DEVICES

Description	Catalog Number
Red polypropylene lockout device accommodates: 3-wire, 15 amp locking molded-on plugs up to 277V rating	**BLDMP**
Red polypropylene lockout device accommodates: 2- and 3-wire, 15 amp locking plugs up to 277V rating; 3-wire; 20 amp 125V power interrupting plugs and 3-, 4- and 5-wire, 20 and 30 amp NEMA and non-NEMA locking plugs	**BLD**



BLD

NOTES:

BRYANT® Wiring Devices
for Industrial and Commercial Environments
Devices for Factory and Maintenance Use

EXTRA HEAVY DUTY INDUSTRIAL SPECIFICATION GRADE

Description	Catalog Number
20 Amp 120-277V AC; Single-Pole; Lock type switch; back and side wired; straight-key included	**4901L**



4904L

TOGGLE AC MOTOR CONTROLLERS SUITABLE AS DISCONNECTS

				HP Ratings				
Description	**Amp**	**Phase**	**Poles**	**120V AC**	**240V AC**	**480V AC**	**600V AC**	**Catalog Number**
Toggle switch	30	1	2	2	5	10	15	**30002D**
Toggle switch	30	3	3	3	7.5	15	20	**30003D**



30003D

TOGGLE AND ROTARY ENCLOSED SWITCHES SUITABLE AS DISCONNECTS

				HP Ratings				Catalog
Description	**Amp**	**Phase**	**Poles**	**120V AC**	**240V AC**	**480V AC**	**600V AC**	**Number**
NEMA 1 aluminum – toggle	30	1	2	2	5	10	15	**30102D**
NEMA 1 aluminum – toggle	30	3	3	3	7.5	15	20	**30103D**
NEMA 3R aluminum	30	1	2	2	5	10	15	**30302D**
NEMA 3R aluminum	30	3	3	3	7.5	15	20	**30303D**



30102D



30302D

PORTABLE GFCI – SINGLE AND TRIPLE TAP 15A 120V AC

	Catalog Number	
Description	**Automatic Set**	**Manual Set**
2' (60.9 cm) GFCI line cord; single; automatic set	**GFC2A**	**GFC2M**



GFC2A

DELUXE STRAIN RELIEF CORD GRIPS

N.P.T. Hub Size	Straight Male Thread	Grip Dia. Range Inches (cm)
½	**DC3712** **DC5012**	.375-.500 (.95-1.27) .500-.625 (1.27-1.59)
¾	**DC5034** **DC6234**	.500-.625 (1.27-1.59) .625-.750 (1.59-1.90)
1	**DC751** **DC871**	.750-.875 (1.90-2.22) .875-1.000 (2.22-2.54)



DC5012

DUST-TIGHT GRIPS

N.P.S./N.P.T.* Hub Size	Catalog Number	Cable Diameter Range Inches (cm)	Mesh Length Inches (cm)
½ N.P.S.	**BDSR43**	.43-.54 (1.09-1.37)	4¾ (12.06)
¾ N.P.S.	**BDSR54**	.54-.73 (1.37-1.85)	6½ (16.51)
1 N.P.S.	**BDSR73**	.73-.97 (1.85-2.46)	7 (17.78)

Note: *N.P.S. = National Pipe Straight; N.P.T. = National Pipe Taper.



BDSR54

LIQUID-TIGHT GRIPS

Conduit Trade Size	Catalog Number	Mesh Length Inches (cm)	N.P.T. Hub Size
½	**FC50**	4 (10.16)	½
¾	**FC75**	4 (10.16)	¾
1	**FC100**	5 (12.70)	1



FC50

NOTES:

Bryant® Electric • Hubbell Incorporated (Delaware) • 40 Waterview Drive • Shelton, CT 06484 • Phone (800) 323-2792 • FAX (800) 543-0538

Printed in U.S.A. Specifications subject to change without notice.
® is a registered trademarks of Hubbell Incorporated.