Thin wall conduit fittings (for EMT conduit)

Straps, clamps, clampbacks/spacers

CLAMPBACKS/SPACERS – MALLEABLE IRON

Applications:

- Provides space between conduit and mounting surface

Standard materials:

- Stamped steel – ½" to 1½"
- Malleable iron – 2" to 6"

Standard finish:

- Zinc plated

UL File No. E-184283



Cat. #	Size	Unit qty.	Wt. lbs. per 100
CB1[D]	½"	25	8
CB2[D]	¾"	25	10
CB3[D]	1"	25	12
CB4[D]	1¼"	25	21
CB5[D]	1½"	25	42
CB6	2"	10	40
CB7	2½"	10	49
CB8	3"	10	62
CB9	3½"	10	91
CB10	4"	10	110
CB11[G]	5"	5	135
CB12[G]	6"	5	225

[D] Stamped steel.
[G] Not UL Listed.

STRAPS – STEEL GALVANIZED

Two hole

UL File No. E-184283



Cat. #	Size	Unit qty.	Wt. lbs. per 100
497 1	½"	250	2
497 2	¾"	150	3
497 3	1"	100	5
497 4	1¼"	50	8
497 5	1½"	50	13
497 6	2"	25	14
496 9	2½"	25	19
496 10	3"	25	23
496 11	3½"	25	93
496 12	4"	10	108

CLAMPS – MALLEABLE IRON

UL File No. E-184283



Cat. #	Size	Unit qty.	Wt. lbs. per 100
516[E]	2½"	5	104
517[E]	3"	2	120
518[E]	3½"	2	150
519[E]	4"	2	220

[E] Also for use with rigid/IMC conduit.

CLAMPS – STEEL

Applications:

- To support EMT conduit to mounting surface

Heavy gauge

UL File No. E-184283



Cat. #	Size	Unit qty.	Wt. lbs. per 100
200	½"	100	5
201	¾"	100	6
202	1"	100	6
203	1¼"	50	13
204	1½"	25	17
205	2"	25	20
206[G]	2½"	25	64
207[G]	3"	25	71
208[G]	3½"	10	120
209[G]	4"	10	130

[G] Not UL Listed.

 Copyright© 2019 Commercial Products Catalog

Thin wall conduit fittings (for EMT conduit)

Nailing straps – steel

NAILING STRAPS – CAST STEEL

Applications:

- To secure EMT conduit, flexible metallic conduit, armoured cable and metal-clad cable to mounting surface

Standard material:

- Cast steel

Standard finish:


- Zinc plated



Cat. #	Conduit sizes EMT	Conduit sizes Rigid	Unit qty.	Wt. lbs. per 100	Load rating
NS 1	1/2"	3/8"	100	2	25lb.
NS 2	3/4"	1/2"	100	2	30lb.
NS 3	1"	3/4"	100	3	40lb.

Dimensions (in inches):

Cat. #	A	B	C	D
NS 1	3/16	1	1 7/8	3/4
NS 2	3/4	1 1/4	2	15/16
NS 3	3/16	1 1/2	2 1/2	1 1/8



NAILING STRAPS – STAMPED STEEL

Applications:

- To secure EMT conduit

Certifications and compliances:

- UL File No. E-184283

Standard material:


- Pre-galvanized stamped steel



Cat. #	Conduit sizes EMT	Conduit sizes Rigid	Unit Qty.	Wt. lbs. per 100
NSS1	1/2"	3/8"	100	2
NSS2	3/4"	1/2"	100	2
NSS3	1"	3/4"	100	3

Dimensions (in inches):

Cat. #	A	B	C	Radius
NSS1	2.100	1.040	0.080	0.350
NSS2	2.300	1.275	0.080	0.460
NSS3	2.200	1.500	0.080	0.580



 Copyright© 2019 Commercial Products Catalog