Thin wall conduit fittings (for EMT conduit)

Compression type fittings – raintight

COMPRESSION TYPE FITTINGS – RAINTIGHT CONNECTORS

Applications:

- Used to join EMT conduit to a box or enclosure in raintight environments
- The design prevents water seepage into conduit, box or enclosure

Features:

- All steel construction with zinc electroplate finish provides for durable corrosion resistance
- Flat surface on gland nut provides smooth, flat surface for easy wrenching
- Distinct black gland nut provides quick raintight identification
- Integral gasketed compression ring secures and seals for reliable installation
- Interior shoulder conduit stop provides positive seating of conduit inside the body
- Gasket on male threads of box connector seals installation for raintight connection between the box and the connector
- Available in insulated and non-insulated versions to meet any customer preference
- Angled teeth on locknut for secure bite into enclosure
- Extruded locknut with shoulder provides more threads for more secure installation
- Concrete tight
- Threadless
- Standard material: steel
- Standard finish: zinc plated

Certifications and compliances:

- UL Listed
- cUL Listed
- Concrete tight
- Raintight

Straight connectors – insulated – raintight

UL File No. E-22132



Cat. #	Size	Unit qty.	Wt. lbs. per 100
1650RT	½"	50	11
1651RT	¾"	25	17
1652RT	1"	25	23
1653RT	1¼"	10	41
1654RT	1½"	10	50
1655RT	2"	5	67
1656RT	2½"	2	177
1657RT	3"	1	234
1658RT	3½"	1	330
1659RT	4"	1	360

Straight connectors – non-insulated – raintight

UL File No. E-22132



Cat. #	Size	Unit qty.	Wt. lbs. per 100
650RT	½"	50	11
651RT	¾"	25	17
652RT	1"	25	23
653RT	1¼"	10	41
654RT	1½"	10	50
655RT	2"	5	67
656RT	2½"	2	177
657RT	3"	1	234
658RT	3½"	1	280
659RT	4"	1	360

Couplings – raintight

UL File No. E-22132



Cat. #	Size	Unit qty.	Wt. lbs. per 100
660RT	½"	50	14
661RT	¾"	25	21
662RT	1"	25	28
663RT	1¼"	10	49
664RT	1½"	10	60
665RT	2"	5	79
666RT	2½"	2	187
667RT	3"	1	245
668RT	3½"	1	390
669RT	4"	1	485