

The KwikWire™ Hanging System is a flexible indoor replacement for jack chain and all thread rod that will help reduce your hanging time.

- Installs up to 50% faster - can quickly wrap around beams with no drilling required
- Simple height adjustments are made by releasing the clamp's adjustment pin - no tools required
- Aesthetic appeal - blends in with upper structural supports
- Compatible with many fastener, anchor, and hanger products
- Ideal for sloped ceiling applications - will support loads at up to a 60° angle from vertical
- 2 sku's cover a wide range of application requirements






KwikWire Clamps



- KwikWire™ system replaces jack chain or ATR to support lighting, ductwork, cable tray, etc.
- Can be quickly installed around beams - No drilling required.
- Ideal for sloped ceilings - can hang objects at up to 60° angles.
- Simple height adjustments are made by releasing locking tab, no tools required.
- Spools of wire can be cut to length in field, helping reduce waste and up front planning.

UPC/Part Number	Catalog Number	For Use With Wire Rope Diameters	Box Qty.
78205140719	**BKC100**	1/16" & 3/32"	100
78205140723	**BKC200-1**	3/32", 1/8" & 3/16"	50



1. Pass the wire through the KwikWire Clamp.
2. Loop wire through/around support.
3. Pass wire back through KwikWire Clamp.
4. Push wire through clamp leaving 2" to 3" tail, then apply tension on wire.
5. To adjust, remove tension and pull wire slightly to disengage teeth, slide adjustment pin in direction shown by arrow to release wire.

KwikWire Clamp Working Loads*

Clamp Part No.	Wire Rope Dia.	Lbs. Safety Factor 4
BKC100	1/16"	0-75
	3/32"	25-150
BKC200-1	3/32"	25-150
	1/8"	25-250
	3/16"	50-500

** Working loads shown are for hanging vertically. For suspending at 15°, 30°, 45° or 60° angles from vertical use the following percentage of the working loads from the chart: 15° = 96%, 30° = 86%, 45° = 70%, 60° = 50%*

Read safety/installation instruction sheets in packages before use.

KwikWire Hanging System

KwikWire Wire Rope





BKW Series

UPC/Part Number	Catalog Number	Wire Diameter	Working Load - lbs.	Spool Qty.
78205140725	**BKW063** (1)	1/16"	96	500 ft.
78205140727	**BKW094** (1)	3/32"	184	500 ft.
78205140733	**BKW125** (1)	1/8"	340	500 ft.
78205140734	**BKW188** (2)	3/16"	840	250 ft.

(1) Wire rope construction Type 7 x 7
(2) Wire rope construction Type 7 x 19
Uncoated Galvanized Wire



7 x 7



7 x 19

KwikPak Kit



- KwikPak™ includes a supply of kwik-clamps and a spool of wire rope.
- KwikPak are shipped in a specially designed dispenser box to ease field cutting of wire.

UPC/Part Number	Catalog Number	Kit Includes	Box Qty.
78205140749	**BKP10063**	BKC100 (100 pcs.) 1/16"Ø Wire Rope (500 ft.)	1
78205140751	**BKP10094**	BKC100 (100 pcs.) 3/32"Ø Wire Rope (500 ft.)	1
78205140761	**BKP20125**	BKC200-1 (50 pcs.) 1/8"Ø Wire Rope (500 ft.)	1
78205140763	**BKP20188**	BKC200-1 (50 pcs.) 3/16"Ø Wire Rope (500 ft.)	1

KwikWire Hanger

















- KwikWire™ the versatility of a bolt with an adjustable wire rope solution.
- Can be quickly installed in existing anchors or metal brackets with a nut.
- Ideal for supporting light fixtures, wire basket cable tray, HVAC ducts, and sign/banner supports.
- See above for wire rope spools.

UPC/Part Number	Catalog Number	Thread Size	Wire Rope Diameter	Load SF5	Box Qty.
78205158764	**BKF100-4**	1/4"-20	1/16" 3/32"	45 lbs. 90 lbs.	100
78205158765	**BKF100-6**	3/8"-16	1/16" 3/32"	45 lbs. 90 lbs.	100

1. Screw KwikWire Hanger into installed hanger support.
2. Push wire up through the bottom of KwikWire Hanger.
3. Continue pushing through until 1/4" minimum is extending out the side of the KwikWire Hanger.
4. To adjust up - pull or push more wire through KwikWire Hanger.
5. To adjust down - push up on bottom of KwikWire Hanger and allow wire to feed down.
6. When hanging the wire is complete, cut off any excess cable wire if desired.

Read safety/installation instruction sheets in packages before use.

KwikWire Accessories



BKL Series

Loop Termination

- Available as a wire rope with loop termination only or as a ready-to-use kit with a BKC100 clamp.
- Available in lengths of 40", 80", 120", 180", 240", and 360".



BKH Series



BKYH Series

Single & "Y" Style Hook Termination

- Hook designed to accept up to ⅜" diameter wire.
- Available as a wire rope with hook termination only or as a ready-to-use kit with a BKC100 clamp.
- Available in lengths of 40", 80", 120", 180", 240", and 360".
- Available in single, double (Y), and triple (3) leg styles.



BKT Series



BKYT Series

Single & "Y" Style Toggle Termination

- Available as a wire rope with toggle termination only or as a ready-to-use kit with a BKC100 clamp.
- Available in lengths of 40", 80", 120", 180", 240", and 360".
- Available in single, double (Y), and triple (3) leg styles.
- All triple (3) leg styles are non-stock, consult us for lead times.

KwikWire Accessories

KwikWire System Recommendations:

- Do not exceed the safe working load of the products shown in their charts.
- All characteristics of KwikWire™ must be used with wire supplied by Eaton's B-Line Division.
- Do not use for overhead lifting or hoisting.
- Do not use if cable or components are visibly distorted or worn, remove damaged cable end prior to inserting in KwikWire™ Clamp.
- Do not paint cable near working area of KwikWire Clamp connector.
- Do not apply lubricant.
- Keep product clean and free of dirt.
- Do not use on coated wire rope.
- Do not use in chlorinated or caustic atmospheres.
- For use in dry locations.
- Cooper's BKCC tool is recommended for cutting wire rope to prevent fraying.
- For use on vertical applications only.



BKB Series

Bolt Loop Termination

- Ideal for use with ARS, ARC, ADI, ACPW, or ACPD anchors.
- Available as a wire rope with bolt termination only or as a ready-to-use kit with a BKC100 clamp.
- Available in lengths of 40", 80", 120", 180", 240", and 360".
- Available in single, double (Y), and triple (3) styles.
- All double (Y) and triple (3) styles are non-stock, consult Eaton's B-Line series representative for lead times.




BKA Series

Angle Bracket Termination

- Available as a wire rope with angle bracket termination only or as a ready-to-use kit with a BKC100 clamp.
- Available in lengths of 40", 80", 120", 180", 240", and 360".

For additional options, refer to KwikWire Brochure.



BKCP



B601-62



BKCC

UPC/Part Number	Catalog Number	Description	Box Qty.
78205140766	**BKCP**	Air Duct Corner Protector	100
78101156059	**B601-62**	Air Duct Support	50
78205140297	**BKCC** *	Wire Rope Cutter	1

DANGER **Never use cutters on energized circuits, wire, or cable. Doing so could result in death, personal injury or property damage.**

Note: Additional accessories include BE Series (page 79) and BF Series (pages 93, 94 & 96).

* Not for use of cutting 3/16" diameter cable.

Application Photos







Read safety/installation instruction sheets in packages before use.