AC/MC fittings

Quick-Lok™ connectors

QUICK-LOK™ CONNECTORS – STEEL

Features:

- No locknut required
- Single unit or duplex construction with captive clamp
- Connects 50 MC, AC and flex RW cable sizes with just three fittings
- Easy to install: tilt, insert and snap down
- Single unit construction eliminates loose component parts; integral green plastic insulated throat bushing provides maximum protection for wire installation

Standard material:


- Tubular steel

Standard finish:

- Zinc plated

UL File No. E-19188





		Cable size				
Cat. #	**Trade size**	**HCF**	**Aluminum and steel RWFMC/FMC**	**Cable dia. range**	**Unit qty.**	**Wt. lbs. per 100**
QLK50S❷❶	½" single	14/2 to 10/3	⅜"	0.385" - 0.600"	50	8
QLK50D❷❶	½" duplex	14/2 to 10/3	½"	0.433" - 0.600"	25	10
QLK75❷❶	¾"	10/3 to 6/3	⅜" & ½"	0.550" - 0.850"	25	14

❷UL approved for use with aluminum interlocking grounding metal-clad cable, Type MCIA (Southwire MCAP™).
MCAP™ is a registered trademark of Southwire company.
❶UL approved for use with MC-PCS cable.

 Copyright© 2019 Commercial Products Catalog