


Midget One-Hole Straps — Steel

TRADE SIZE	HALEX PART #	CTN/CASE QTY	CTN/CASE WT (LBS)	DIMENSIONS (IN INCHES) A	B
3/16″ O.D.	**26212**	20 BAGS OF 50 PCS	3	0.73	0.33
1/4″ O.D.	**26214**	10 BAGS OF 50 PCS	3	0.95	0.50



APPLICATION: INDOORS OR OUTDOORS. Use to secure bare solid copper wire to a working surface. **MATERIAL:** Steel, Zinc Electro-Plate.




One-Hole Service-Cable Straps — Steel

TRADE SIZE	HALEX PART #	CTN/CASE QTY	CTN/CASE WT (LBS)	DIMENSIONS (IN INCHES) A	B	C	D
FITS NM CABLE							
#12/2-#14/2	**62171B**	100/1000	1/10	0.585	0.300	1.322	0.500
FITS SE AND SEU CABLE							
3#8-3#4	**62191B**	100/1000	2/20	0.875	0.375	1.688	0.562
3#3-3#2	**62192B**	100/1000	2/20	1.000	0.500	1.937	0.562
3#1-3#2/0	**62193B**	25/250	1.8/17.5	1.250	0.750	2.500	1.000
3#3/0-3#4/0	**62194B**	25/250	2/20	1.500	0.812	2.812	1.000



APPLICATION: INDOORS OR OUTDOORS. Use to secure service entrance cable (SEU, SE) to a wood, masonry or similar surface. **MATERIAL:** Steel, Zinc Electro-Plate.



Two-Hole Service-Cable Straps — Steel

TRADE SIZE	HALEX PART #	CTN/CASE QTY	CTN/CASE WT (LBS)	DIMENSIONS (IN INCHES) A	B	C	D
FITS SE AND SEU CABLE							
3#8-3#4	**62291B**	100/1000	3/30	0.875	0.375	2.375	0.750
3#3-3#2	**62292B**	100/1000	3/30	1.000	0.500	2.750	0.750
3#1-3#2/0	**62293B**	25/250	1/10	1.250	0.750	3.188	0.750
3#3/0-3#4/0	**62294B**	25/250	1/10	1.500	0.812	3.500	0.750



APPLICATION: INDOORS OR OUTDOORS. Use to secure service entrance cable (SEU, SER) to a wood, masonry or similar surface. **MATERIAL:** Steel, Zinc Electro-Plate.



Water-Tight Connectors — Zinc Die Cast

TRADE SIZE	HALEX PART #	CTN/CASE QTY	CTN/CASE WT (LBS)	DIMENSIONS (IN INCHES) A (MIN)	A (MAX)	B (MIN)	B (MAX)	C
COMPRESSION TYPE (KO/CABLE SIZE)								
1″ / 3#6	**07210**	10	4	0.425	0.465	0.665	0.730	
1″ / 3#4	**07310B**	10/100	4/34	0.465	0.545	0.730	0.860	
1 1/4″ / 3#3	**08112B**	10/100	5/52	0.522	0.562	0.860	0.920	
1 1/4″ / 3#2	**08212B**	10/100	5/52	0.550	0.590	0.920	0.970	
1 1/4″ / 3#1	**08312**	10	5	0.590	0.670	0.970	1.135	
1 1/2″/3#1/0	**09115B**	5/50	3/33	0.670	0.725	1.135	1.210	
1 1/2″/3#2/0	**09215**	5	3	0.710	0.750	1.205	1.245	
2″ / 3#2/0	**10220B**	5/50	4/44	0.710	0.750	1.215	1.250	
2″ / 3#4/0	**10420B**	5/50	4/44	0.845	0.910	1.425	1.550	
2″ / 3#4/0	**10520B**	5/50	4/44	0.910	1.005	1.550	1.600	
FITS UF CABLE ONLY: #14/2, #12/2								
1/2″	**06605B**	25/250	4.3/42.5	0.10	0.22	0.48	0.44	1.20
FITS UF CABLE: #14/3, #12/3								
3/4″	**06607B**	25/250	6.5/65	0.18	0.22	0.80	0.66	1.27



APPLICATION: INDOORS OR OUTDOORS. Use to secure SE/SEU cable to a metal enclosure. Use to connect UF cable to a waterproof box with a threaded hub or thru-hole (ko). **MATERIAL:** Zinc Die Cast. **PURPOSE:** For SE/SEU Flat Style cable; 2 insulated conductors, 1 bare. **CERTIFICATIONS:** TO UL AND CSA REQUIREMENTS.