


Liquid-Tight Connectors — Zinc Die Cast

ONE-PIECE

TRADE SIZE	HALEX PART #	CTN/CASE QTY	CTN/CASE WT (LBS)	DIMENSIONS (IN INCHES) A	B	C
1/2″	**06305B**	25/100	3.5/14	1.661	0.521	1.543
3/4″	**06307B**	10/100	2.1/21	1.721	0.521	1.790
WITH INSULATED THROAT						
1/2″	**86305B**	25/100	3.5/14	1.741	0.591	1.543
3/4″	**86307B**	10/100	2.1/21	1.801	0.600	1.790




APPLICATION: INDOORS OR OUTDOORS. Use to connect flexible metallic or type B non-metallic liquid-tight conduit to a steel outlet box or other metal enclosure or hub. **MATERIAL:** Zinc Die Cast. **FEATURES:** New one-piece design allows for quick and easy installation. Push in and twist conduit counter-clockwise until seated. Tighten screw to 35 in-lbs. and install into enclosure. It's that easy! **CERTIFICATIONS:** TO UL AND CSA REQUIREMENTS.



Liquid-Tight Connectors — Zinc Die Cast

MULTI-PIECE

TRADE SIZE	HALEX PART #	CTN/CASE QTY	CTN/CASE WT (LBS)	DIMENSIONS (IN INCHES) A	B	C
3/8″(1/2 ko)	**16203B**	25/100	5/20	1.32	0.50	1.18
1/2″	**16205B**	25/100	4.3/17	1.40	0.50	1.29
3/4″	**16207B**	10/100	2.5/25	1.45	0.50	1.57
1″	**16210B**	10/100	4.4/44	2.06	0.58	1.81
1 1/4″	**16212B**	4/40	2.7/26.8	2.06	0.61	2.18
1 1/2″	**16215B**	2/20	1.8/18.4	2.09	0.63	2.51
2″	**16220B**	2/20	2.8/28	2.15	0.63	3.03
WITH INSULATED THROAT						
3/8″(1/2 ko)	**96203B**	25/100	5/20	1.37	0.50	1.18
1/2″	**96205B**	25/100	4.3/17	1.45	0.50	1.29
3/4″	**96207B**	10/100	2.5/25	1.50	0.50	1.57
1″	**96210B**	10/100	4.4/44	2.11	0.63	1.81
1 1/4″	**96212B**	4/40	2.7/26.8	2.11	0.66	1.81
1 1/2″	**96215B**	2/20	1.8/18.4	2.11	0.68	2.18
2″	**96220B**	2/20	2.8/28	2.14	0.68	2.51
2 1/2″	**96225B**	1	2.7	2.20	0.68	3.03
3″	**96230B**	1	3.06	4.05	1.01	4.34
3 1/2″	**96235B**	1	3.80	4.30	1.05	4.78
4″	**96240B**	1	4.31	4.75	1.05	5.19




APPLICATION: INDOORS OR OUTDOORS. Use to connect flexible metallic or type B non-metallic liquid-tight conduit to a steel outlet box or other metal enclosure or hub. **MATERIAL:** Zinc Die Cast. **MISC:** 3/8″ size fits 1/2″ knockout. **CERTIFICATIONS:** TO UL AND CSA REQUIREMENTS.



90° Liquid-Tight Connectors — Zinc Die Cast

ONE-PIECE

TRADE SIZE	HALEX PART #	CTN/CASE QTY	CTN/CASE WT (LBS)	DIMENSIONS (IN INCHES) A	B	C
1/2″	**06805B**	25/100	4.6/18.4	2.47	1.520	0.521
3/4″	**06807B**	10/100	2.8/28	2.761	1.695	0.521



APPLICATION: INDOORS OR OUTDOORS. Use to connect flexible metallic or type B non-metallic liquid-tight conduit to a steel outlet box or other metal enclosure or hub. **MATERIAL:** Zinc Die Cast. **FEATURES:** New one-piece design allows for quick and easy installation. Push in and twist conduit counter-clockwise until seated. Tighten screw to 35 in-lbs. and install into enclosure. It's that easy! **CERTIFICATIONS:** TO UL AND CSA REQUIREMENTS.




• Image shown is for 1/2" - 2". 2 1/2" - 4" has four screws.

Set-Screw Connectors — Steel

TRADE SIZE	HALEX PART #	CTN/CASE QTY	CTN/CASE WT (LBS)	DIMENSIONS (IN INCHES) A
2 1/2″	**62725B**	12	15	3.24
3″	**62730B**	12	21	3.74
3 1/2″	**62735B**	6	13	3.99
4″	**62740B**	6	15	4.24
WITH INSULATED THROAT				
2 1/2″	**82725B**	12	15	
3″	**82730B**	12	21	
3 1/2″	**82735B**	6	13	
4″	**82740B**	6	15	

APPLICATION: INDOORS. Use to connect threadless Rigid or IMC conduit to a steel outlet box or other metal enclosure. **MATERIAL:** Steel-Zinc Electro-Plate. **MISC:** 2 1/2″-4″ can be used for EMT conduit also. **CERTIFICATIONS:** TO UL AND CSA REQUIREMENTS.



• Image shown is for 1/2" - 2". 2 1/2" - 4" has two screws.




• Image shown is for 1/2" - 2". 2 1/2" - 4" has four screws.

Set-Screw Connectors — Zinc Die Cast

TRADE SIZE	HALEX PART #	CTN/CASE QTY	CTN/CASE WT (LBS)	DIMENSIONS (IN INCHES) A	B
2 1/2″	**12125B**	12	9.96	3.03	1.00
3″	**12130B**	12	12	3.37	1.06
3 1/2″	**12135B**	10	12.8	3.58	1.09
4″	**12140B**	6	9.36	3.75	1.09
WITH INSULATED THROAT					
2 1/2″	**92125B**	12	9.96	3.08	1.05
3″	**92130B**	12	12	3.42	1.11
3 1/2″	**92135B**	10	12.8	3.63	1.14
4″	**92140B**	6	9.36	3.80	1.14

APPLICATION: INDOORS. Use to connect threadless Rigid or IMC conduit to a steel outlet box or other metal enclosure. **MATERIAL:** Zinc Die Cast. **MISC:** 2 1/2″-4″ can be used for EMT conduit also. **CERTIFICATIONS:** TO UL AND CSA REQUIREMENTS.



• Image shown is for 1/2" - 2". 2 1/2" - 4" has two screws.




• Image shown is for 1/2" - 2". 2 1/2" - 4" has four screws.

Set-Screw Couplings — Zinc Die Cast

TRADE SIZE	HALEX PART #	CTN/CASE QTY	CTN/CASE WT (LBS)	DIMENSIONS (IN INCHES) A	B
2 1/2″	**12225B**	12	9.12	3.99	3.30
3″	**12230B**	12	12.36	4.55	3.94
3 1/2″	**12235B**	10	14.76	4.92	4.45
4″	**12240B**	6	9.66	5.24	4.97

APPLICATION: INDOORS. Use to join two lengths of threadless Rigid or IMC conduit together. **MATERIAL:** Zinc Die Cast. **MISC:** 2 1/2″-4″ can be used for EMT conduit also. **CERTIFICATIONS:** TO UL AND CSA REQUIREMENTS.



• Image shown is for 1/2" - 2". 2 1/2" - 4" has four screws.



• Image shown is for 1/2" - 2". 2 1/2" - 4" has four screws.

Set-Screw Couplings — Steel

TRADE SIZE	HALEX PART #	CTN/CASE QTY	CTN/CASE WT (LBS)	DIMENSIONS (IN INCHES) A	B
2 1/2″	**62825B**	12	17.5		
3″	**62830B**	12	25		
3 1/2″	**62835B**	6	14		
4″	**62840B**	6	17		

APPLICATION: INDOORS. Use to join two lengths of threadless Rigid or IMC conduit together. **MATERIAL:** Steel-Zinc Electro-Plate. **MISC:** 2 1/2″-4″ can be used for EMT conduit also. **CERTIFICATIONS:** TO UL AND CSA REQUIREMENTS.