


Flush Rectangular Non-Metallic Floor Boxes with Non-Metallic Covers, for Use In Concrete Floor


ScrubShield® cULus
Complies with UL514A

Style	1-Gang	2-Gang	3-Gang
	 PFBRG1*	 PFBRG2	 PFBRG3
Min. Depth of Pour	3.00" (76.2)	3.00" (76.2)	3.00" (76.2)
Adjustability	Fully	Fully	Fully
Cubic Inch (cm^3) Capacity per Gang	14.3 cu. in. (234.3 cm^3) per 1" depth	14.3 cu. in. (234.3 cm^3) per 1" depth	14.3 cu. in. (234.3 cm^3) per 1" depth
Dimensions – A	6.00" (152.4)	6.00" (152.4)	6.00" (152.4)
Dimensions – B	3.60" (91.4)	6.80" (172.7)	10.04" (255.0)
Dimensions – C	5.47" (138.9)	5.47" (138.9)	5.47" (138.9)
Dimensions – D	6.90" (175.3)	6.90" (175.3)	6.90" (175.3)
Dimensions – E	5.41" (137.4)	8.56" (221.4)	11.75" (298.4)
Hubs	(4) 1-1/4"	(6) 1-1/4"	(8) 1-1/4"
Reducers	(4) 1" to 3/4" and (4) 1-1/4" to 1"	(6) 1" to 3/4" and (6) 1-1/4" to 1"	(8) 1" to 3/4" and (8) 1-1/4" to 1"
Concrete Cover Included	✓	✓	✓
Closure Plugs Included	✓	✓	✓
Low Voltage Barrier**	–	(1) Removable	(2) Removable

Note: UL File Number E92074.
**Suitable for single service applications only.*
***Replacement low voltage barriers, 5 pack, catalog number PRFBLVDPK5.*

Flush Rectangular Non-Metallic Covers and Flanges*

Required Components for Carpet Applications						
Carpet Flanges				Cover with Duplex and Style Line® decorator inserts included		
Number of Gangs Dimensions	1-Gang 6.00" x 4.88"	2-Gang 6.00" x 8.13"	3-Gang 6.00" x 11.35"	One Required per Gang 4.15" x 2.97"		
Black Brown Gray Ivory	**PFBRFBL1** **PFBRFBR1** **PFBRFGY1** **PFBRFI1**	**PFBRFBL2** **PFBRFBR2** **PFBRFGY2** **PFBRFI2**	**PFBRFBL3** **PFBRFBR3** **PFBRFGY3** **PFBRFI3**	**PFBR826BLA** **PFBR826BRA** **PFBR826GYA** **PFBR826IA**		
				 Cover	 Duplex Insert	 Style Line® Decorator Insert

Required Components for Tile Applications		
Mounting Collar	Cover Frame	Cover with Duplex and Style Line decorator inserts included
One Required per Gang	One Required per Gang Dim. 4.47" x 3.25"	One Required per Gang 4.15" x 2.97"
PFBRMC	**PFBRFRA**	**PFBR826GYA**
		 Cover  Duplex Insert  Style Line Decorator Insert

*Note: *Flush rectangular non-metallic covers and flanges are UL listed only. Not CSA certified. COVER LOAD RATING; Non-metallic covers and flanges 300 lbs. Load applied through a 3 in. (76) mandrel at the center of the cover.*

Dimensions in Inches (mm)