
Flush Rectangular Non-Metallic Floor Boxes with Non-Metallic Covers, for Use In Concrete Floor

ScrubShield® Complies with UL514A

Style	1-Gang	2-Gang	3-Gang
	 PFBRG1*	 PFBRG2	 PFBRG3
Min. Depth of Pour	3.00" (76.2)	3.00" (76.2)	3.00" (76.2)
Adjustability	Fully	Fully	Fully
Cubic Inch (cm^3) Capacity per Gang	14.3 cu. in. (234.3 cm^3) per 1" depth	14.3 cu. in. (234.3 cm^3) per 1" depth	14.3 cu. in. (234.3 cm^3) per 1" depth
Dimensions – A	6.00" (152.4)	6.00" (152.4)	6.00" (152.4)
Dimensions – B	3.60" (91.4)	6.80" (172.7)	10.04" (255.0)
Dimensions – C	5.47" (138.9)	5.47" (138.9)	5.47" (138.9)
Dimensions – D	6.90" (175.3)	6.90" (175.3)	6.90" (175.3)
Dimensions – E	5.41" (137.4)	8.56" (221.4)	11.75" (298.4)
Hubs	(4) 1-1/4"	(6) 1-1/4"	(8) 1-1/4"
Reducers	(4) 1" to 3/4" and (4) 1-1/4" to 1"	(6) 1" to 3/4" and (6) 1-1/4" to 1"	(8) 1" to 3/4" and (8) 1-1/4" to 1"
Concrete Cover Included	✓	✓	✓
Closure Plugs Included	✓	✓	✓
Low Voltage Barrier**	–	(1) Removable	(2) Removable

Note: UL File Number E92074.
**Suitable for single service applications only.*
***Replacement low voltage barriers, 5 pack, catalog number PRFBLVDPK5.*


Rectangular Metal Covers and Flanges

Required Components for Flush Tile Applications

Adapter Collar (One required per gang)

Gray **PFBRAC** 

Adapter Frame with Grounding Wire (One required per gang) Dim. 4.36" x 3.20" x 0.30"

Brass Aluminum **S5017GR SA5017GR** 

Flush Rectangular Metal Covers and Flanges




Required Components for Flat Flange Applications

Adapter Collar (One required per gang)

Gray **PFBRAC** 

Flat Flanges*

Flat Flange Height 0.125"

Number of Gangs Dimensions	1-Gang 6.00" x 4.85"	2-Gang 6.00" x 8.13"	3-Gang 6.00" x 11.34"
Brass, square edge Aluminum, square edge Brass, beveled edge Aluminum, beveled edge	**SB3083W SA3083W SB3083WB SA3083WB** 	**SB3084W SA3084W SB3084WB SA3084WB** 	**SB3085W SA3085W SB3085WB SA3085WB** 

*Note: *Flange applications; square edge for carpet and recessed, beveled edge for use on hard finished surfaces.*

Covers – One Required per Gang†

Brass Aluminum Dimensions 4.15" x 2.99"	**S3825 SA3825**	**S3625 SA3625**	**S3625TR SA3625TR**	**S3826 SA3826**	**S2425 SA2425**	**S2625 SA2625**	**S2825** –	**S3425** –	**S3813 SA3813**
									
	Duplex Flap	Duplex Screw	Tamper Resistant Duplex Screw	Style Line® Decorator Opening	2-1/8" x 3/4" Combination	2-1/8" x 1" Combination	2-1/8" Single Receptacle	2-3/8" Single Receptacle	Blank

Note: †COVER LOAD RATING; Metallic covers and flanges 2,000 lbs. with 2x safety factor Load applied through a 3 in. (76) mandrel at the center of the cover.

Dimensions in Inches (mm)