
Flush Rectangular Cast Iron Floor Boxes with Metal Covers, for Use In Concrete Floor

ScrubShield® c UL us
Complies with UL514A



Style	Cast Iron					
	1-Gang Deep	2-Gang Deep	3-Gang Deep	1-Gang Shallow	2-Gang Shallow	3-Gang Shallow
						
Catalog Numbers	**FB4133***	**FB4233**	**FB4333**	**FB4114***	**FB4214**	**FB4314**
Cover Frame Material	Thermoplastic	Thermoplastic	Thermoplastic	Thermoplastic	Thermoplastic	Thermoplastic
Min. Depth of Pour	3.50" (95.3)	3.50" (95.3)	3.50" (95.3)	2.00" (50.8)	2.00" (50.8)	2.00" (50.8)
Adjustability	Fully	Fully	Fully	Semi	Semi	Semi
Before Pour External Height Adjustment	1.25" (31.8)	1.25" (31.8)	1.25" (31.8)	1.25" (31.8)	1.25" (31.8)	1.25" (31.8)
After Pour Internal Height Adjustment	.875" (22.2)	.875" (22.2)	.875" (22.2)	–	–	–
Cubic Inch (cm^3) Capacity per Gang	33.0 (540.8)	36.5 (598.2)	36.5 (598.2); 34.8 (570.3) center gang	16.0 (262.2)	16.0 (262.2)	16.0 (262.2)
Dimensions – A	3.42" (87.0)	3.40" (86.4)	3.40" (86.4)	2.03" (51.4)	2.05" (51.9)	2.06" (52.2)
Dimensions – B	4.85" (123.2)	4.91" (124.7)	4.91" (124.7)	5.66" (143.7)	5.46" (138.7)	5.46" (138.7)
Dimensions – C	4.85" (123.2)	8.13" (206.5)	11.41" (289.8)	4.38" (111.3)	7.50" (190.4)	10.71" (272.0)
Dimensions – D	4.32" (109.7)	4.32" (109.7)	4.32" (109.7)	4.32" (109.7)	4.32" (109.7)	4.32" (109.7)
Dimensions – E	3.20" (81.3)	6.42" (163.0)	9.64" (244.8)	3.20" (81.3)	6.42" (163.0)	9.64" (244.8)
Threaded Hubs	(4) 1"	(6) 1"	(8) 1"	(4) 3/4"	(4) 3/4"	(6) 3/4"
Concrete Cover Included	✓	✓	✓	✓	✓	✓
Closure Plugs Included	✓	✓	✓	✓	✓	✓
1" to 3/4" Threaded Reducer	2 Each	4 Each	4 Each	–	–	–
Low Voltage Barrier	–	(1) Removable	(2) Removable	–	Non-Removable	Non-Removable

Note: UL File Number E92074.
**Suitable for single service applications only.*



Flush Rectangular Covers Flanges

Required Components for Flush Tile or Finished Concrete Applications

Brass Aluminum	**S5017GR** **SA5017GR**		Adapter Frame with Grounding Wire (One required per gang) Dim. 4.36" x 3.20" x 0.30".

Flat Flanges*

Flat Flange Height 0.125"

Number of Gangs Dimensions	1-Gang 6.00" x 4.85"	2-Gang 6.00" x 8.13"	3-Gang 6.00" x 11.34"
Brass, square edge Aluminum, square edge Brass, beveled edge Aluminum, beveled edge	**SB3083W** **SA3083W** **SB3083WB** **SA3083WB** 	**SB3084W** **SA3084W** **SB3084WB** **SA3084WB** 	**SB3085W** **SA3085W** **SB3085WB** **SA3085WB** 

*Note: *Flange applications; square edge for carpet and recessed, beveled edge for use on hard finished surfaces*

Covers – One Required per Gang†

Brass Aluminum Dimensions 4.15" x 2.99"	**S3825** **SA3825**	**S3625** **SA3625**	**S3625TR** **SA3625TR**	**S3826** **SA3826**	**S2425** **SA2425**	**S2625** **SA2625**	**S2825** –	**S3425** –	**S3813** **SA3813**
									
	Duplex Flap	Duplex Screw	Tamper Resistant Duplex Screw	Style Line® Decorator Opening	2-1/8" x 3/4" Combination	2-1/8" x 1" Combination	2-1/8" Single Receptacle	2-3/8" Single Receptacle	Blank

Note: †COVER LOAD RATING; Metallic covers and flanges 2,000 lbs. with 2x safety factor Load applied through a 3 in. (76) mandrel at the center of the cover.
Dimensions in Inches (mm)