Residential Round Non-Metallic Floor Box offers an economical solution for electrical power or a combination of power and voice/data applications. Designed specifically for slab-on-grade installation. Quick and easy installation is assured using a push in place leveling system. UL Listed.



RF406BK
with RF400

Features

After the box has been secured in concrete, cut for height, apply PVC glue and push the cover assembly into the box. No fasteners or adjustment screws required.

- 4 inch minimum concrete pour
- Removable neoprene gaskets allow for independent use of either side of the receptacle with the cover closed
- Self height and leveling ring, no adjustments
- Pre-assembled flange, cover and leveling ring for quick installation
- Parallel PVC hubs for 1 inch and 3/4 inch conduit
- Recessed GFCI/decorator opening
- Tamper-Resistant duplex receptacle included
- UL Listed floor box

Floor Boxes for Concrete Floors

Description	Rating	Material/Color	Catalog Number
Flange and Hinged Door Cover Assembly. Includes tamper-resistant duplex receptacle, gasket, floor leveling PVC ring, high impact and chemically resistant nylon. Factory pre-assembled for easy drop-in installation.	15A 125V NEMA 5-15R	Brushed Aluminum Black Aluminum Brushed Brass Plated Solid Brass Almond Black Chestnut Brown Gray	**RF406ALU** **RF406BLK** **RF406BP** **RF406BR** **RF406AL** **RF406BK** **RF406BN** **RF406GY**
Flush fit cover for hardwood and tile floors (similar to above).		Solid Brass	**RF409BR**
PVC Floor Box with Concrete Protective Cover. Accepts 3/4 in. and 1.0 in. schedule 40 and schedule 80 PVC conduit. Includes round box (47/8 in. diameter x 6.0 in. deep), four reducers, closure plugs, and concrete cover with locator flag.		Gray	**RF400**
Hinged Nylon Replacement Door Cover. Includes neoprene gasket to seal plug openings. Replacement cover for RF406 series.		Solid Brass Almond Black	**RF407BR** **RF407AL** **RF407BK**
Low Voltage Divider. For use in PVC box RF400, when JLOAD Multimedia Outlet is used.		Gray	**RF408**



RF406ALU



RF409BR

Adjustable Non-Metallic Concrete Floor Box Stand

Description	Color	Catalog Number
PVC floor box stand, adjusts up to 4 inches.	Gray	**PFBSTANDGY**



RF408

JLOAD® Multimedia Outlet - See page BB-31 for Features



15A 125V
NEMA 5-15R
UL/CSA



20A 125V
NEMA 5-20R
UL/CSA

Description	Color	Tamper-Resistant	Tamper-Resistant
JLOAD Multimedia Outlet. Specifically designed to provide power, Cat. 5e and coaxial in a single gang box. Requires Low Voltage Divider RF408 when used in PVC Box RF400. Includes decorator frame, one Cat. 5e, one F-connector and one power receptacle 125V with voltage dividers*.	Black Gray Ivory Light Almond White	**RJ650BKTR** **RJ650GYTR** **RJ650ITR** **RJ650LATR** **RJ650WTR**	**RJ620BKTR** **RJ620GYTR** **RJ620ITR** **RJ620LATR** **RJ620WTR**
JLOAD Multimedia Outlet Includes decorator frame with two open ports for custom configuration and one power receptacle 125V with voltage dividers*.	Black Gray Ivory Light Almond White	**RJ65BKTR** **RJ65GYTR** **RJ65ITR** **RJ65LATR** **RJ65WTR**	**RJ62BKTR** **RJ62GYTR** **RJ62ITR** **RJ62LATR** **RJ62WTR**



PFBSTANDGY



RJ650BKTR

*Note: *Dividers provided for use with the RJ600, RF515 series and RU200 series boxes. RF408 required for use with the RF400 series floor boxes. See page BB-10 for snap fit inserts. See pages BB-25 to BB-30 for floor boxes and under cabinet power distribution options. See page Tech-10 for Tamper-Resistant description.*

Dimensions in Inches (mm)