## For 15 and 20 Ampere, 125 and 250 Volts and 277 Volts AC Devices

### Wallplates, 1-Gang

| Description | Color | Duplex Receptacle | Style Line® Receptacle | Single Receptacle Plate 1.40 in. (35.6) Dia. |
|---|---|---|---|---|
| Thermoplastic, smooth. | Black<br>Brown<br>Gray<br>Ivory<br>Light Almond<br>Orange<br>Red<br>White | **P8BK**<br>**P8**<br>**P8GY**<br>**P8I**<br>**P8LA**<br>**P8OR**<br>**P8R**<br>**P8W** | **P26BK**<br>**P26**<br>**P26GY**<br>**P26I**<br>**P26LA**<br>—<br>**P26R**<br>**P26W** | **P7BK**<br>**P7**<br>**P7GY**<br>**P7I**<br>**P7LA**<br>—<br>**P7R**<br>**P7W** |
| Stainless steel 302/304, .035 in. (0.9) horizontal brushed finish. | | **SS8** | **SS26** | **SS7** |
| Brass .04 in. (1.0), horizontal brushed finish. | | **SB8** | **SB26** | **SB7** |
| Aluminum .05 in. (1.3), horizontal brushed finish. | | **SA8** | — | **SA7** |



**P8**



**P26I**



**SS7**

### Weatherproof Covers

| Description | Duplex Receptacle | Single Receptacle Plate 1.40 in. (35.6) Dia. |
|---|---|---|
| RTP, gray, for FS/FD box mounting. | **HBL5221** | **HBL7423WO** |
| RTP, yellow, for FS/FD box mounting. | **HBL52CM21** | **HBL74CM23WO** |
| RTP, gray, for device mounting. | **HBL5222** | — |
| RTP, yellow, for device mounting. | **HBL52CM22** | — |
| Cast aluminum for FS/FD box mounting. | **HBL5206WO** | **HBL7420** |
| Cast aluminum for device mounting. | **HBL5205WO** | — |

*Note: All weatherproof plates are UL Listed for Wet Locations.*
*Those with suffix WO are listed for use with cover open, all others with cover closed.*
*RTP is an abbreviation for reinforced thermoplastic polyester.*
*See section P for additional information on cover plates.*



**HBL52CM22**



**HBL5206WO**



**HBL7423WO**

*Dimensions in Inches (mm)*