

30A 125V
NEMA L5-30R
UL/CSA

Plugs, receptacles and connectors only.

30A 125V Twist-Lock® Devices

Description	Catalog Number
Yellow Insulgrip® plug has rugged nylon housing and cord grip with range of .36–.93 in. (9–24) that utilizes a unique offset jaws arrangement to provide secure strain relief. **IP20 suitability.**	**HBL26CM11**
Yellow Insulgrip connector body has rugged nylon housing and cord grip with range of .36–.93 in. (9–24) that utilizes a unique offset jaws arrangement to provide secure strain relief.	**HBL26CM13**
Yellow single receptacle has Rynite® body and abuse resistant nylon face. **IP20 suitability.**	**HBL26CM10**



HBL26CM11



HBL26CM13

Boots and Weatherproof Plates

Description	Catalog Number
Yellow Seal-Tite® cover for weatherproofing HBL26CM11 plugs. **IP44 suitability.** Note: Fits Insulgrip devices only.	**HBL60CM31+**
White Seal-Tite cover for weatherproofing HBL26CM11 plugs. **IP44 suitability.** Note: Fits Insulgrip devices only.	**HBL60CM31W+**
Yellow Seal-Tite cover for weatherproofing HBL26CM13 connector bodies when used with shore power inlets. Threaded sealing ring makes connection watertight. Also for weatherproofing HBL26CM11 plug when used with HBL303SSO power outlet. **IP56 suitability.** Note: Fits Insulgrip devices only.	**HBL60CM33+**
White Seal-Tite cover for weatherproofing HBL26CM13 connector body when used with shore power inlets. Threaded sealing ring makes connection watertight. Also for weatherproofing HBL26CM11 plug when used with HBL303SSO power outlet. **IP56 suitability.** Note: Fits Insulgrip devices only.	**HBL60CM33W+**
Yellow Seal-Tite cover for weatherproofing HBL26CM13 connector bodies when used on extension cords or adapters. **IP44 suitability.** Note: Fits Insulgrip devices only.	**HBL60CM32+**
Yellow polycarbonate spring-loaded lift cover for weather-proofing old style 26CM10 receptacle. Meets the most stringent requirements of UL's three listing categories for weatherproof plates. Stainless steel screws and neoprene gasket included for mounting to FS/FD type weatherproof boxes. **IP44 suitability.**	**HBL74CM24WO****
Same as HBL74CM24WO except gray in color. **IP44 suitability.**	**HBL7424WO****
Yellow polycarbonate spring-loaded lift cover for weather-proofing HBL26CM10 receptacle. Meets the most stringent requirements of UL's three listing categories for weatherproof plates. Stainless steel screws and neoprene gasket included for mounting to FS/FD type weatherproof boxes. **IP44 suitability.**	**HBL74CM25WOA****
Same as HBL74CM25WOA except white in color. **IP44 suitability.**	**HBL74CM25WOAW**
Same as HBL74CM25WOA except gray in color. **IP44 suitability.**	**HBL7425WOA****
Stainless steel wall plate for old 26CM10.	**SS725**
Stainless steel wall plate for new HBL26CM10.	**SS720**

Note: +Boots are not UL Listed or CSA Certified.
***See page CC-49 for aditional weatherproof plates.*



HBL74CM25WOA



HBL74CM25WOAW



SS725



HBL60CM31



HBL60CM33



HBL60CM32

Rynite® is a registered trademark of E. I. DuPont.

Dimensions in Inches (mm)