EXPLOSION PROOF CONDUIT OUTLET BOX - TYPE C



Installed in conduit systems within hazardous areas to protect conductors in threaded rigid conduit

Features: Suitable for NEMA 4X applications
Material: Aluminum
Certifications: cULus

Catalog Number	Trade Size	Unit Pkg.	Standard Pkg.
GUAC-50A	1/2"	1	5
GUAC-75A	3/4"	1	5
GUAC-100A	1"	1	5

EXPLOSION PROOF CONDUIT OUTLET BOX - TYPE LB



Installed in conduit systems within hazardous areas to protect conductors in threaded rigid conduit

Features: Suitable for NEMA 4X applications
Material: Aluminum
Certifications: cULus

Catalog Number	Trade Size	Unit Pkg.	Standard Pkg.
GUAB-50A	1/2"	1	5
GUAB-75A	3/4"	1	5
GUAB-100A	1"	1	5

EXPLOSION PROOF CONDUIT OUTLET BOX - TYPE L



Installed in conduit systems within hazardous areas to protect conductors in threaded rigid conduit

Features: Suitable for NEMA 4X applications
Material: Aluminum
Certifications: cULus

Catalog Number	Trade Size	Unit Pkg.	Standard Pkg.
GUAL-50A	1/2"	1	5
GUAL-75A	3/4"	1	5
GUAL-100A	1"	1	5

EXPLOSION PROOF CONDUIT OUTLET BOX - TYPE T



Installed in conduit systems within hazardous areas to protect conductors in threaded rigid conduit

Features: Suitable for NEMA 4X applications
Material: Aluminum
Certifications: cULus

Catalog Number	Trade Size	Unit Pkg.	Standard Pkg.
GUAT-50A	1/2"	1	5
GUAT-75A	3/4"	1	5
GUAT-100A	1"	1	5

EXPLOSION PROOF CONDUIT BODIES - TYPE LB



Connects conduit lengths and changes direction of conduit while meeting classified area requirements

Features: Tapered hub threads for tight, rigid joints and ground continuity
Material: Aluminum
Certifications: cULus

Catalog Number	Trade Size	Unit Pkg.	Standard Pkg.
XLB-50	1/2"	5	25
XLB-75	3/4"	5	25

EXPLOSION PROOF CONDUIT BODIES - TYPE T



Connects conduit lengths and changes direction of conduit while meeting classified area requirements

Features: Tapered hub threads for tight, rigid joints and ground continuity
Material: Aluminum
Certifications: cULus

Catalog Number	Trade Size	Unit Pkg.	Standard Pkg.
XT-50	1/2"	5	25
XT-75	3/4"	5	25

EXPLOSION PROOF CAPPED ELLS



Makes 90° bends in conduit systems where space is limited and can serve as pulling fitting

Features: Screw-on cover for ease of installation and removal
Material: Ductile Iron
Certifications: cULus

Catalog Number	Trade Size	Unit Pkg.	Standard Pkg.
PLBY-50	1/2"	2	10
PLBY-75	3/4"	2	10
PLBY-100	1"	2	10
PLBY-125	1 1/4"	2	10

EXPLOSION PROOF UNIONS



Use for joining conduit and connecting conduit to enclosures in classified areas

Features: Accurately tapped threads for rigid joints and ground continuity
Material: Steel
Certifications: cULus

Catalog Number	Trade Size	Unit Pkg.	Standard Pkg.
UNF-50	1/2"	10	50
UNF-75	3/4"	5	25
UNF-100	1"	5	25