XLERATOR® HAND DRYER



ENHANCED STANDARD FEATURES

- Adjustable Speed and Sound Control
- Multi-Voltage Options: 110-120V Or 208-277V
- Adjustable Heat Settings: High, Medium, Low & Off
- Externally Visible Service LED

8
SECONDS[1]
dry time

95%
COST SAVINGS
versus paper towels

3.7
WATT HOURS
energy use

INTERNATIONAL WELL BUILDING INSTITUTE MEMBER CORNERSTONE

CERTIFIED INC. EXCEL HAND DRYER, INC. SELECT PRODUCTS CERTIFIED

SMART EPD CERTIFIED ENVIRONMENTAL PRODUCT DECLARATION

hpdc

U.S. GREEN BUILDING COUNCIL MEMBER

eHEPA® ELECTROSTATIC HEPA FILTRATION

XLERATOR® HAND DRYER

MODELS: **XL -** **BW** **W** **GR** **C** **SB** **SI** **SP** **-H** (HEPA Filter) OPTIONS: **-1.1N** (Noise Reduction Nozzle) **-VOLTAGE** (See Chart)



XL-BW
White Nylon

TESTED TO PCR GUIDELINES

DRY TIME: 8 SECONDS[1] | **ENERGY PER USE: 3.7 Wh**

SMART EPD CERTIFIED ENVIRONMENTAL PRODUCT DECLARATION

Smart EPD® verifies Environmental Product Declarations (EPDs) for consistency with the LCA and conformance with global Product Category Rules (PCR) for hand dryers. UL Environment published the first global PCR for hand dryers. Third-party testing to these guidelines documents a product's environmental impact over its lifecycle. This impact is detailed in Environmental Product Declarations, enabling specifiers and buyers to make true apples-to-apples comparisons and more informed product selections. Excel Dryer received the industry's first certified EPDs.

FEATURES & BENEFITS

- Industry Leading 7-Year Limited Warranty
- 95% Cost Savings Vs. Paper Towels
- Helps Contribute to WELL Points and Several LEED® credits
- Made In USA Certified®
- A Hygienic Hand Drying Solution
- Washable Pre-Filter
- Adjustable Sensor Range

OPTIONS

- **Electrostatic HEPA (eHEPA®) Filtration System:** Removes 99.999% of viruses and 99.97% of potentially present bacteria at 0.3 microns from the airstream[2].
- **1.1" Noise Reduction Nozzle:** Reduces the sound level by 9 decibels by significantly decreasing air deflection noise while only increasing dry time by approximately 3 seconds.



XL-W
White Epoxy Painted



XL-GR-H
Graphite Textured Painted



XL-SP-H[3]
Custom Special Paint



XL-SI-H[4]
Custom Special Image



XL-C
Chrome Plated



XL-SB
Brushed Stainless Steel

PERFORMANCE

ADJUSTABLE SOUND LEVEL: 65-75 dB **ADJUSTABLE VELOCITY**: 13,000-20,000 LFM
ADJUSTABLE HEAT RANGE: 72°F-135°F **ADJUSTABLE FLOW RATE**: 42-63 CFM

DIMENSIONS

Width 11 3/4" (298 mm) **Height** 12 11/16" (322 mm) **Depth** 6 11/16" (170 mm)

ELECTRICAL

VOLTS	AMPS	WATTS	AMPS (HEAT OFF)	WATTS (HEAT OFF)	HERTZ	LISTING
110-120V	11.3-12.2A	1,213-1,450W	4.3-4.5A	442-513W	50/60 Hz	cULus
208-240V	5.6-6.2A	1,135-1,450W	2.0-2.2A	495W	50/60 Hz	cULus
208-277V	5.6-6.2A	1,135-1,450W	2.0-2.2A	416-495W	50/60 Hz	UL
230V	6.1A	1,400W	2.1A	500W	50-60 Hz	CE

CERTIFICATIONS

SMART EPD CERTIFIED · hpdc · MADE IN USA CERTIFIED · WELL BUILDING INSTITUTE MEMBER · U.S. GREEN BUILDING COUNCIL MEMBER · cULus · CE · OSHA COMPLIANCE · BuildingGreen APPROVED · RoHS

WEIGHT

XL-BW: 12.4 lbs. (5.62 kgs.) **XL-SB**: 16 lbs. (7.26 kgs.) **XL-W, GR, C, SI, SP**: 17 lbs. (7.71 kgs.)

ACTIVATION

Automatic Sensor Operated

MOUNTING

Surface Mounted

SUGGESTED MOUNTING HEIGHTS

Men 45" (114 cm) **Women** 43" (109 cm) **Accessible** 37" (94 cm)
Note: Heights measured from floor to bottom of dryer.

ACCESSORIES

- Antimicrobial Wall Guards (#89B, #89W, #89S)
- XChanger® Paper Towel Dispenser Retrofit Kit (#40575, #40550)
- ADA-Compliant Recess Kit (#40505/#40502)

#40505/#40502



[1]Dry time and energy use testing performed by SGS International on standard XLERATOR Hand Dryer with 0.8" nozzle to 0.25g or less of residual moisture, pursuant to the UL Environment Global Product Category Rules (PCR) for Hand Dryers. [2]Based on testing performed by LMS Technologies, 2023. [3]Special Paint powder-coated covers are available in many colors and textures. [4]Exclusive digital image technology allows for the addition of company, school or team logos with any color, design or a 'green message'.