Specifications



Eaton DH221NRK

Eaton enhanced visible blade single-throw fused safety switch, 30 A, NEMA 3R, Painted galvanized steel, Class H, Fusible with neutral, Two-pole, Three-wire, 240 V, Max Hp: 1.5, 3 hp/3, 7.5 hp/5 hp (1,3PH @ Std fuse/time delay/250 Vdc)

General specifications	
PRODUCT NAME	Eaton heavy duty fusible safety switch
CATALOG NUMBER	DH221NRK
UPC	782113205359
PRODUCT LENGTH/DEPTH	16.5 in
PRODUCT HEIGHT	8.31 in
PRODUCT WIDTH	9.12 in
PRODUCT WEIGHT	13.6 lb
WARRANTY	Eaton Selling Policy 25-000, one (1) year from the date of installation of the Product or eighteen (18) months from the date of shipment of the Product, whichever occurs first.
CERTIFICATIONS	UL Listed CSA Certified Build America, Buy America (BABA) Act
CATALOG NOTES	3-Phase hp ratings shown are grounded B phase ratings; UL listed
PRODUCT TYPE	Fusible safety switch

Physical Attributes

ENCLOSURE	NEMA 3R
ENCLOSURE MATERIAL	Painted galvanized steel
FUSE CLASS PROVISION	Class H
FUSE CONFIGURATION	Fusible with neutral
NUMBER OF POLES	Two-pole
NUMBER OF WIRES	3
TYPE	Heavy duty fusible safety switch

Performance Ratings

AMPERAGE RATING	30A
HP RATING - MAX	1.5, 3 hp/3, 7.5 hp/5 hp (1,3PH @ Std fuse/time delay/250 Vdc)
NEMA RATING	NEMA 3R
VOLTAGE RATING	240V

Miscellaneous

PRODUCT CATEGORY	Heavy Duty, Fusible with neutral

Resources

CATALOGS	Commercial Distribution, Switching Devices, Volume 2, Tab 1
SPECIFICATIONS AND DATASHEETS	Eaton Specification Sheet - DH221NRK

PROJECT NAME:	
PROJECT NUMBER:	
PREPARED BY:	
DATE:	

Eaton Corporation plc Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com

Follow us on social media to get the latest product and support information.

© 2026 Eaton. All Rights Reserved.