Specifications



Photo is representative





Eaton FRS-R-5

Eaton Bussmann Series Class RK5 fuse, FRS-R, time-delay, dual-element, current limiting fuse, 5 A, non-indicating fuse, interrupting rating of 200 kA at 600 Vac and 20 kA at 300 Vdc

General specifications	
PRODUCT NAME	Eaton Bussmann series FRS-R fuse
CATALOG NUMBER	FRS-R-5
UPC	051712508223
PRODUCT LENGTH/DEPTH	5 in
PRODUCT HEIGHT	0.81 in
PRODUCT WIDTH	0.81 in
PRODUCT WEIGHT	0.14 lb
WARRANTY	Not Applicable
COMPLIANCES	CE Marked
PRODUCT TYPE	Fuse

Electrical rating

AMPERAGE RATING	5 A
INTERRUPT RATING	200 kAIC at 600 Vac 20 kAIC at 300 Vdc
RESPONSE TIME	10 sec at 500%
VOLTAGE RATING	600 Vac, 300 Vdc

Physical details

NUMBER OF ELEMENTS	Dual
PACKAGING TYPE	Standard

General information

CLASS	Class RK5
CONNECTION	Ferrule end x ferrule end
FUSE INDICATOR	Non-indicating

Resources

CATALOGS	Low Voltage Branch Circuit Fuse Chapter Bussmann Full Line Catalog
COMPLIANCE INFORMATION	RoHS Search Tool
MULTIMEDIA	Bussmann series Fuseology
TECHNICAL SERVICE BULLETINS	Bussmann series FRS-R 600 V Class R up to 60 A fuse data sheet no. 1017

PROJECT NAME:	
PROJECT NUMBER:	
PREPARED BY:	
DATE:	

Eaton Corporation plc Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com

© 2026 Eaton. All Rights Reserved.

Follow us on social media to get the latest product and support information.