Specifications



Photo is representative

Eaton LT25090

Eaton Crouse-Hinds series Liquidator liquidtight connector, FMC, 90° angle, Non-insulated, Malleable iron, 2-1/2"

General specifications

PRODUCT NAME	Eaton Crouse-Hinds series Liquidator liquidtight connector
CATALOG NUMBER	LT25090
UPC	784564902504
PRODUCT LENGTH/DEPTH	9.31 in
PRODUCT HEIGHT	9.31 in
PRODUCT WIDTH	4 in
PRODUCT WEIGHT	8.38 lb
CERTIFICATIONS	UL514B UL467 cUL standard C22.2 No. 18F
PRODUCT TYPE	Liquidtight connector

Certifications and compliances

AREA CLASSIFICATION	Hazardous/Classified Locations
STANDARDS TYPE	NEC/CEC
NEC HAZARDOUS RATING	Class I, Division 2 Class II, Division 1 Class II, Division 2 Class III

Product specifications

CONDUIT TYPE	FMC
CONNECTOR TYPE	90° angle
MATERIAL	Malleable iron
INSULATOR	Non-insulated
TRADE SIZE	2-1/2"

Resources

3D CAD DRAWING PACKAGE	Eaton Crouse-Hinds LT25090 3D drawing
CATALOGS	Crouse-Hinds series Malleable and Aluminum Liquidtight Fittings catalog page
CERTIFICATION REPORTS	Metallic Liquidtight Fittings UL certification Metallic Liquidtight Fittings Canadian certification
SPECIFICATIONS AND DATASHEETS	Eaton Specification Sheet - LT25090

PROJECT NAME:	
PROJECT NUMBER:	
PREPARED BY:	
DATE:	

Eaton Corporation plc Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com

Follow us on social media to get the latest product and support information.

© 2026 Eaton. All Rights Reserved.