Specifications



Photo is representative

Eaton LT30045

Eaton Crouse-Hinds series Liquidator liquidtight connector, FMC, 45° angle, Non-insulated, Malleable iron, 3"

General specifications

PRODUCT NAME	Eaton Crouse-Hinds series Liquidator liquidtight connector
CATALOG NUMBER	LT30045
UPC	784564453006
PRODUCT LENGTH/DEPTH	8.75 in
PRODUCT HEIGHT	8.75 in
PRODUCT WIDTH	4.19 in
PRODUCT WEIGHT	8.6 lb
CERTIFICATIONS	UL467 UL514B cUL standard C22.2 No. 18F
PRODUCT TYPE	Liquidtight connector

Certifications and compliances

AREA CLASSIFICATION	Hazardous/Classified Locations
STANDARDS TYPE	NEC/CEC
NEC HAZARDOUS RATING	Class I, Division 2 Class II, Division 1 Class II, Division 2 Class III

Product specifications

CONDUIT TYPE	FMC
CONNECTOR TYPE	45° angle
MATERIAL	Malleable iron
INSULATOR	Non-insulated
TRADE SIZE	3"

Resources

3D CAD DRAWING PACKAGE	Eaton Crouse-Hinds LT30045 3D drawing
CATALOGS	Crouse-Hinds series Malleable and Aluminum Liquidtight Fittings catalog page
CERTIFICATION REPORTS	Metallic Liquidtight Fittings Canadian certification Metallic Liquidtight Fittings UL certification
SPECIFICATIONS AND DATASHEETS	Eaton Specification Sheet - LT30045

PROJECT NAME:	
PROJECT NUMBER:	
PREPARED BY:	
DATE:	

Eaton Corporation plc Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com

Follow us on social media to get the latest product and support information.

© 2026 Eaton. All Rights Reserved.