EIKO CERTIFIED GREEN

LITESPANLED®

LED PAR16 & PAR20



7 watts

420-500 lumens

up to 71 lpw

2700-4000K CCT

features

- Direct replacement for halogen PARs
- Compatible with a wide array of dimmers
- +25,000 hour rated life for ENERGY STAR® Approved lamps*
- 50,000 hour design life**
- Up to 80% electricity savings vs. halogen
- Choice of 2700K, 3000K and 4000K color temperatures
- 2700K & 3000K ENERGY STAR® Approved
- 20°, 25° and 40° beam angles available
- No mercury or UV/IR emissions
- Shatter-resistant for reduced risk of injury and breakage

RoHS Compliant

ENERGY STAR

c UL US LISTED

performance

- PAR16 replaces 50W PAR16 Halogen
- PAR20 replaces 50W PAR20 Halogen
- 80+ CRI
- 120V @ 60Hz
- Operating temperature range from -40°F to 104°F (-40°C to 40°C)
- Not for use in enclosed fixtures
- Not for use with electronic timers, photocells, or motion/occupancy sensors

applications

- Recessed / Track Lighting
- Property Management
- Accent / Display Lighting
- Retail / Residential
- Hospitality
- Houses of Worship
- Healthcare
- Task Lighting

* Early initial qualification for ENERGY STAR allows for directional lamp life claims of 25,000 hours (L70) with 3,000 hour actual test data, LM80 data and in-situ temperature measurements. As the lamps pass ENERGY STAR requirements, manufacturers may increase the lifetime of a product as dictated by ENERGY STAR guidelines. See http://www.energystar.gov/index.cfm?fuseaction=products_for_partners.showLightbulbs for further details.

** Design life is based on engineering testing and probability analysis

SHATTER RESISTANT | DIMMABLE | 25,000 LIFETIME HRS | CRI (Ra) | INSTANT ON | 5 YR WARRANTY

selection. solutions. simplicity. eiko.com

EiKO CERTIFIED GREEN

LITESPANLED®

LED PAR16 & PAR20

dimensions



ordering information

	Order Code	Item #	Lm	W	CBCP	CCT	CRI	Bm	MOL	Life/ Hrs*	Replaces Incandescent		
PAR16	**09038**	LED7WPAR16/NFL/827K-DIM-G5	420	7W	2,000	2700K	80+	20°	2.87"	25K	50W PAR16		
	09039	LED7WPAR16/NFL/830K-DIM-G5	420	7W	2,000	3000K	80+	20°	2.87"	25K	50W PAR16		
	09040	LED7WPAR16/NFL/840K-DIM-G5	450	7W	2,000	4100K	80+	20°	2.87"	25K	50W PAR16		
	09041	LED7WPAR16/FL/827K-DIM-G5	450	7W	1,200	2700K	80+	40°	2.87"	25K	50W PAR16		
	09042	LED7WPAR16/FL/830K-DIM-G5	450	7W	1,200	3000K	80+	40°	2.87"	25K	50W PAR16		
	09043	LED7WPAR16/FL/840K-DIM-G5	450	7W	1,200	4100K	80+	40°	2.87"	25K	50W PAR16		
PAR20	**90024**	LED7WPAR20/FL/827K-DIM-G4A**	500	7W	1,074	2700K	80+	40°	3.37"	25K	50W PAR20		★
	90023	LED7WPAR20/FL/830K-DIM-G4A**	500	7W	1,127	3000K	80+	40°	3.37"	25K	50W PAR20		★
	90022	LED7WPAR20/FL/840K-DIM-G4A**	500	7W	1,101	4000K	80+	40°	3.37"	25K	50W PAR20	✖	
	90021	LED7WPAR20/NFL/827K-DIM-G4A**	500	7W	1,526	2700K	80+	25°	3.37"	25K	50W PAR20		★
	90020	LED7WPAR20/NFL/830K-DIM-G4A**	500	7W	1,750	3000K	80+	25°	3.37"	25K	50W PAR20		★
	90019	LED7WPAR20/NFL/840K-DIM-G4A**	500	7W	1,638	4000K	80+	25°	3.37"	25K	50W PAR20	✖	★
	09184	LED7WPAR20/FL/827K-DIM-G6	470	7W	1,166	2700K	80+	40°	3.39"	25K	50W PAR20		★
	09185	LED7WPAR20/FL/830K-DIM-G6	470	7W	1,206	3000K	80+	40°	3.39"	25K	50W PAR20		★
	09186	LED7WPAR20/FL/840K-DIM-G6	470	7W	1,308	4000K	80+	40°	3.39"	25K	50W PAR20		★
	09187	LED7WPAR20/NFL/827K-DIM-G6	470	7W	2,135	2700K	80+	25°	3.39"	25K	50W PAR20		
	09188	LED7WPAR20/NFL/830K-DIM-G6	470	7W	2,088	3000K	80+	25°	3.39"	25K	50W PAR20		★
	09189	LED7WPAR20/NFL/840K-DIM-G6	470	7W	2,155	4000K	80+	25°	3.39"	25K	50W PAR20		

** 25,000-40,000 hour ENERGY STAR® rated life. 50,000 hour design life. See note on obverse.*
*** While supplies last*

✖ *Lighting Design Lab Qualified* ★ *ENERGY STAR® Approved*

watch > like > follow

23220 W. 84th St, Shawnee, KS 66227 · (P) 1.800.852.2217 (F) 1.800.492.8975
Canada: 81 King St, Barrie, ON L4N 6B5 · (P) 1.888.410.8151 (F) 1.888.705.1335

Rev. 2/18/16

PAR20 LED									
Ordering Code	**Watts**	**Volts**	**Shape**	**Base**	**Lumens**	**MOL**	**MOD**	**Life Hours**	**Approvals**
LED7WPAR20/FL/827K-DIM-G4A	7	120	PAR 20	Medium Screw (E26)	470	3.37/85.5	2.48/63	25,000	UL, cUL, Energy Star
LED7WPAR20/FL/830K-DIM-G4A	7	120	PAR 20	Medium Screw (E26)	470	3.37/85.5	2.48/63	25,000	UL, cUL, Energy Star
LED7WPAR20/FL/840K-DIM-G4A	7	120	PAR 20	Medium Screw (E26)	470	3.37/85.5	2.48/63	25,000	UL, cUL
LED7WPAR20/NFL/830K-DIM-G4A	7	120	PAR 20	Medium Screw (E26)	500	3.37/85.5	2.48/63	25,000	UL, cUL, Energy Star
LED7WPAR20/NFL/840K-DIM-G4A	7	120	PAR 20	Medium Screw (E26)	500	3.37/85.5	2.48/63	25,000	UL, cUL
LED8WPAR20/FL/841-DIM	8	120	PAR 20	Medium Screw (E26)	490	3.39/86	2.48/63	40,000	UL, cUL
LED8WPAR20/NFL/827-DIM	8	120	PAR 20	Medium Screw (E26)	460	3.39/86	2.48/63	40,000	UL, cUL, Energy Star
LED8WPAR20/NFL/830-DIM	8	120	PAR 20	Medium Screw (E26)	470	3.39/86	2.48/63	40,000	UL, cUL, Energy Star
LED8WPAR20/NFL/841-DIM	8	120	PAR 20	Medium Screw (E26)	490	3.39/86	2.48/63	40,000	UL, cUL

NOTES: