FLANGE MOUNT CONDUIT CLIP SIDEMOUNT



UL LISTED

FEATURES:

The Conduit/Pipe to flange Clip for side-mount applications is available for EMT, rigid, and aluminum conduit (refer to chart below). Only a hammer is required for installation and the side mount clip will pivot 360˚.

FINISH:

Elite Shield

MATERIAL:

Spring Steel

PART NUMBER	FLANGE SIZE	CONDUIT SIZE	LOAD (LBS)	BOX QTY.
E6M24SM	1/8”-1/4”	3/8”	25	100
E6M58SM	5/16”-1/2”	3/8”	25	100
E6M912SM	9/16”-3/4”	3/8”	25	100
E812M24SM	1/8”-1/4”	1/2”-3/4”	25	100
E812M58SM	5/16”-1/2”	1/2”-3/4”	25	100
E812M912SM	9/16”-3/4”	1/2”-3/4”	25	100
E16M24SM	1/8”-1/4”	1”	25	100
E16M58SM	5/16”-1/2”	1”	25	100
E16M912SM	9/16”-3/4”	1”	25	100
E20M24SM	1/8”-1/4”	1 1/4”	25	100
E20M58SM	5/16”-1/2”	1 1/4”	25	100
E20M912SM	9/16”-3/4”	1 1/4”	25	50
E24M24SM	1/8”-1/4”	1 1/2”	25	50
E24M58SM	5/16”-1/2”	1 1/2”	25	50
E24M912SM	9/16”-3/4”	1 1/2”	25	50
E32M24SM	1/8”-1/4”	2”	25	50
E32M58SM	5/16”-1/2”	2”	25	50
E32M912SM	9/16”-3/4”	2”	25	50