
90° Compression Connector




Listed
Control No. 865G

File No. 1HUO

TRADE SIZE	HALEX PART*	PCS/ UNIT	CTN/CASE QTY	CTN/CASE WT(lbs.)	UPC BAR CODED SELL UNIT	DIMENSIONS (in inches) A	B	C
1/2"	02905B	bulk	25/250	5/50	NA	1.75	0.83	0.52
3/4"	02907B	bulk	20/200	5.2/52	NA	1.86	0.95	0.52
1"	02910	tray box	10	4.6	UPC on product	2.21	1.12	0.67
BAGGED ITEMS								
1/2"	90291	1/bag	35 bags	7	UPC on bag	1.75	0.83	0.52
3/4"	90292	1/bag	20 bags	5.2	UPC on bag	1.86	0.95	0.52

Application: Indoors Only
Use to join two lengths of E.M.T. conduit.
Material: Zinc Die Cast
Features: Rain-Tight and Concrete-Tight

One-Hole Strap




File No. **AP9XII.1**

1/2"	61505B	bulk	100/1000	3/30	UPC on carton	1.250	0.562
3/4"	61507B	bulk	100/1000	4/40	UPC on carton	1.375	0.625
1"	61510B	bulk	50/500	3/30	NA	1.562	0.750
1 1/4"	61512B	bulk	50/500	4/40	NA	2.000	0.875
1 1/2"	61515B	bulk	25/250	3/30	NA	2.125	1.000
2"	61520B	bulk	25/250	4.3/43	NA	2.625	1.125
2 1/2"	61125B	bulk	50	21	NA	3.312	1.250
3"	61130B	bulk	25	12.3	NA	3.625	1.250
3 1/2"	61135B	bulk	25	17.8	NA	4.000	1.250
4"	61140B	bulk	20	15.6	NA	4.250	1.250
BAGGED ITEMS							
1/2"	96151	4/bag	50 bags	6	UPC on bag	1.250	0.562
1/2"	26151	25/bag	40 bags	30	UPC on bag	1.250	0.562
1/2"	26158	100/bag	10 bags	30	UPC on bag	1.250	0.562
3/4"	96152	4/bag	30 bags	4.2	UPC on bag	1.375	0.625
3/4"	26152	20/bag	40 bags	32	UPC on bag	1.375	0.625
3/4"	26159	75/bag	10 bags	30	UPC on bag	1.375	0.625
1"	26153	4/bag	30 bags	7	UPC on bag	1.562	0.750
1"	96153	1/bag	35 bags	2.1	UPC on bag	1.562	0.750
1 1/4"	26154	4/bag	25 bags	8	UPC on bag	2.000	0.875
1 1/2"	26155	2/bag	10 bags	2.4	UPC on bag	2.125	1.000
2"	26156	2/bag	20 bags	2	UPC on bag	2.625	1.125
CARDED ITEMS							
1/2"	46151	5/card	10 cards	1.5	UPC on card	1.250	0.562
3/4"	46152	5/card	10 cards	2	UPC on card	1.375	0.625
CONTRACTOR BUCKETS							
1/2"	26256	550/bkt	1 bucket	16.5	UPC on bucket	1.250	0.562
3/4"	26257	350/bkt	1 bucket	14	UPC on bucket	1.375	0.625

Application: Indoors Or Outdoors
To support E.M.T. conduit where greater load bearing is required.
Material: Steel
Type: Snap-on Style

23901 Aurora Road Bedford Hts., Ohio 44146 Phone: 440.439.1616 Fax: 440.439.1792

One-Hole Strap (Steel)




Listed
Control No. 43Y8
File No. AP9X1U

TRADE SIZE	HALEX PART #	PCS/ UNIT	CTN/CASE QTY	CTN/CASE WT	UPC BAR CODED SELL UNIT	DIMENSIONS A (in inches)	B (in inches)
1/2"	61105B	bulk	100/1000	3/30	NA	1.375	0.625
3/4"	61107B	bulk	100/1000	5/50	NA	1.562	0.750
1"	61110B	bulk	50/500	3.5/35	NA	1.812	0.875
1 1/4"	61112B	bulk	50/500	5/50	NA	2.000	0.875
1 1/2"	61115B	bulk	25/250	4.2/42.5	NA	2.500	1.000
2"	61120	tray box	25	5.5	UPC on product	2.750	1.125
2"	61120B	bulk	25/250	5.5/55	NA	2.750	1.125
2 1/2"	61125	tray box	50	21	UPC on product	3.312	1.250
2 1/2"	61125B	bulk	50	21	NA	3.312	1.250
3"	61130	tray box	25	12.3	UPC on product	3.625	1.250
3"	61130B	bulk	25	12.3	NA	3.625	1.250
3 1/2"	61135B	bulk	25	17.8	NA	4.000	1.250
4"	61140B	bulk	20	15.6	NA	4.250	1.250
BAGGED ITEMS							
1/2"	96111	4/bag	50 bags	1.5	UPC on bag	1.375	0.625
3/4"	96112	4/bag	25 bags	1.3	UPC on bag	1.562	0.750
1"	96113	4/bag	25 bags	1.8	UPC on bag	1.812	0.875

Application: Dry Locations
Use to secure Rigid or I.M.C. conduit to wood, masonry or similar surfaces where greater load bearing is required.

Compression Connector




Listed
Control No. 43YX
File No. AP98113

1"	63510	tray box	10	3.6	UPC on product	1.48	1.43
1 1/4"	63512	tray box	5	2	UPC on product	1.96	2.16
1 1/2"	63515	tray box	5	2.5	UPC on product	2.15	2.38
2"	63520	tray box	2	2	UPC on product	2.24	2.88
BAGGED ITEMS							
1/2"	26351	2/bag	40 bags	10	UPC on bag	1.43	1.17
3/4"	26352	2/bag	30 bags	12	UPC on bag	1.48	1.43

Application: Dry Locations
Use to join threadless Rigid or I.M.C. conduit to a steel outlet box or other metal enclosure.
Features: Concrete-Tight
Material: Steel

Set-Screw Connector



Listed
Control No. 862G
File No. 18130

1/2"	03505	tray box	50	5	UPC on product	1.34	0.39
1/2"	03505B	bulk	50/500	5/50	NA	1.34	0.39
3/4"	03507B	bulk	25/250	3.8/37.5	NA	1.44	0.45
1"	0351 OB	bulk	25/100	5.5/22	NA	1.54	0.49

Application: Dry Locations
Use to join threadless Rigid or I.M.C. conduit to a steel outlet box or other metal enclosure.
Material: Zinc Die-Cast
Note: EMT connectors can be used for sizes 2 1/2" and above.
See page 5.