COMMERCIAL OUTDOOR LUMINAIRE

DuraGem™ LED Wall Pack

Illuminate outdoors from dusk to dawn with proprietary DuraGem™ Technology. Engineered for balanced LED lumen output with long-rated life. IP65 Rated for wet locations. Smart Ready for photocell and bi-level dimming functions.

Project:	
Date:	
Catalog No:	
Prepared By:	



Features

IP Rating	IP65 - Wet Location
Finish	Dark Bronze Satin
Diffuser	Anti-UV Prismatic Tempered Glass Lens
Rated Life	75000 hours
Warranty	7 years

Construction

Manufactured for weather-proof durability using heavy duty die cast aluminum housing with anti-UV polyester coating to resist corrosion, discoloration, and scratching.

Applications

Primary luminaire use as outdoor non-cutoff and semi-cutoff wall-mounted for walkways or security lights that produces a non-negligible amount of uplight.

Listings

DLC listed. ETL certified to meet US and Canadian standards. FCC, CE and RoHS compliant. IP65 rated for wet location use. View DLC listing at: *designlights.org/qpl*

Warranty

7 year exclusive limited warranty. View complete product warranty information at: *etheriumled.com/warranty*

Performance

Wattage	See ordering information.
Voltage	120-277V
Frequency	50/60 Hz
Efficacy	105 lm/W
CCT	4000K or 5000K
CRI	≥ 80
Power Factor	≥ 0.9
THD	≤ 15%
Operating Temp.	-40°C to 45°C (-40°F to 113°F)
Dimming	0-10V

ORDERING INFORMATION

Model No.	Wattage (W)	Voltage (V)	CCT (K)	Light Output	Efficacy (lm/w)	Rated Life
-WP-40W-G2-4000K	40	120-277V	4000K	4200 lm	105 lm/W	75000 hrs
-WP-40W-G2-5000K	40	120-277V	5000K	4200 lm	105 lm/W	75000 hrs
-WP-60W-G2-4000K	60	120-277V	4000K	6300 lm	105 lm/W	75000 hrs
-WP-60W-G2-5000K	60	120-277V	5000K	6300 lm	105 lm/W	75000 hrs
-WP-80W-G2-4000K	80	120-277V	4000K	8400 lm	105 lm/W	75000 hrs
-WP-80W-G2-5000K	80	120-277V	5000K	8400 lm	105 lm/W	75000 hrs
-WP-100W-G2-4000K	100	120-277V	4000K	10500 lm	105 lm/W	75000 hrs
-WP-100W-G2-5000K	100	120-277V	5000K	10500 lm	105 lm/W	75000 hrs
-WP-120W-G2-4000K	120	120-277V	4000K	12600 lm	105 lm/W	75000 hrs
-WP-120W-G2-5000K	120	120-277V	5000K	12600 lm	105 lm/W	75000 hrs