


TRADE SIZE	HALEX PART #	CTN/CASE QTY	CTN/CASE WT (LBS)	DIMENSIONS (IN INCHES) A	B
Screw-In Connectors				**Zinc Die Cast**	
3/8″(1/2" ko)	**04403B**	50/500	3/30	1.31	0.92
1/2″	**04405B**	50/500	3/30	1.38	0.92
3/4″	**04407B**	25/250	2.5/25	1.62	1.12
1″	**04410B**	25/250	4/40	1.94	1.37
1 1/4″	**04412B**	10/100	2.8/28	2.12	1.75
1 1/2″	**04415B**	10/40	3.8/15.2	2.31	2.13
2″	**04420B**	10/40	6.3/25.2	2.58	2.67
WITH INSULATED THROAT					
3/8″(1/2" ko)	**84403B**	50/500	3/30	1.36	0.92
1/2″	**84405B**	50/500	3/30	1.43	0.92
3/4″	**84407B**	25/250	2.5/25	1.67	1.12
1″	**84410**	15	2.3	1.99	1.37
1 1/4″	**84412**	10	2.8	2.17	1.75
1 1/2″	**84415**	5	1.9	2.36	2.13
2″	**84420**	5	3.2	2.63	2.67



APPLICATION: INDOORS ONLY - Use to connect flexible metallic conduit to steel outlet box, load center or other metal enclosure. **MATERIAL:** Zinc Die Cast. **MISC:** 3/8″ size fits 1/2″ knockout (ko). **SUITABLE FOR:** 1/2″ - steel, reduced wall steel, and aluminum flexible metal conduit. 3/8″, 3/4″ to 1 1/4″ and 2″ flexible metal conduit. 1 1/2″ - steel and steel reduced wall flexible metal conduit. **CERTIFICATIONS:** TO UL AND CSA REQUIREMENTS.



TRADE SIZE	HALEX PART #	CTN/CASE QTY	CTN/CASE WT (LBS)	DIMENSIONS (IN INCHES) A	B
Screw-In Connectors				**Zinc Die Cast**	
SNAP-IN TYPE					
3/8″(1/2" ko)	**04403NB**	50/500	1.9/19	1.269	0.918
1/2″	**04405NB**	50/500	2/20	1.344	0.918



APPLICATION: INDOORS ONLY - Use to connect flexible metallic conduit to steel outlet box, load center or other metal enclosure. **MATERIAL:** Zinc Die Cast. **MISC:** 3/8″ size fits 1/2″ knockout (ko). **SUITABLE FOR:** 3/8″ flexible metal conduit. 1/2″ - steel and steel reduced wall flexible metal conduit. **FEATURES:** New Snap-In design allows for quick and easy installation. No locknuts required. Meets UL ground fault requirements. **CERTIFICATIONS:** TO UL AND CSA REQUIREMENTS.



TRADE SIZE	HALEX PART #	CTN/CASE QTY	CTN/CASE WT (LBS)	DIMENSIONS (IN INCHES) A	B
Screw-In Couplings				**Zinc Die Cast**	
1/2″	**04505B**	50/500	3/30	1.81	0.92
3/4″	**04507B**	25/250	2.3/22.5	2.09	1.12
1″	**04510**	15	3.8	2.41	1.37
1 1/4″	**04512**	10	2.5	2.75	1.81
1 1/2″	**04515**	5	2	3.05	2.12
2″	**04520**	4	2.4	3.28	2.67



APPLICATION: INDOORS ONLY - Use to join two pieces of flexible metallic conduit. **MATERIAL:** Zinc Die Cast. **SUITABLE FOR:** 1/2″ - steel, steel reduced wall, and aluminum flexible metal conduit; 3/4″ to 1 1/4″ and 2″ flexible metal conduit; 1 1/2″ - steel and steel reduced wall flexible metal conduit. **CERTIFICATIONS:** TO UL AND CSA REQUIREMENTS.