


Mogul Pulling Elbows - Type LB — Aluminum



TRADE SIZE	HALEX PART #	CTN/CASE QTY	CTN/CASE WT (LBS)	DIMENSIONS (IN INCHES) A	B	C
1 1/4″	**58212B**	5	7	3.500	2.719	9.625
1 1/2″	**58215B**	2	7	5.500	4.125	14.563
2″	**58220B**	2	7	5.500	4.125	14.563

APPLICATION: INDOORS OR OUTDOORS. Use to gain access to the interior of a raceway for wire pulling, splicing (with limitations as specified by the NEC), and maintenance. **Not listed for wet locations. MATERIAL:** Copper-Free Die-Cast Aluminum. **MISC:** Allows larger access to inside of raceway for easier wire pulling. **CERTIFICATIONS:** TO UL AND CSA REQUIREMENTS.




Water-Tight "Myers" Conduit Hubs — Zinc Die Cast



TRADE SIZE	HALEX PART #	CTN/CASE QTY	CTN/CASE WT (LBS)	DIMENSIONS (IN INCHES) A	B
WITH INSULATED THROAT					
1/2″	**91631**	10	1.9	1.438	1.344
3/4″	**91632**	10	2.7	1.719	1.469
1″	**16310**	5	2.1	2.000	1.656
1 1/4″	**16312**	5	2.6	2.375	1.688
1 1/2″	**16315**	4	2.8	2.750	1.688
2″	**16320**	3	2.9	3.250	1.750
2 1/2″	**16325B**	2	3.12	3.750	2.219
3″	**16330B**	2	4.26	4.375	2.313
3 1/2″	**16335B**	1	2.6	5.000	2.375
4″	**16340B**	1	3.4	5.500	2.438

APPLICATION: INDOORS OR OUTDOORS. Use to connect Rigid or IMC conduit to a load center or other metal enclosure where a water-tight joint is required at knockouts or slip-fit holes. **MATERIAL:** Zinc Die Cast. **FEATURES:** Flame Retardant Insulated Throat. Rain, Oil and dust tight. Oversize locknut assures vibration-proof installation and positive grounding. **CERTIFICATIONS:** TO UL AND CSA REQUIREMENTS.




90° Short Radius Elbows — Zinc Die Cast



TRADE SIZE	HALEX PART #	CTN/CASE QTY	CTN/CASE WT (LBS)	DIMENSIONS (IN INCHES) A	B
1/2″	**19005**	20	2.1	0.98	0.96
3/4″	**19007**	10	1.7	1.17	1.04

APPLICATION: INDOORS OR OUTDOORS. Use to connect Rigid or IMC conduit to an outlet box where a close radius is desired. **MATERIAL:** Zinc Die Cast. **CERTIFICATIONS:** TO UL AND CSA REQUIREMENTS.



90° Large Radius Adapter Elbows — Zinc Die Cast



TRADE SIZE	HALEX PART #	CTN/CASE QTY	CTN/CASE WT (LBS)	DIMENSIONS (IN INCHES) A	B	C
1/2″	**19205B**	25	2.9	1.294	1.450	0.521
3/4″	**19207B**	10	1.6	1.526	1.690	0.521

APPLICATION: INDOORS OR OUTDOORS. Use to connect Rigid or IMC conduit to an outlet box where a large radius is desired. Use to convert any standard straight fitting to a 90° fitting. **MATERIAL:** Zinc Die Cast. **FEATURES:** Exceptional wire pulling ability. **CERTIFICATIONS:** TO UL AND CSA REQUIREMENTS.