Threaded Conduit Bodies — Aluminum

WITH COVER AND GASKET





TRADE SIZE	HALEX PART #	CTN/CASE QTY	CTN/CASE WT (LBS)	DIMENSIONS (IN INCHES) A	B	C	D
TYPE: LB							
1/2″	**58605**	10	2.7	3.87	1.31	4.24	1.41
3/4″	**58607**	10	3.8	4.67	1.53	4.97	1.65
1″	**58610**	3	1.9	5.37	1.74	5.79	1.91
1 1/4″	**58612**	2	2.6	7.23	2.49	7.79	2.48
1 1/2″	**58615**	2	2.7	7.23	2.49	7.81	2.67
2″	**58620**	1	2.4	9.46	3.10	10.20	3.42
2 1/2″	**58625**	1	6	12.22	4.44	13.14	3.93
3″	**58630B**	1	5	12.22	4.44	13.14	4.52
3 1/2″	**58635B**	1	9.5	14.83	5.42	15.46	5.39
4″	**58640B**	1	8.5	14.83	5.42	15.46	5.39





TYPE: T							
1/2″	**58805**	5	1.6	3.87	1.31	4.82	1.40
3/4″	**58807**	3	1.3	4.67	1.53	5.40	1.64
1″	**58810**	2	1.4	5.37	1.74	6.33	1.90
1 1/4″	**58812**	2	3.7	7.23	2.49	8.45	2.73
1 1/2″	**58815**	2	3.3	7.23	2.49	8.45	2.73
2″	**58820**	1	2.5	9.46	3.10	10.71	3.41
2 1/2″	**58825B**	1	6.222	11.208	4.50	13.75	
3″	**58830B**	1	6.780	11.208	4.50	13.687	
3 1/2″	**58835B**	1	12.526	14.937	4.50	16.904	
4″	**58840B**	1	10.66	14.937	5.50	15.875	





TYPE: LR							
1/2″	**58905**	5	1.5	3.87	1.31	4.40	1.40
3/4″	**58907**	3	1.3	4.67	1.53	5.07	1.64
1″	**58910**	2	1.4	5.37	1.74	5.94	1.90
1 1/4″	**58912**	2	2.8	7.23	2.49	7.78	2.85
1 1/2″	**58915**	2	3.3	7.23	2.49	7.78	2.85
2″	**58920**	1	2.7	9.46	3.10	9.88	3.41
2 1/2″	**58925B**	1	6.000	12.22	4.50	13.14	4.00
3″	**58930B**	1	6.800	11.208	4.50	12.5	
3 1/2″	**58935B**	1	11.55	14.937	5.50	15.062	
4″	**58940B**	1	10.6375	14.937	5.50	15.187	





TYPE: LL							
1/2″	**58305**	5	1.5	3.87	1.31	4.40	1.40
3/4″	**58307**	3	1.3	4.67	1.53	5.07	1.64
1″	**58310**	2	1.4	5.37	1.74	5.94	1.90
1 1/4″	**58312**	2	2.8	7.23	2.49	7.87	2.85
1 1/2″	**58315**	2	3.1	7.23	2.49	7.87	2.85
2″	**58320**	1	2.7	9.46	3.10	10.20	3.41
2 1/2″	**58325B**	1	3	12.22	4.50	13.14	4.00
3″	**58330B**	1	6.592	11.208	4.50	12.5	
3 1/2″	**58335B**	1	10.286	14.937	5.50	15.25	
4″	**58340B**	1	9.8792				





TYPE: C							
1/2″	**58405**	5	1.4	3.87	1.31	4.82	1.40
3/4″	**58407**	3	1.3	4.67	1.53	5.50	1.64
1″	**58410**	2	1.2	5.37	1.74	6.44	1.90
1 1/4″	**58412**	2	3.3	7.23	2.49	8.45	2.73
1 1/2″	**58415**	2	3	7.23	2.49	8.45	2.73
2″	**58420**	1	2.6	9.46	3.10	10.71	3.41
2 1/2″	**58425B**	1	5.682	11.208	4.50	13.75	
3″	**58430B**	1	6.314	11.208	5.50	13.687	
3 1/2″	**58435B**	1	9.74	14.937	5.50	16.875	
4″	**58440B**	1	10.226	14.937	5.50	16.875	

APPLICATION: INDOORS OR OUTDOORS. Use to gain access to the interior of a raceway for wire pulling, splicing (with limitations as specified by the NEC), and maintenance. **Not listed for wet locations. MATERIAL:** Copper-Free Die-Cast Aluminum, Aluminum Stamped Cover and Neoprene Gasket. **CERTIFICATIONS:** TO UL AND CSA REQUIREMENTS.