
One-Hole Strap (Steel)




Listed
Control No. 43Y8
File No. AP9X1U

TRADE SIZE	HALEX PART #	PCS/ UNIT	CTN/CASE QTY	CTN/CASE WT	UPC BAR CODED SELL UNIT	DIMENSIONS A (in inches)	B (in inches)
1/2"	61105B	bulk	100/1000	3/30	NA	1.375	0.625
3/4"	61107B	bulk	100/1000	5/50	NA	1.562	0.750
1"	61110B	bulk	50/500	3.5/35	NA	1.812	0.875
1 1/4"	61112B	bulk	50/500	5/50	NA	2.000	0.875
1 1/2"	61115B	bulk	25/250	4.2/42.5	NA	2.500	1.000
2"	61120	tray box	25	5.5	UPC on product	2.750	1.125
2"	61120B	bulk	25/250	5.5/55	NA	2.750	1.125
2 1/2"	61125	tray box	50	21	UPC on product	3.312	1.250
2 1/2"	61125B	bulk	50	21	NA	3.312	1.250
3"	61130	tray box	25	12.3	UPC on product	3.625	1.250
3"	61130B	bulk	25	12.3	NA	3.625	1.250
3 1/2"	61135B	bulk	25	17.8	NA	4.000	1.250
4"	61140B	bulk	20	15.6	NA	4.250	1.250
BAGGED ITEMS							
1/2"	96111	4/bag	50 bags	1.5	UPC on bag	1.375	0.625
3/4"	96112	4/bag	25 bags	1.3	UPC on bag	1.562	0.750
1"	96113	4/bag	25 bags	1.8	UPC on bag	1.812	0.875

Application: Dry Locations
Use to secure Rigid or I.M.C. conduit to wood, masonry or similar surfaces where greater load bearing is required.

Compression Connector




Listed
Control No. 43YX
File No. AP98113

1"	63510	tray box	10	3.6	UPC on product	1.48	1.43
1 1/4"	63512	tray box	5	2	UPC on product	1.96	2.16
1 1/2"	63515	tray box	5	2.5	UPC on product	2.15	2.38
2"	63520	tray box	2	2	UPC on product	2.24	2.88
BAGGED ITEMS							
1/2"	26351	2/bag	40 bags	10	UPC on bag	1.43	1.17
3/4"	26352	2/bag	30 bags	12	UPC on bag	1.48	1.43

Application: Dry Locations
Use to join threadless Rigid or I.M.C. conduit to a steel outlet box or other metal enclosure.
Features: Concrete-Tight
Material: Steel

Set-Screw Connector



Listed
Control No. 862G
File No. 18130

1/2"	03505	tray box	50	5	UPC on product	1.34	0.39
1/2"	03505B	bulk	50/500	5/50	NA	1.34	0.39
3/4"	03507B	bulk	25/250	3.8/37.5	NA	1.44	0.45
1"	0351 OB	bulk	25/100	5.5/22	NA	1.54	0.49

Application: Dry Locations
Use to join threadless Rigid or I.M.C. conduit to a steel outlet box or other metal enclosure.
Material: Zinc Die-Cast
Note: EMT connectors can be used for sizes 2 1/2" and above.
See page 5.