
Two-Hole Strap

TRADE SIZE	HALEX PART#	PCS/ UNIT	CTN/CASE QTY	CTN/CASE WT	UPC BAR CODED SELL UNIT	DIMENSIONS A	B	C
						(in inches)		
1/2"	61205B	bulk	1 00/1 000	2/20	NA	2.250	1.625	0.562
3/4"	61207B	bulk	100/1000	3/30	NA	2.875	2.250	0.638
1"	61210B	bulk	50/500	2.5/25	NA	3.375	2.625	0.750
1 1/4"	61212B	bulk	25/250	1.8/17.5	NA	4.188	3.437	0.875
1 1/2"	61215B	bulk	25/250	3/30	NA	4.625	3.812	0.875
2"	61220B	bulk	50/200	7.5/30	NA	5.125	4.250	1.000
2 1/2"	61225	tray box	7	1.2	UPC on product	5.875	4.875	1.000
2 1/2"	61225B	bulk	50	8.5	NA	5.875	4.875	1.000
3"	61230	tray box	25	5.8	UPC on product	6.500	5.500	1.000
3"	61230B	bulk	25	5.8	NA	6.500	5.500	1.000
3 1/2"	61235B	bulk	25	6.5	NA	7.375	6.375	1.000
4"	61240B	bulk	20	6.6	NA	8.000	7.000	1.000
BAGGED ITEMS								
1/2"	96121	4/bag	30 bags	0.6	UPC on bag	2.500	1.875	0.625
1/2"	26121	10/bag	25 bags	5	UPC on bag	2.500	1.875	0.625
3/4"	96122	4/bag	20 bags	0.6	UPC on bag	2.875	2.250	0.638
3/4"	26122	10/bag	20 bags	6	UPC on bag	2.875	2.250	0.638
1"	96123	1/bag	30 bags	1.5	UPC on bag	3.375	2.625	0.750
1"	26123	4/bag	25 bags	5	UPC on bag	3.375	2.625	0.750
1 1/4"	26124	4/bag	15 bags	4	UPC on bag	4.188	3.437	0.875
1 1/2"	26125	2/bag	20 bags	5	UPC on bag	4.625	3.812	0.875
2"	26126	2/bag	15 bags	9	UPC on bag	5.125	4.250	1.000




Listed
Control No. 43Y8
File No. AP98113

Application: Dry Locations
Use to secure Rigid or I.M.C. conduit to wood, masonry or similar surfaces where greater load bearing is required.
Material: Steel

One-Hole Strap (Malleable Iron)

1/2"	**31205B**	bulk	100/1000	5/50	NA	2.016	0.625	0.969
3/4"	**31207B**	bulk	100/1000	6/60	NA	2.219	0.750	1.031




Listed
Control No. 43Y8
File No. AW8113

Application: Dry Locations
Use to secure Rigid or I.M.C. conduit to wood, masonry or similar surfaces where greater load bearing is required.

Clamp Back

1/2"	**33205B**	bulk	25/250	2.5/25	NA	2.297	1.031
3/4"	**33207B**	bulk	25/250	2.8/27.5	NA	2.438	1.172



Listed
Control No. 43Y8
File No. AP981IJ

Application: Dry Locations
Use to provide spacing between mounting surface and Rigid conduit.
Material: Malleable Iron