




DIMENSIONS (in inches)

TRADE SIZE	HALEX PART #	CTN/CASE QTY	CTN/CASE WT(lbs.)	A	B
Compression Connectors					**STEEL**
1/2"	**63505B**	25/100	3.2/13	1.43	1.17
3/4"	**63507B**	25/100	5/20	1.48	1.43
1"	**63510**	10	3.6	1.48	1.43
1 1/4"	**63512**	5	2	1.96	2.16
1 1/2"	**63515**	5	2.5	2.15	2.38
2"	**63520**	2	2	2.24	2.88


Application: Indoors. Use to join threadless Rigid or IMC conduit to a steel outlet box or other metal enclosure. **Material:** Steel, Zinc electro-plate **Features:** Concrete-Tight





Compression Connectors					**ZINC DIE CAST**
2 1/2"	**02125B**	12	12.5	2.62	1.00
3"	**02130B**	12	16.4	2.75	1.06
3 1/2"	**02130B**	10	17	2.83	1.14
4"	**02135B**	6	12	2.84	1.14
WITH INSULATED THROAT					
2 1/2"	**82125B**	12	12.5	2.62	1.00
3"	**82130B**	12	16.4	2.75	1.06
3 1/2"	**82135B**	10	17	2.83	1.14
4"	**82140B**	6	12	2.84	1.14


Application: Indoors. Use to connect EMT, threadless Rigid or IMC conduit to a steel outlet box or other material enclosure. **Material:** Zinc Die Cast **Features:** Concrete-Tight





Compression Couplings					**STEEL**
1/2"	**96361**	10	1.6	1.76	1.17
3/4"	**96362**	8	2	1.93	1.43
1"	**63610**	10	4.8	2.19	1.77
1 1/4"	**63612**	5	2.8	2.51	2.16
1 1/2"	**63615**	5	4.5	2.77	2.38
2"	**63620**	2	2	2.78	2.88

Application: Indoors. Use to join two lengths of threadless Rigid or IMC conduit. **Material:** Steel, Zinc electro-plate **Features:** Concrete-Tight





Compression Couplings					**ZINC DIE CAST**
2 1/2"	**02225B**	12	15.5	3.29	3.51
3"	**02230B**	12	20.6	3.42	4.21
3 1/2"	**02235B**	10	20.5	3.51	4.75
4"	**02240B**	6	15	3.54	5.32

Application: Indoors. Use to join two lengths of EMT, threadless Rigid or IMC conduit together. **Material:** Zinc Die Cast **Features:** Concrete-Tight