
45° Elbow

TRADE SIZE	HALEX PART#	PCS/ UNIT	CTN/CASE QTY	CTN/CASE WT	UPC BAR CODED SELL UNIT	DIMENSIONS Min. UL Radius (in inches)	DIMENSIONS A Offset (in inches)
1/2"	64505	bulk	10/50	2.4/12	UPC on product	4.000	6.250
3/4"	64507	bulk	10/40	4/16	UPC on product	4.500	7.060
1"	64510	bulk	25	18	UPC on product	5.750	9.250
1 1/4"	64512	bulk	20	20	UPC on product	7.250	10.500
1 1/2"	64515	bulk	15	22.1	UPC on product	8.250	12.625
2"	64520	bulk	10	21	UPC on product	9.500	14.250




Listed
File No. 43Y8
File No. AP98113

Application: Indoors Only
Use to allow a 45° change of direction in a run of E.M.T. conduit.
Material: Galvanized Steel

E.M.T.-to-Flex Combination Coupling (Compression-to-Screw-In Type)

						A	B
1/2"	**04905B**	bulk	50/500	4/40	NA	0.84	1.10
3/4"	**04907B**	bulk	25/250	2.8/27.5	NA	0.95	1.30
1"	**04910**	tray box	25/250	5.8/57.5	UPC on product	1.11	1.62
BAGGED ITEMS							
1/2"	**20491**	2/bag	30 bags	9.6	UPC on bag	0.84	1.10
3/4"	**20492**	2/bag	20 bags	8.8	UPC on bag	0.95	1.30




Listed
Control No. 862G
Control No. 43Y8
File No. AP98113
File No. 18130

Application: Indoors Or Outdoors
Use to join E.M.T. conduit to flexible metallic conduit.
Material: Zinc Die Cast


also see page 22

E.M.T.-to-Flex Combination Coupling (Set-Screw Type)


						A min	Ajnax	B
1/2"-3/8"	**15303B**	bulk	50/500	4/40	NA	0.17	0.63	1.35
1/2"-1/2"	**15305B**	bulk	25/250	2.5/25	NA	0.75	0.95	1.65
3/4"-3/4"	**15307B**	bulk	25/250	3.6/36	NA	-	1.11	1.98
BAGGED ITEMS								
1/2"-3/8"	**91530**	1/bag	50 bags	4	UPC on bag	0.17	0.63	1.35
1/2"-1/2"	**91531**	1/bag	40 bags	4	UPC on bag	0.75	0.95	1.65



Listed
File No. 43Y8
File No. AP98113



Application: Indoors Or Outdoors
Use to join E.M.T. conduit to flexible metallic conduit.
Material: Zinc Die Cast




also see page 11

E.M.T.-to-Flex Combination Coupling
(Compression-to-Screw-In Type)


TRADE SIZE	HALEX PART#	PCS/ UNIT	CTN/CASE QTY	CTN/CASE WT	UPC BAR CODED SELL UNIT	DIMENSIONS A MIN	A MAX	B (in inches)
1/2"	**04905B**	bulk	50/500	4/40	NA		0.84	1.10
3/4"	**04907B**	bulk	25/250	2.8/27.5	NA		0.95	1.30
1"	**04910**	tray box	25	5.8	UPConproduct		1.11	1.62
BAGGED ITEMS								
1/2"	**20491**	2/bag	30 bags	9.6	UPConbag		0.84	1.10
3/4"	**20492**	2/bag	20 bags	8.8	UPC on bag		0.95	1.30

Application: Indoors Or Outdoors
Use to join E.M.T. conduit to flexible metallic conduit.
Material: Zinc Die Cast

also see page 11




E.M.T.-to-Flex Combination Coupling (Set-screw Type)



Listed
Control No. 862G
Control No. 43Y8
File No. AP9813
File No. 18UO

1/2"-3/8"	**15303B**	bulk	50/500	4/40	NA	0.17	0.63	1.35
1/2"-1/2"	**15305B**	bulk	25/250	2.5/25	NA	0.75	0.95	1.65
3/4"-3/4"	**15307B**	bulk	25/250	3.6/36	NA	-	1.11	1.98
BAGGED ITEMS								
1/2"-3/8"	**91530**	1/bag	50 bags	4	UPC on bag	0.17	0.63	1.35
1/2"-1/2"	**91531**	1/bag	40 bags	4	UPC on bag	0.75	0.95	1.65

Application: Indoors Or Outdoors
Use to join E.M.T. conduit to flexible metallic conduit.
Material: Zinc Die Cast



BX One-Hole Strap

3/8"	**62181B**	bulk	100/1000	1/10	UPC on carton	0.96		0.50
BAGGED ITEMS								
3/8"	**96213**	4/bag	75 bags	.75	UPC on bag	0.96		0.50
3/8"	**26211**	10/bag	20 bags	2	UPC on bag	0.96		0.50

Application: Indoors Only
Use to secure BX cable to a wood, masonry or similar surface.
Material: Steel