

Liquid-Tight Connectors — Zinc Die Cast

ONE-PIECE

TRADE SIZE	HALEX PART #	CTN/CASE QTY	CTN/CASE WT (LBS)	DIMENSIONS (IN INCHES) A	B	C
1/2″	**06305B**	25/100	3.5/14	1.661	0.521	1.543
3/4″	**06307B**	10/100	2.1/21	1.721	0.521	1.790
WITH INSULATED THROAT						
1/2″	**86305B**	25/100	3.5/14	1.741	0.591	1.543
3/4″	**86307B**	10/100	2.1/21	1.801	0.600	1.790



APPLICATION: INDOORS OR OUTDOORS. Use to connect flexible metallic or type B non-metallic liquid-tight conduit to a steel outlet box or other metal enclosure or hub. **MATERIAL:** Zinc Die Cast. **FEATURES:** New one-piece design allows for quick and easy installation. Push in and twist conduit counter-clockwise until seated. Tighten screw to 35 in-lbs. and install into enclosure. It's that easy! **CERTIFICATIONS:** TO UL AND CSA REQUIREMENTS.



Liquid-Tight Connectors — Zinc Die Cast

MULTI-PIECE

TRADE SIZE	HALEX PART #	CTN/CASE QTY	CTN/CASE WT (LBS)	DIMENSIONS (IN INCHES) A	B	C
3/8″(1/2 ko)	**16203B**	25/100	5/20	1.32	0.50	1.18
1/2″	**16205B**	25/100	4.3/17	1.40	0.50	1.29
3/4″	**16207B**	10/100	2.5/25	1.45	0.50	1.57
1″	**16210B**	10/100	4.4/44	2.06	0.58	1.81
1 1/4″	**16212B**	4/40	2.7/26.8	2.06	0.61	2.18
1 1/2″	**16215B**	2/20	1.8/18.4	2.09	0.63	2.51
2″	**16220B**	2/20	2.8/28	2.15	0.63	3.03
WITH INSULATED THROAT						
3/8″(1/2 ko)	**96203B**	25/100	5/20	1.37	0.50	1.18
1/2″	**96205B**	25/100	4.3/17	1.45	0.50	1.29
3/4″	**96207B**	10/100	2.5/25	1.50	0.50	1.57
1″	**96210B**	10/100	4.4/44	2.11	0.63	1.81
1 1/4″	**96212B**	4/40	2.7/26.8	2.11	0.66	1.81
1 1/2″	**96215B**	2/20	1.8/18.4	2.11	0.68	2.18
2″	**96220B**	2/20	2.8/28	2.14	0.68	2.51
2 1/2″	**96225B**	1	2.7	2.20	0.68	3.03
3″	**96230B**	1	3.06	4.05	1.01	4.34
3 1/2″	**96235B**	1	3.80	4.30	1.05	4.78
4″	**96240B**	1	4.31	4.75	1.05	5.19




APPLICATION: INDOORS OR OUTDOORS. Use to connect flexible metallic or type B non-metallic liquid-tight conduit to a steel outlet box or other metal enclosure or hub. **MATERIAL:** Zinc Die Cast. **MISC:** 3/8″ size fits 1/2″ knockout. **CERTIFICATIONS:** TO UL AND CSA REQUIREMENTS.



90° Liquid-Tight Connectors — Zinc Die Cast

ONE-PIECE

TRADE SIZE	HALEX PART #	CTN/CASE QTY	CTN/CASE WT (LBS)	DIMENSIONS (IN INCHES) A	B	C
1/2″	**06805B**	25/100	4.6/18.4	2.47	1.520	0.521
3/4″	**06807B**	10/100	2.8/28	2.761	1.695	0.521



APPLICATION: INDOORS OR OUTDOORS. Use to connect flexible metallic or type B non-metallic liquid-tight conduit to a steel outlet box or other metal enclosure or hub. **MATERIAL:** Zinc Die Cast. **FEATURES:** New one-piece design allows for quick and easy installation. Push in and twist conduit counter-clockwise until seated. Tighten screw to 35 in-lbs. and install into enclosure. It's that easy! **CERTIFICATIONS:** TO UL AND CSA REQUIREMENTS.




90° Liquid-Tight Connectors — Zinc Die Cast



TRADE SIZE	HALEX PART #	CTN/CASE QTY	CTN/CASE WT (LBS)	DIMENSIONS (IN INCHES) A	B	C
MULTI-PIECE						
3/8″(1/2″ko)	**16903B**	25/100	7.5/30	1.45	0.50	1.66
1/2″	**16905B**	25/100	6.8/27	1.45	0.50	1.77
3/4″	**16907B**	10/100	3.9/39	1.60	0.50	1.95
1″	**16910B**	5/50	3.3/33	3.46	0.58	3.86
1 1/4″	**16914B**	4/40	4.2/42	3.37	0.67	3.99
1 1/2″	**16915B**	2/20	2.6/25.8	4.28	0.61	5.04
2″	**16920B**	2/20	3.9/39.2	4.21	0.71	5.06
WITH INSULATED THROAT						
3/8″(1/2″ko)	**96903B**	25/100	7.5/30	1.50	0.55	1.66
1/2″	**96905B**	25/100	6.8/27	1.50	0.55	1.77
3/4″	**96907B**	10/100	3.9/39	1.65	0.55	1.95
1″	**96910B**	5/50	3.3/33	3.51	0.63	3.86
1 1/4″	**96912B**	4/40	4.2/42	3.47	0.72	3.99
1 1/2″	**96915B**	2/20	2.6/25.8	4.33	0.66	5.04
2″	**96920B**	2/20	3.9/39.2	4.26	0.76	5.06
2 1/2″	**96925B**	1	3.48	4.26	0.76	5.06
3″	**96930B**	1	5.25	4.05	1.00	3.86
3 1/2″	**96935B**	1	6.25	4.30	1.03	4.13
4″	**96940B**	1	8.08	4.75	1.05	4.52

APPLICATION: INDOORS OR OUTDOORS. Use to connect flexible metallic or type B non-metallic liquid-tight conduit to a steel outlet box or other metal enclosure or hub. **MATERIAL:** Zinc Die Cast. **MISC:** 3/8″ size fits 1/2″ knockout. **CERTIFICATIONS:** TO UL AND CSA REQUIREMENTS.



Liquid-Tight Connectors — Steel/Malleable Iron



TRADE SIZE	HALEX PART #	CTN/CASE QTY	CTN/CASE WT (LBS)	DIMENSIONS (IN INCHES) A	B	C
STRAIGHT						
3/8″(1/2 ko)	**66203B**	25/100	3.85/15.5	1.125	0.500	1.125
1/2″	**66205B**	25/100	4.4/17.7	1.250	0.500	1.250
3/4″	**66206B**	10/100	2.9/28.8	1.250	0.500	1.5625
1″	**66210B**	5/20	2.0/8.0	1.4375	0.625	1.822
1 1/4″	**66212B**	5/20	2.8/11.0	1.500	0.6875	2.250
1 1/2″	**66215B**	2/20	1.45/14.5	1.625	0.750	2.4375
2″	**66220B**	2/20	2.0/2.0	1.750	0.750	3.000
INSULATED THROAT						
3/8″(1/2 ko)	**86203B**	25/100	3.9/15.7	1.125	0.5625	1.125
1/2″	**86205B**	25/100	4.5/18.0	1.250	0.5625	1.250
3/4″	**86207B**	10/100	2.9/29	1.250	0.5625	1.5625
1″	**86210B**	5/20	2.0/8.0	1.4375	0.6875	1.8215
1 1/4″	**86212B**	5/20	2.8/11.2	1.500	0.750	2.250
1 1/2″	**86215B**	2/20	1.45/14.5	1.625	0.8215	2.4375
2″	**86220B**	2/20	2.0/2.0	1.750	0.8215	3.000
2 1/2″	**86225B**	1	2.488			
3″	**86230B**	1	3.780			
3 1/2″	**86235B**	1	5.072			
4″	**86240B**	1	6.364			

APPLICATION: INDOORS OR OUTDOORS. Use to connect flexible metallic liquid-tight conduit to a steel outlet box or other metal enclosure or hub. **MATERIAL:** Steel/Malleable Iron (1/2″ – 1″ Steel; 1 1/4″ – 2″ Malleable Iron). **MISC:** 3/8″ size fits 1/2″ knockout. **CERTIFICATIONS:** TO UL AND CSA REQUIREMENTS.