
Solderless Terminal Lug




Listed
Control No. 43Y8
File No. AP98113

TRADE SIZE	HALEX PART #	PCS/ UNIT	CTN/CASE QTY	CTN/CASE WT	UPC BAR CODED SELL UNIT	DIMENSIONS A (in inches)	B	C
#14-#6	**32606B**	bulk	250	7.5	NA	0.438	1.125	0.375
#8-#2	**32602B**	bulk	200	10	NA	0.500	1.438	0.500
#1/0-#8	**32510B**	bulk	100	11	NA	0.625	1.875	0.625
CARDED ITEMS								
#14-#10	**43269**	2/card	10 cards	0.5	UPC on card	0.281	0.938	0.313
#14-#6	**43266**	2/card	10 cards	0.3	UPC on card	0.438	1.125	0.375
#8-#2	**43262**	2/card	10 cards	1.4	UPC on card	0.500	1.438	0.500
#3/0-#4	**43253**	1/card	10 cards	1.6	UPC on card	0.750	2.250	0.750
#4/0-#2/0	**43254**	1/card	10 cards	2.4	UPC on card	1.000	2.375	1.000

Application: Indoors or Outdoors
Use to connect a wire or wires to a metal enclosure.
Material: Electrolytic Copper
Features: One Hole, Single Collar


Snap-In Bushing



1/2"	**72505B**	bulk	100	0.5	NA	0.72	0.99	0.36
3/4"	**72507B**	bulk	100	0.6	NA	0.95	1.22	0.36
1"	**72510B**	bulk	50	0.4	NA	1.20	1.51	0.37
1 1/4"	**72512B**	bulk	50	0.6	NA	1.55	1.86	0.43
1 1/2"	**72515B**	bulk	25	0.5	NA	1.74	2.21	0.53
2"	**72520B**	bulk	25	1	NA	2.20	2.65	0.75

Application: Indoors Only
Use to protect non-metallic cable from damage when running cable through metal studs.
Material: PVC

"Universal" Snap-In Bushing



	72599B	bulk	25	0.6	NA	1.20	2.48	0.44
BAGGED ITEMS								
	27250	5/bag	20 bags	2.4	UPC on bag	1.20	2.48	0.44
	27259	25/bag	6 bags	3.6	UPC on bag	1.20	2.48	0.44

Application: Indoors Only
Use to protect non-metallic cable from damage when running cable through metal studs.
Material: PVC
Features: Fits a variety of pre-punched metal stud openings

Duct Seal



1 Lb. Slug	**79910B**	bulk	1/50	1/50
5 Lb. Slug	**79950B**	bulk	1/10	5/50

Application: Indoors or Outdoors
Use to seal around junction boxes, flashings, and service entrance locations.
Features: Service Temperature Range: -30°F - 100°F; Compound is pliable and noncorrosive to metals; Compound can be painted.