


TRADE SIZE	HALEX PART #	CTN/CASE QTY	CTN/CASE WT (LBS)	DIMENSIONS (IN INCHES) A	B
EMT-To-Flex Combination Couplings					**Zinc Die Cast**
COMPRESSION TO SCREW-IN TYPE					
1/2″-1/2″	**04905B**	50/500	4/40	0.84	1.00
3/4″-3/4″	**04907B**	25/250	2.8/27.5	0.95	1.19
1″-1″	**04910**	10	1.7	1.11	1.48




APPLICATION: INDOORS ONLY – Use to join EMT conduit to flexible metallic conduit. **MATERIAL:** Zinc Die Cast. **TYPE:** Compression To Screw-In. **SUITABLE FOR:** 1/2″ steel, steel reduced wall, and aluminum flexible metal conduit to EMT, 3/4″-1″ flexible metal conduit to EMT. **CERTIFICATIONS:** TO UL AND CSA REQUIREMENTS.



TRADE SIZE	HALEX PART#	CTN/CASE QTY	CTN/CASE WT (LBS)	DIMENSIONS (IN INCHES) A	B	C
EMT-To-Flex Combination Couplings						**Zinc Die Cast**
SET-SCREW TYPE						
1/2″-1/2″	**15305B**	25/250	2.5/25	0.75	0.95	1.65
3/4″-3/4″	**15307B**	25/250	3.6/36	0.91	1.11	1.98




APPLICATION: INDOORS ONLY – Use to join EMT conduit to flexible metal conduit. **MATERIAL:** Zinc Die Cast. **TYPE:** Set-Screw. **CERTIFICATIONS:** TO UL AND CSA REQUIREMENTS.



TRADE SIZE	HALEX PART #	CTN/CASE QTY	CTN/CASE WT (LBS)	DIMENSIONS (IN INCHES) A	B
EMT-To-Non-Metallic Combination Couplings					**Zinc Die Cast**
1/2″-NM	**15303B**	50/500	4/40	0.17	0.63	1.35



APPLICATION: INDOORS ONLY – Use to join EMT conduit to non-metallic sheathed cable (1) 14-2 to (1) 10-3, (2) 14-2 to (2) 12-3. **MATERIAL:** Zinc Die Cast. **TYPE:** Set-Screw. **CERTIFICATIONS:** TO UL AND CSA REQUIREMENTS.



TRADE SIZE	HALEX PART #	CTN/CASE QTY	CTN/CASE WT (LBS)	DIMENSIONS (IN INCHES) A	B	C
EMT Insulating Bushings						**Polyethylene**
1/2"	**75005B**	100/1000	0.4/4.0	0.725	0.181	0.570
3/4"	**75007B**	75/750	0.35/3.5	0.940	1.030	0.760
1"	**75010B**	50/500	0.35/3.5	0.945	1.300	0.635
1 1/4"	**75012B**	25/250	0.25/2.5	1.240	1.655	0.625
1 1/2"	**75015B**	25/250	0.3/3.0	1.44	1.918	0.625
2"	**75020B**	25/250	0.45/4.5	1.870	2.380	0.625



APPLICATION: INDOORS ONLY – Use to protect cables from abrasion from edge of EMT. **MATERIAL:** Polyethylene. **FEATURES:** Holds firmly in place while pulling various cables, i.e. power, cable TV, telephone/modem, alarm/security systems. Meets 2008 NEC code requirements for 300.16 (B) protection.

NEW



TRADE SIZE	HALEX PART #	CTN/CASE QTY	CTN/CASE WT (LBS)	
EMT-To-Rigid Combination Couplings				**Steel**
SET-SCREW TYPE				
1/2"-1/2"	**15304B**	25	3.5	
3/4"-3/4"	**15306B**	25	6.1	

APPLICATION: INDOORS ONLY – Use to join EMT conduit to Rigid metal conduit. **MATERIAL:** Steel, Zinc Electro-Plate. **TYPE:** Set-Screw.