


TRADE SIZE	HALEX PART #	CTN/CASE QTY	CTN/CASE WT (LBS)	DIMENSIONS (IN INCHES) A	B
FLEX-To-EMT Combination Couplings					**Zinc Die Cast**
COMPRESSION TO SCREW-IN TYPE					
1/2″	**04905B**	50/500	4/40	0.84	1.10
3/4″	**04907B**	25/250	2.8/27.5	0.95	1.30
1″	**04910**	10	1.7	1.11	1.62




APPLICATION: INDOORS ONLY - Use to join EMT conduit to flexible metallic conduit **MATERIAL:** Zinc Die Cast. **TYPE:** Compression to Screw-in. **SUITABLE FOR:** 1/2″ steel, steel reduced wall, and aluminum flexible metal conduit to EMT, 3/4″-1″ flexible metal conduit to EMT. **CERTIFICATIONS:** TO UL AND CSA REQUIREMENTS.



TRADE SIZE	HALEX PART #	CTN/CASE QTY	CTN/CASE WT (LBS)	DIMENSIONS (IN INCHES) A (MIN)	A (MAX)	B
FLEX-To-EMT Combination Couplings						**Zinc Die Cast**
SET-SCREW TYPE						
1/2″-1/2″	**15305B**	25/250	2.5/25	0.75	0.95	1.65
3/4″-3/4″	**15307B**	25/250	3.6/36	—	1.11	1.98



APPLICATION: INDOORS ONLY - Use to join EMT conduit to flexible metal conduit. **MATERIAL:** Zinc Die Cast. **TYPE:** Set-Screw Type. **CERTIFICATIONS:** TO UL AND CSA REQUIREMENTS.



TRADE SIZE	HALEX PART #	CTN/CASE QTY	CTN/CASE WT (LBS)	DIMENSIONS (IN INCHES) A	B
AC (MC) One-Hole Straps					**Steel**
3/8″	**62181B**	100/1000	1/10	0.96	0.50



APPLICATION: INDOORS ONLY - Use to secure AC/MC cable to a wood, masonry or similar surface. **MATERIAL:** Steel, Zinc Electro-Plate.



TRADE SIZE	HALEX PART #	CTN/CASE QTY	CTN/CASE WT (LBS)	DIMENSIONS (IN INCHES) A	B
Set-Screw Connectors					**Zinc Die Cast**
1/2″	**04805B**	25/250	2.5/25	0.94	1.46
3/4″	**04807B**	25/250	3.8/38	1.15	1.56
WITH INSULATED THROAT					
1/2″	**84805B**	25/250	2.5/25	0.94	1.51
3/4″	**84807B**	25/250	3.8/38	1.15	1.61



APPLICATION: INDOORS ONLY - In a dry location, use to connect steel or aluminum flexible metallic conduit to a steel outlet box or other metal enclosure. **MATERIAL:** Zinc Die Cast. **CERTIFICATIONS:** TO UL AND CSA REQUIREMENTS.



TRADE SIZE	HALEX PART #	CTN/CASE QTY	CTN/CASE WT (LBS)	DIMENSIONS (IN INCHES) A (MIN)	A (MAX)	B	C
Clamp-Combination Connectors							**Zinc Die Cast**
3/8″(1/2" ko)	**05703B**	100/1000	6/60	0.18	0.64	1.18	0.34



APPLICATION: INDOORS - In a dry location, use to connect flexible metallic conduit, AC, MC, or NM cable to steel outlet box or other enclosure. **MATERIAL:** Zinc Die Cast. **MISC:** 3/8″ size fits 1/2″ knockout. **SUITABLE FOR:** #14/2 thru 12/3 with ground NM sheathed cable, #14-2 wire steel armored cable, 3/8″ steel flexible metal conduit, alum. cont. corrugated metal clad cable 0.365-0.519″ dia., alum. smooth sheath metal clad cable 0.345-0.525″ dia., alum. interlocked metal clad cable 0.455-0.575″ dia., rect. alum. cont. corrugated metal clad cable 0.277″ x 0.375″, steel interlocked metal clad cable 0.435-0.547″ dia. **CERTIFICATIONS:** TO UL AND CSA REQUIREMENTS.