

## EMT-To-EMT Pull Elbows — Zinc Die Cast



| TRADE SIZE | HALEX PART # | CTN/CASE QTY | CTN/CASE WT (LBS) | DIMENSIONS (IN INCHES) A | B |
|---|---|---|---|---|---|
| ***WITHOUT GASKET*** | | | | | |
| 1/2″ | **14405** | 15 | 2.8 | 1.31 | 0.97 |
| 3/4″ | **14407** | 10 | 3.7 | 1.50 | 1.20 |
| ***WITH NEOPRENE GASKET*** | | | | | |
| 1/2″ | **94405** | 10 | 2.4 | 1.31 | 0.97 |
| 3/4″ | **94407** | 5 | 1.9 | 1.50 | 1.20 |
| 1″ | **94410** | 5 | 3.4 | 1.85 | 1.52 |

**APPLICATION:** DRY LOCATIONS – Use to connect EMT conduit together at a 90° bend**. MATERIAL:** Zinc Die Cast. **TYPE:** Set-Screw. **FEATURES:** Removable aluminum cover facilitates wire pulling. **CERTIFICATIONS:** TO UL AND CSA REQUIREMENTS.



## EMT-To-Box Pull Elbows — Zinc Die Cast




| TRADE SIZE | HALEX PART # | CTN/CASE QTY | CTN/CASE WT (LBS) | DIMENSIONS (IN INCHES) A | B |
|---|---|---|---|---|---|
| ***WITHOUT GASKET*** | | | | | |
| 1/2″ | **14305** | 10 | 2.2 | 1.31 | 0.97 |
| 3/4″ | **14307** | 5 | 1.8 | 1.50 | 1.20 |

**APPLICATION:** DRY LOCATIONS – Use to connect EMT conduit to a metal box or enclosure to form a 90° bend**. MATERIAL:** Zinc Die Cast. **TYPE:** Set-Screw. **FEATURES:** Removable aluminum cover facilitates wire pulling. Die cast locknut provided. **CERTIFICATIONS:** TO UL AND CSA REQUIREMENTS.



## EMT/Rigid-To-EMT/Rigid Combo Elbows — Zinc Die Cast





| TRADE SIZE | HALEX PART # | CTN/CASE QTY | CTN/CASE WT (LBS) | DIMENSIONS (IN INCHES) A | B |
|---|---|---|---|---|---|
| ***WITH NEOPRENE GASKET*** | | | | | |
| 1/2″ | **94505** | 10 BAGS | 2.0 | 1.31 | 0.97 |
| 3/4″ | **94507** | 10 BAGS | 3.0 | 1.500 | 1.200 |
| 1″ | **94510** | 5 | 2.9 | 1.85 | 1.52 |

**APPLICATION:** INDOORS OR OUTDOORS. Use as a wire pulling elbow to facilitate wire pulling through a sharp bend in a run of EMT or threaded Rigid or IMC conduit. Removable cover provides easy access to facilitate wire pulling. Not listed for wet locations**. MATERIAL:** Zinc Die Cast. **CERTIFICATIONS:** TO UL AND CSA REQUIREMENTS.



## EMT/Rigid-To-Box Combo Elbows — Zinc Die Cast




| TRADE SIZE | HALEX PART # | CTN/CASE QTY | CTN/CASE WT (LBS) | DIMENSIONS (IN INCHES) A | B |
|---|---|---|---|---|---|
| ***WITH NEOPRENE GASKET*** | | | | | |
| 1/2″ | **94705** | 10 BAGS | 1.90 | 1.310 | 1.020 |
| 3/4″ | **94707** | 5 BAGS | 1.50 | 1.500 | 1.270 |

**APPLICATION:** INDOORS OR OUTDOORS. Use to connect a run of EMT or threaded Rigid or IMC conduit to an outlet box, or other metal enclosure. Removable cover provides easy access to facilitate wire pulling. Not listed for wet locations**. MATERIAL:** Zinc Die Cast. **CERTIFICATIONS:** TO UL AND CSA REQUIREMENTS.



## EMT-To-EMT Inside-Corner Pull Elbows — Zinc Die Cast



| TRADE SIZE | HALEX PART # | CTN/CASE QTY | CTN/CASE WT (LBS) | DIMENSIONS (IN INCHES) A | B |
|---|---|---|---|---|---|
| ***WITHOUT GASKET*** | | | | | |
| 1/2″ | **14601B** | 15 | 2.7 | 1.81 | 1.00 |
| 1/2″ | **14605** | 15 | 2.7 | 1.81 | 1.00 |
| 3/4″ | **14607** | 8 | 1.9 | 2.00 | 1.25 |

**APPLICATION:** INDOORS ONLY – Use to connect EMT conduit together on a 90° inside corner**. MATERIAL:** Zinc Die Cast. **TYPE:** Set-Screw. **FEATURES:** Removable cover facilitates wire pulling. **CERTIFICATIONS:** TO UL AND CSA REQUIREMENTS.