Reducing Washers, Knockout Blanks, Bushing Pennies, Fixture Stems

Applications




- Reducing washer: to reduce a knockout or sliphole in a sheet metal enclosure to a smaller trade size.
- Knockout blank: to close a knockout or sliphole in a sheet metal enclosure.
- Bushing penny: used inside a bushing to prevent foreign material from entering the conduit.
- Fixture stems: to suspend fixtures from threaded rods.

Material

- Washers, blanks and pennies: steel
- Fixture stem: malleable iron

Certifications and Compliances

- UL Standard: 514B
- UL Listed: E14817
- CSA Standard: C22.2 No. 18.3
- cUL Listed: E14817
- NEMA: FB-1

Trade Size (Inches)	Dimensions in Millimeters (Inches) A	B	C	Weight per 100 kg (lb)	Catalog Number	
Reducing Washers — Steel						
3/4 to 1/2	34.0 (1.34)	22.4 (0.88)	-	0.54 (1.20)	**RW75-50**	
1 to 1/2	42.9 (1.69)	22.4 (0.88)	-	1.09 (2.40)	**RW100-50**	
1 to 3/4	42.9 (1.69)	28.2 (1.11)	-	0.91 (2.00)	**RW100-75**	
1-1/4 to 1/2	51.6 (2.03)	22.4 (0.88)	-	2.27 (5.00)	**RW125-50**	
1-1/4 to 3/4	51.6 (2.03)	28.2 (1.11)	-	1.99 (4.40)	**RW125-75**	
1-1/4 to 1	51.6 (2.03)	35.1 (1.38)	-	1.36 (3.00)	**RW125-100**	
1-1/2 to 1/2	57.9 (2.28)	22.4 (0.88)	-	2.99 (6.60)	**RW150-50**	
1-1/2 to 3/4	57.9 (2.28)	28.2 (1.11)	-	2.72 (6.00)	**RW150-75**	
1-1/2 to 1	57.9 (2.28)	35.1 (1.38)	-	2.27 (5.00)	**RW150-100**	
1-1/2 to 1-1/4	57.9 (2.28)	43.9 (1.73)	-	1.81 (4.00)	**RW150-125**	
2 to 1/2	69.9 (2.75)	22.4 (0.88)	-	4.54 (10.00)	**RW200-50**	
2 to 3/4	69.9 (2.75)	28.2 (1.11)	-	3.63 (8.00)	**RW200-75**	
2 to 1	69.9 (2.75)	35.1 (1.38)	-	3.63 (8.00)	**RW200-100**	
2 to 1-1/4	69.9 (2.75)	43.9 (1.73)	-	3.18 (7.00)	**RW200-125**	
2 to 1-1/2	69.9 (2.75)	50.3 (1.98)	-	2.27 (5.00)	**RW200-150**	
Snap-in Knockout Blanks — Steel ①						
1/2	26.9 (1.06)	7.9 (0.31)	-	0.45 (1.00)	**S50**	
3/4	31.8 (1.25)	7.9 (0.31)	-	0.91 (2.00)	**S75**	
1	38.1 (1.50)	8.6 (0.34)	-	1.36 (3.00)	**S100**	
1-1/4	46.0 (1.81)	7.9 (0.31)	-	1.45 (3.20)	**S125**	
1-1/2	56.4 (2.22)	9.7 (0.38)	-	2.18 (4.80)	**S150**	
2	68.3 (2.69)	9.7 (0.38)	-	2.72 (6.00)	**S200**	
Bushing Pennies — Steel ①						
1/2	18.3 (0.72)	-	-	0.32 (0.70)	**P50**	
3/4	22.4 (0.88)	-	-	0.50 (1.10)	**P75**	
1	27.7 (1.09)	-	-	0.82 (1.80)	**P100**	-
1-1/4	38.9 (1.53)	-	-	1.54 (3.40)	**P125**	
1-1/2	43.7 (1.72)	-	-	1.81 (4.00)	**P150**	
Open Type No Bolt Fixture Stems — Malleable Iron						
3/8 Male	49.3 (1.94)	17.5 (0.69)	38.1 (1.50)	3.63 (8.00)	**NBFS-38**	
3/8 Male 1/8 Female	49.3 (1.94)	17.5 (0.69)	38.1 (1.50)	3.63 (8.00)	**NBFS-38M**	

① *Not UL Listed.*

© April 2015