HUBBELL
Wiring Device-Kellems

Straight Blade Devices, Receptacles, Duplex, Compact Hospital Grade, 2-Pole 3-Wire Grounding, 20A 125V, 5- 20R, Red, Single Pack



By Hubbell Wiring Device-Kellems
Catalog # HBL8300HRED

Straight Blade Devices, Receptacles, Duplex, Compact Hospital Grade, 2-Pole 3-Wire Grounding, 20A 125V, 5- 20R, Red, Single Pack

Features

- Slender/compact design
- Impact-resistant finder groove face
- Triple wipe contacts

Application

Hospital Grade

Performance

Electrical - Current Interrupting - Certified for current interrupting at full rated current, Electrical - Dielectric Voltage - Withstands 2,000V minimum, Environmental - Flammability - UL 94 V-0, Environmental - Operating Temperatures - Maximum continuous 75°C, minimum -40°C (w/o impact), Mechanical - Product Identification - Ratings are a permanent part of the device, Mechanical - Terminal Accommodation - #12-#10 AWG stranded or solid copper wire only, Mechanical - Terminal Identification - Terminals identified in accordance with UL 498 and CSA

Specifications

Standards - RoHS Compliance Status	CM
Environmental Conditions	Indoor Dry Unless Protected By Additional Means
Nema Rating	5-20R
Industry Standard(s)	• CSA Certified, C22.2, No. 42 File 285 • Fed. Spec. W-C-596 • NEMA® WD-6 Compliant • UL Listed to UL498 File No. E2186

Conductor

Number Of Wires	3-Wire
Wire Size	#12 AWG to #10 AWG
Number Of Poles	2-Pole

Current

Amperage Rating	20 A
Voltage Rating Description	125 V
Dielectric Strength	Withstands 2,000V minimum
Current Rating	20 A
Voltage Rating	125 V
Wattage	2500 W
Connectivity	Back and Side Wired Screw Terminals
Phase	Single Phase
Current / Amperage Rating	20 A

Dimensions

Length	3.28 in
Display Size	Standard Sized Product
Weight	0.25 lb.
Height	1.05 in
Width	1.33 in
Dimensions	3.28 in x 1.33 in x 1.05 in

General

Color	Red
Style	Slender/Compact
Product Family	Hospital Grade
Specifications	• Automatic Self-grounding Staple - Stainless steel • Base - PBT • Clamping Plate - Nickel plated steel • Contacts - 0.031" (0.8) Brass • Face - Nylon • Ground Contacts - .031 in. (.8) Brass • Mounting Screws - Zinc plated steel • Mounting Strap - .050 in. (1.3) Galvanized steel • Terminal Screws - Brass
UPC	783585247519
Type	Duplex Receptacle
Material - Mounting Hardware	Screw Mounting
Item Type	Traditional Duplex
Material	Nylon

Logistics

Pallet Quantity	3600
Carton Quantity	10

Operational

Operating Temperature	Maximum continuous 75°C and minimum -40°C without Impact
Horsepower - Maximum	1

Product Assets

Catalog [English]
Catalog Page [English]
Catalog Page [English]
Installation Manual [English]
Sales Drawing [English]

A Hubbell brand

© 2026 Hubbell Incorporated. All rights reserved