Section V
tradeSELECT®
netSELECT®

tradeSELECT® **Page**

Decorator Products
- Advantages V-2
- Decorator Quiet Rocker Switches V-3
- Combination Quiet Rocker Switches/Devices V-4
- Weather Resistant, Tamper-Resistant and Standard Receptacles V-5
- Snap-On, Nylon and Metal Wallplates V-6
- Combination Wallplates V-7
- Decorator Frames V-8
- Modular Snap Fit Jacks V-9
- Molded-In Voice/Data/Video V-10

Switches and Receptacles
- Toggle Switches and Combination Switches/Devices V-11
- Three and Four Way Toggle Switches V-12
- Combination Switches/Devices V-13
- Duplex Quick Thread Receptacles V-14
- Duplex and Single Receptacles V-15
- GFCI Receptacles V-16
- Range and Dryer Power Receptacles and Plugs V-17
- Special Use Products V-18

Lighting Controls
- Dimmers and Fan Speed Controls V-19
- Toggle Dimmers and Fan Speed Controls V-20
- Occupancy and Vacancy Sensors V-21

Power Delivery
- Floor Boxes for Wood Floors V-22
- Floor Boxes for Concrete Floors V-24
- Under Cabinet/Counter Power Distribution V-26
- JLOAD® Multimedia Outlet V-27
- Decorator Switches V-28

netSELECT® **V-29**

Structured Wiring
- In-Wall AV Delivery V-30
- HDMI Products V-31
- Advantages and Wiring Layout V-32
- Network Enclosures V-33
- Network Modules V-34
- Audio/Video Modules V-35
- Universal Consolidation Blocks, Patch Panels and Patch Cords V-36
- Accessories V-37

Data Communications and Audio/Video
- Modular Snap Fit Jacks V-38
- Decorator Frames V-39
- Molded-In Voice/Data/Video V-40
- Molded-In Plates V-41
- Telephone Wall Jacks V-42









tradeSELECT®
Decorator Quiet Rocker Switches
Advantages

Smart Style, Good Looks.

Residential Decorator Switches and Receptacles provide more than solid, dependable function alone. Indeed, they are fashion statements, masterfully complementing the look and feel of any room in any home.

A PERFECT MATCH
Residential decorator devices and wallplates blend in beautifully with all kinds of wall coverings.

EASY-ACTIVATE ROCKERS
Ideal for use in assisted-living environments—or any living environment.



FLUSH AND CONTEMPORARY
Sleek, smart and appealing, Residential devices add beautiful, fashionable, highly-styled devices to any home.

MINI-ROCKER SWITCHES
Take up less space and provide full function.

SNAP-ON WALLPLATES
Snap-on wallplates offer a clean, elegant look that can be installed in seconds.



Color Selection



tradeSELECT®
Decorator Quiet Rocker Switches

Features

- Smooth, quiet rocker
- Self-grounding feature is standard
- Ultrasonically welded cover and base
- Operating temperature: -20°C to 60°C
- UL Listed E3896, CSA Certified

Single Pole Decorator Quiet Rocker Switches

Description	Single Pole	Single Pole, Illuminated*	Single Pole, Pilot Light**	Single Pole with ON/OFF Marking
Termination	Self-Grounding, Push, Back and Side Wire	Self-Grounding, Push, Back and Side Wire	Self-Grounding, Push, Back and Side Wire	Self-Grounding, Push, Back and Side Wire
Rating	15A 120-277V AC	15A 120V AC	15A 120V AC	15A 120-277V AC
Almond	**RSD115AL**	**RSD115ILAL**	**RSD115PLAL**	**—**
Black	**RSD115BK**	**—**	**—**	**—**
Brown	**RSD115**	**—**	**—**	**—**
Gray	**RSD115GY**	**—**	**—**	**—**
Ivory	**RSD115I**	**RSD115ILI**	**RSD115PLI**	**RSD115IM**
Light Almond	**RSD115LA**	**RSD115ILLA**	**RSD115PLLA**	**RSD115LAM**
White	**RSD115W**	**RSD115ILW**	**RSD115PLW**	**RSD115WM**

*Note: * Light glows through the top portion of the rocker when switch is in the off position. Does not require a neutral wire.*
*** Light glows through the top portion of the rocker when switch is in the on position. Requires a neutral wire.*



RSD115W



RSD115PLW

Double Pole, Three Way and Four Way Decorator Quiet Rocker Switches

Description	Double Pole	Three Way	Three Way, Illuminated*	Four Way
Termination	Self-Grounding, Back and Side Wire	Self-Grounding, Push, Back and Side Wire	Self-Grounding, Push, Back and Side Wire	Self-Grounding, Back and Side Wire
Rating	15A 120-277V AC	15A 120-277V AC	15A 120V AC	15A 120-277V AC
Almond	**RSD215AL**	**RSD315AL**	**RSD315ILAL**	**RSD415AL**
Black	**RSD215BK**	**RSD315BK**	**—**	**RSD415BK**
Brown	**RSD215**	**RSD315**	**—**	**RSD415**
Gray	**RSD215GY**	**RSD315GY**	**—**	**RSD415GY**
Ivory	**RSD215I**	**RSD315I**	**RSD315ILI**	**RSD415I**
Light Almond	**RSD215LA**	**RSD315LA**	**RSD315ILLA**	**RSD415LA**
White	**RSD215W**	**RSD315W**	**RSD315ILW**	**RSD415W**

*Note: * Light glows through the top portion of the rocker when switch is in the off position. Does not require a neutral wire.*




RSD115WM




RSD215W

Product Dimensions



Single Pole Decorator Switch



Three Way Decorator Switch

tradeSELECT®
Combination Quiet Rocker Switches/Devices
Decorator Products

Features

- Low profile, less than 1 inch deep
- Self-grounding feature is standard
- Operating temperature: -20°C to 60°C
- UL Listed E3896, CSA Certified


RCD111W


RCD101W


RCD108W


RCD109W


Combination Quiet Rocker Switches/Devices

Description	Three (3) Single Pole Switches	Two (2) Single Pole Switches	Single Pole and Three Way Switch	Single Pole Switch, Tamper-Resistant*, 2 Pole, 3 Wire, Receptacle	Single Pole Switch, 2 Pole, 3 Wire Receptacle
Termination	Self-Grounding, Side Wire	Self-Grounding, Side Wire	Self-Grounding, Side Wire	Self-Grounding, Side Wire	Self-Grounding, Side Wire
Rating	15A 120-277V AC	15A 120-277V AC	15A 120-277V AC	15A 120V (switch) 15A 125V (recept.) NEMA 5-15R	15A 120V 15A 125V NEMA 5-15R
Almond	**RCD111AL**	**RCD101AL**	**RCD103AL**	**RCD108ALTR**	**RCD108AL**
Black	**RCD111BK**	**RCD101BK**	**RCD103BK**	**RCD108BKTR**	**RCD108BK**
Gray	**—**	**RCD101GY**	**RCD103GY**	**RCD108GYTR**	**RCD108GY**
Ivory	**RCD111I**	**RCD101I**	**RCD103I**	**RCD108ITR**	**RCD108I**
Light Almond	**RCD111LA**	**RCD101LA**	**RCD103LA**	**RCD108LATR**	**RCD108LA**
White	**RCD111W**	**RCD101W**	**RCD103W**	**RCD108WTR**	**RCD108W**

Description	Two (2) Three Way Switches	Three Way Switch, Tamper-Resistant*, 2 Pole, 3 Wire, Receptacle	Three Way Switch, 2 Pole, 3 Wire Receptacle	Single Pole Switch, Pilot Light, Clear Lens, Amber Neon Bulb	Three Way Switch, Pilot Light, Clear Lens, Amber Neon Bulb
Termination	Self-Grounding, Side Wire	Self-Grounding, Side Wire	Self-Grounding, Side Wire	Self-Grounding, Side Wire	Self-Grounding, Side Wire
Rating	15A 120-277V AC	15A 120V (switch) 15A 125V (recept.) NEMA 5-15R	15A 120V (switch) 15A 125V (recept.) NEMA 5-15R	15A 120V	15A 120V
Almond	**RCD303AL**	**RCD308ALTR**	**RCD308AL**	**RCD109AL**	**RCD309AL**
Black	**RCD303BK**	**RCD308BKTR**	**RCD308BK**	**—**	**—**
Gray	**RCD303GY**	**RCD308GYTR**	**RCD308GY**	**—**	**—**
Ivory	**RCD303I**	**RCD308ITR**	**RCD308I**	**RCD109I**	**RCD309I**
Light Almond	**RCD303LA**	**RCD308LATR**	**RCD308LA**	**RCD109LA**	**RCD309LA**
White	**RCD303W**	**RCD308WTR**	**RCD308W**	**RCD109W**	**RCD309W**

*Note: * See Section X, page X-10 for TR description.*

Pilot Light Wiring Diagram



tradeSELECT®

Weather Resistant, Tamper-Resistant and Standard Receptacles

Decorator Products

Decorator Duplex Receptacles, 2 Pole, 3 Wire

Description	Weather and Tamper-Resistant*	Tamper-Resistant*	Standard	Standard
Termination	Self-Grounding, Push and Side Wire	Self-Grounding, Push and Side Wire	Self-Grounding, Push and Side Wire	Push and Side Wire
Rating	15A 125V NEMA 5-15R	15A 125V NEMA 5-15R	15A 125V NEMA 5-15R	15A 125V NEMA 5-15R
Almond	**RRD15SALWRTR**	**RRD15SALTR**	**RRD15SAL**	**RRD15AL**
Black	**RRD15SBKWRTR**	**RRD15SBKTR**	**RRD15SBK**	**RRD15BK**
Brown	**RRD15SWRTR**	**RRD15STR**	**RRD15S**	**RRD15**
Gray	**RRD15SGYWRTR**	**RRD15SGYTR**	**RRD15SGY**	**RRD15GY**
Ivory	**RRD15SIWRTR**	**RRD15SITR**	**RRD15SI**	**RRD15I**
Light Almond	**RRD15SLAWRTR**	**RRD15SLATR**	**RRD15SLA**	**RRD15LA**
White	**RRD15SWWRTR**	**RRD15SWTR**	**RRD15SW**	**RRD15W**



RRD15SW

Description	Tamper-Resistant*	Standard	Tamper-Resistant*, Without Ears**	Standard, Without Ears**
Termination	Self-Grounding, Eight Push Wire Holes Only #14 AWG	Self-Grounding, Eight Push Wire Holes Only #14 AWG	Self-Grounding, Push and Side Wire	Self-Grounding, Push and Side Wire
Rating	15A 125V NEMA 5-15R	15A 125V NEMA 5-15R	15A 125V NEMA 5-15R	15A 125V NEMA 5-15R
Almond	**RRD15EALTR**	**RRD15EAL**	**RRD15KALTR**	**RRD15KAL**
Black	**RRD15EBKTR**	**RRD15EBK**	**RRD15KBKTR**	**RRD15KBK**
Brown	**RRD15ETR**	**RRD15E**	**RRD15KTR**	**RRD15K**
Gray	**RRD15EGYTR**	**RRD15EGY**	**RRD15KGYTR**	**RRD15KGY**
Ivory	**RRD15EITR**	**RRD15EI**	**RRD15KITR**	**RRD15KI**
Light Almond	**RRD15ELATR**	**RRD15ELA**	**RRD15KLATR**	**RRD15KLA**
White	**RRD15EWTR**	**RRD15EW**	**RRD15KWTR**	**RRD15KW**



RRD15W



RRD15KW

*Note: * See Section X, page X-10 for WR and TR descriptions.*
*** 100 per case, bulk packed. Mounting screws inserted into strap.*

Decorator Single Receptacles, 2 Pole, 3 Wire

Description	Tamper-Resistant*	Standard	Tamper-Resistant*	Standard
Termination	Self-Grounding, Side Wire	Self-Grounding, Side Wire	Self-Grounding, Side Wire	Self-Grounding, Side Wire
Rating	15A 125V NEMA 5-15R	15A 125V NEMA 5-15R	20A 125V NEMA 5-20R	20A 125V NEMA 5-20R
Almond	**RRD151ALTR**	**RRD151AL**	**RRD201ALTR**	**RRD201AL**
Black	**RRD151BKTR**	**RRD151BK**	**RRD201BKTR**	**RRD201BK**
Brown	**RRD151TR**	**RRD151**	**RRD201TR**	**RRD201**
Gray	**RRD151GYTR**	**RRD151GY**	**RRD201GYTR**	**RRD201GY**
Ivory	**RRD151ITR**	**RRD151I**	**RRD201ITR**	**RRD201I**
Light Almond	**RRD151LATR**	**RRD151LA**	**RRD201LATR**	**RRD201LA**
White	**RRD151WTR**	**RRD151W**	**RRD201WTR**	**RRD201W**



RRD151W

Description	Standard	Standard
Termination	Self-Grounding, Side Wire	Self-Grounding, Side Wire
Rating	15A 250V NEMA 6-15R	20A 250V NEMA 6-20R
Almond	**RRD155AL**	**RRD205AL**
Black	**RRD155BK**	**RRD205BK**
Brown	**RRD155**	**RRD205**
Gray	**RRD155GY**	**RRD205GY**
Ivory	**RRD155I**	**RRD205I**
Light Almond	**RRD155LA**	**RRD205LA**
White	**RRD155W**	**RRD205W**




RRD201W

*Note: * See Section X, page X-10 for TR description.*


tradeSELECT®
Snap-On, Nylon and Metal Wallplates
Decorator Products





A subplate is fastened to the device, then a screwless snap-on cover plate is affixed. Four snaps securely hold the cover to the subplate.

Snap-On, Nylon, Two Piece Construction Wallplates



Color	1-Gang, 1-Decorator	2-Gang, 2-Decorator	3-Gang, 3-Decorator	4-Gang, 4-Decorator	5-Gang, 5-Decorator	6-Gang, 6-Decorator
Almond	**RCW1AL**	**RCW2AL**	**RCW3AL**	**RCW4AL**	**RCW5AL**	**RCW6AL**
Ivory	**RCW1I**	**RCW2I**	**RCW3I**	**RCW4I**	**RCW5I**	**RCW6I**
Light Almond	**RCW1LA**	**RCW2LA**	**RCW3LA**	**RCW4LA**	**RCW5LA**	**RCW6LA**
White	**RCW1W**	**RCW2W**	**RCW3W**	**RCW4W**	**RCW5W**	**RCW6W**

Decorator, Standard, Nylon Wallplates

Color	1-Gang, 1-Decorator	2-Gang, 2-Decorator	3-Gang, 3-Decorator	4-Gang, 4-Decorator	5-Gang, 5-Decorator	6-Gang, 6-Decorator
Almond	**NP26AL**	**NP262AL**	**NP263AL**	**NP264AL**	**NP265AL**	**NP266AL**
Black	**NP26BK**	**NP262BK**	**NP263BK**	**NP264BK**	**NP265BK**	**NP266BK**
Brown	**NP26**	**NP262**	**NP263**	**NP264**	**NP265**	**NP266**
Gray	**NP26GY**	**NP262GY**	**NP263GY**	**NP264GY**	**NP265GY**	**NP266GY**
Ivory	**NP26I**	**NP262I**	**NP263I**	**NP264I**	**NP265I**	**NP266I**
Light Almond	**NP26LA**	**NP262LA**	**NP263LA**	**NP264LA**	**NP265LA**	**NP266LA**
White	**NP26W**	**NP262W**	**NP263W**	**NP264W**	**NP265W**	**NP266W**

Decorator, Mid-Size, Nylon Wallplates


Color	1-Gang, 1-Decorator	2-Gang, 2-Decorator	3-Gang, 3-Decorator	4-Gang, 4-Decorator	5-Gang, 5-Decorator	6-Gang, 6-Decorator
Almond	**NPJ26AL**	**NPJ262AL**	**NPJ263AL**	**NPJ264AL**	—	—
Black	**NPJ26BK**	**NPJ262BK**	**NPJ263BK**	**NPJ264BK**	—	—
Brown	**NPJ26**	**NPJ262**	**NPJ263**	**NPJ264**	—	—
Gray	**NPJ26GY**	**NPJ262GY**	**NPJ263GY**	**NPJ264GY**	—	—
Ivory	**NPJ26I**	**NPJ262I**	**NPJ263I**	**NPJ264I**	—	—
Light Almond	**NPJ26LA**	**NPJ262LA**	**NPJ263LA**	**NPJ264LA**	—	—
White	**NPJ26W**	**NPJ262W**	**NPJ263W**	**NPJ264W**	—	—

Decorator, Mid-Size, Metal Wallplates

Material	1-Gang, 1-Decorator	2-Gang, 2-Decorator	3-Gang, 3-Decorator	4-Gang, 4-Decorator	5-Gang, 5-Decorator	6-Gang, 6-Decorator
Brass	**SB26**	**SB262**	—	—	—	—
Brass Plated	**SBP26**	**SBP262**	**SBP263**	—	—	—
Chrome	**SCH26**	**SCH262**	—	—	—	—
S/S 302/304	**SS26**	**SS262**	**SS263**	**SS264**	**SS265**	**SS266**
S/S 430	**SS26L**	**SS262L**	—	—	—	—

tradeSELECT®
Combination Wallplates
Decorator Products

Combination, Nylon, Standard Wallplates



Color	2-Gang, 1-Toggle 1-Decorator	2-Gang, 1-Duplex, 1-Decorator	2-Gang, 1-Blank Box Mount 1-Decorator	3-Gang, 2-Toggle 1-Decorator	3-Gang, 1-Toggle 2-Decorator	4-Gang, 3-Toggle 1-Decorator	4-Gang, 2-Toggle 2-Decorator
Almond	**NP126AL**	**NP826AL**	**NP1326AL**	**NP226AL**	**NP1262AL**	**NP326AL**	**NP2262AL**
Black	**NP126BK**	**NP826BK**	**NP1326BK**	**NP226BK**	**NP1262BK**	**NP326BK**	**NP2262BK**
Brown	**NP126**	**NP826**	**NP1326**	**NP226**	**NP1262**	**NP326**	**NP2262**
Gray	**NP126GY**	**NP826GY**	**NP1326GY**	**NP226GY**	**NP1262GY**	**NP326GY**	**NP2262GY**
Ivory	**NP126I**	**NP826I**	**NP1326I**	**NP226I**	**NP1262I**	**NP326I**	**NP2262I**
Light Almond	**NP126LA**	**NP826LA**	**NP1326LA**	**NP226LA**	**NP1262LA**	**NP326LA**	**NP2262LA**
White	**NP126W**	**NP826W**	**NP1326W**	**NP226W**	**NP1262W**	**NP326W**	**NP2262W**


Combination, Nylon, Mid-Size Wallplates

Color	2-Gang, 1-Toggle 1-Decorator	2-Gang, 1-Duplex, 1-Decorator	2-Gang, 1-Blank Box Mount 1-Decorator	3-Gang, 2-Toggle 1-Decorator	3-Gang, 1-Toggle 2-Decorator	4-Gang, 3-Toggle 1-Decorator	4-Gang, 2-Toggle 2-Decorator
Almond	**NPJ126AL**	**NPJ826AL**	**NPJ1326AL**	**NPJ226AL**	—	—	—
Black	**NPJ126BK**	**NPJ826BK**	—	**NPJ226BK**	—	—	—
Brown	**NPJ126**	**NPJ826**	**NPJ1326**	**NPJ226**	—	—	—
Gray	**NPJ126GY**	**NPJ826GY**	—	**NPJ226GY**	—	—	—
Ivory	**NPJ126I**	**NPJ826I**	**NPJ1326I**	**NPJ226I**	—	—	—
Light Almond	**NPJ126LA**	**NPJ826LA**	**NPJ1326LA**	**NPJ226LA**	—	—	—
White	**NPJ126W**	**NPJ826W**	**NPJ1326W**	**NPJ226W**	—	—	—

Combination, Standard, Metal Wallplates

Material	2-Gang, 1-Toggle 1-Decorator	2-Gang, 1-Duplex, 1-Decorator	2-Gang, 1-Blank Strap Mount 1-Decorator	3-Gang, 2-Toggle 1-Decorator	3-Gang, 1-Toggle 2-Decorator	4-Gang, 3-Toggle 1-Decorator	4-Gang, 2-Toggle 2-Decorator
Brass	**SB126**	**SB826**	—	—	—	—	—
Brass Plated	**SBP126**	—	—	—	—	—	—
Chrome	—	—	—	—	—	—	—
SS 302/304	**SS126**	**SS826**	**SS1426**	**SS226**	—	**SS326**	—
SS 430	**SS126L**	—	—	—	—	—	—

Product Dimensions



Dimensions in Inches (mm)


tradeSELECT®
Decorator Frames
Decorator Products

Features

Decorator frames provide a stylized look for that finishing touch. This allows all devices to match. Multimedia jacks insert into frame for custom configuration.

- Elongated strap for better wall box mounting
- High impact-resistant thermoplastic frame
- UL Listed 1863 - Communication Circuit Accessory and CSA Certified

Customize the jack selections and look



Decorator Frames



Color	1-Gang, 2-Port	1-Gang, 3-Port	1-Gang, 4-Port	1-Gang, 6-Port	1-Gang, Adapter .406" (10.30) Dia. Hole*	1-Gang, Adapter Blank**
Almond	**NS612AL**	**NS613AL**	**NS614AL**	**NS616AL**	**NS621AL**	**NS620AL**
Black	**NS612BK**	**NS613BK**	**NS614BK**	**NS616BK**	—	—
Gray	**NS612GY**	**NS613GY**	**NS614GY**	**NS616GY**	—	—
Ivory	**NS612I**	**NS613I**	**NS614I**	**NS616I**	**NS621I**	**NS620I**
Light Almond	**NS612LA**	**NS613LA**	**NS614LA**	**NS616LA**	**NS621LA**	**NS620LA**
White	**NS612W**	**NS613W**	**NS614W**	**NS616W**	**NS621W**	**NS620W**

*Note: * For use with rotary dimmers or to pull through AV or telephone cable.*
*** To fill an extra decorator opening or to create customized openings.*

tradeSELECT®

Modular Snap Fit Jacks

Decorator Products

Features

netSELECT® Voice/Data Jacks and AV Connectors allow custom creation of multimedia outlets and workstations while maintaining a decorative look.

- Quick and secure snap-in design
- Use with multimedia plates and decorator frames (see pages V-8 and V-39)
- UL Listed and CSA Certified, or cULus Listed 1863 - Communication Circuit Accessory

Molded-In Voice/Low-Speed Data

Description	Modular Snap Fit Cat. 6 Jack	Modular Snap Fit Cat. 5e Jack	Modular Snap Fit USOC Jack
Color			
Almond	**NSJ6AL**	**NSJ5EAL**	**NSJUAL**
Black	**NSJ6BK**	**NSJ5EBK**	**NSJUBK**
Blue	**NSJ6B**	**NSJ5EB**	**NSJUB**
Gray	**NSJ6GY**	**NSJ5EGY**	**NSJUGY**
Green	**NSJ6GN**	**NSJ5EGN**	**NSJUGN**
Ivory	**NSJ6I**	**NSJ5EI**	**NSJUI**
Light Almond	**NSJ6LA**	**NSJ5ELA**	**NSJULA**
Orange	**NSJ6OR**	**NSJ5EOR**	**NSJUOR**
Red	**NSJ6R**	**NSJ5ER**	**NSJUR**
White	**NSJ6W**	**NSJ5EW**	**NSJUW**
Yellow	**NSJ6Y**	**NSJ5EY**	**NSJUY**

Audio/Video Connectors - Standard Bulkhead

Description	Gold F-Type Coupler Bulkhead, Female to Female	Nickel F-Type Coupler Bulkhead, Female to Female	RCA Gold Pass Through, Female to Female, Red Interior	RCA Gold Pass Through, Female to Female, White Interior	RCA Gold Pass Through, Female to Female, Yellow Interior	RCA Gold Pass Through, Female to Female, Blue Interior	RCA Gold Pass Through, Female to Female, Green Interior
Color							
Almond	**SFFGAL**	**NSF70AL**	**SFRCRFFAL**	**SFRCWFFAL**	**SFRCYFFAL**	**SFRCBFFAL**	**SFRCGNFFAL**
Black	**SFFGBK**	**NSF70BK**	**SFRCRFFBK**	**SFRCWFFBK**	**SFRCYFFBK**	**SFRCBFFBK**	**SFRCGNFFBK**
Gray	**SFFGGY**	**NSF70GY**	**SFRCRFFGY**	**SFRCWFFGY**	**SFRCYFFGY**	**SFRCBFFGY**	**SFRCGNFFGY**
Ivory	**SFFGEI**	**NSF70I**	**SFRCRFFEI**	**SFRCWFFEI**	**SFRCYFFEI**	**SFRCBFFEI**	**SFRCGNFFEI**
Light Almond	**SFFGLA**	**NSF70LA**	**SFRCRFFLA**	**SFRCWFFLA**	**SFRCYFFLA**	**SFRCBFFLA**	**SFRCGNFFLA**
White	**SFFGW**	**NSF70W**	**SFRCRFFW**	**SFRCWFFW**	**SFRCYFFW**	**SFRCBFFW**	**SFRCGNFFW**

Audio/Video Connectors - Recessed

Description	Gold F-Type Coupler Bulkhead, Female to Female	RCA Gold Pass Through, Female to Female, Red Interior	RCA Gold Pass Through, Female to Female, White Interior	RCA Gold Pass Through, Female to Female, Yellow Interior	RCA Gold Pass Through, Female to Female, Blue Interior	RCA Gold Pass Through, Female to Female, Green Interior	Blank Insert
Color							
Almond	**SFGRFAL**	**SFRCRRAL**	**SFRCWRAL**	**SFRCYRAL**	**SFRCBRAL**	**SFRCGNRAL**	**SFSBAL10***
Black	**SFGRFBK**	**SFRCRRBK**	**SFRCWRBK**	**SFRCYRBK**	**SFRCBRBK**	**SFRCGNRBK**	**SFSBBK10***
Gray	**SFGRFGY**	**SFRCRRGY**	**SFRCWRGY**	**SFRCYRGY**	**SFRCBRGY**	**SFRCGNRGY**	**SFSBGY10***
Ivory	**SFGRFEI**	**SFRCRREI**	**SFRCWREI**	**SFRCYREI**	**SFRCBREI**	**SFRCGNREI**	**SFSBEI10***
Light Almond	**SFGRFLA**	**SFRCRRLA**	**SFRCWRLA**	**SFRCYRLA**	**SFRCBRLA**	**SFRCGNRLA**	**SFSBLA10***
White	**SFGRFW**	**SFRCRRW**	**SFRCWRW**	**SFRCYRW**	**SFRCBRW**	**SFRCGNRW**	**SFSBW10***

*Note: * Sold in a package of 10. Order 1 to receive a bag of 10 blanks.*

tradeSELECT®
Molded-In Voice/Data/Video
Decorator Products

Features

Designed to complement decorator styling, these jacks offer voice and Cat. 5e devices to fit within a decorator wallplate.

- High impact-resistant thermoplastic frame
- Meets FCC part 68
- UL Listed 1863 - Communication Circuit Accessory and CSA Certified

Molded-In Voice/Low-Speed Data

Description	Decorator Frame, One RJ11 Jack, 6-Position, 4-Conductor	Decorator Frame, One RJ11 Jack, 6-Position, 6-Conductor	Decorator Frame, Duplex RJ11 Jacks, 6-Position, 6-Conductor	Decorator Frame, One Cat. 5e 110 Punch-Down, One RJ11 Jack, 6-Position, 4-Conductor
Termination	Screw Terminations	Screw Terminations	Screw Terminations	Screw Terminations
				
Color				
Almond	**NS770AL**	**NS771AL**	**NS772AL**	**NS784AL**
Black	**NS770BK**	**—**	**—**	**NS784BK**
Brown	**NS770**	**NS771**	**—**	**NS784**
Gray	**NS770GY**	**—**	**—**	**NS784GY**
Ivory	**NS770I**	**NS771I**	**NS772I**	**NS784I**
Light Almond	**NS770LA**	**NS771LA**	**NS772LA**	**NS784LA**
White	**NS770W**	**NS771W**	**NS772W**	**NS784W**

Features

Coaxial video and combination jacks complement multimedia needs in a 1-gang decorator opening.

- High impact-resistant thermoplastic frame
- Jacks meet FCC part 68
- UL Listed 1863 - Communication Circuit Accessory and CSA Certified


Molded-In Voice/Low-Speed Data

Description	Decorator Frame, Single F-Type Coupler Bulkhead, Female to Female	Decorator Frame, Duplex F-Type Coupler Bulkhead, Female to Female	Decorator Frame, One RJ11 Jack, 6-Position, 4-Conductor, One F-Type Coupler Bulkhead, Female to Female	Decorator Frame, One Cat. 5e 110 Punch-Down, One F-Type Coupler Bulkhead, Female to Female
Termination	Screw Terminations	Screw Terminations	Screw Terminations	Screw Terminations
				
Color				
Almond	**NS780AL**	**NS782AL**	**NS783AL**	**NS785AL**
Black	**—**	**—**	**—**	**NS785BK**
Brown	**—**	**—**	**—**	**NS785**
Gray	**—**	**—**	**—**	**NS785GY**
Ivory	**NS780I**	**NS782I**	**NS783I**	**NS785I**
Light Almond	**NS780LA**	**NS782LA**	**NS783LA**	**NS785LA**
White	**NS780W**	**NS782W**	**NS783W**	**NS785W**

tradeSELECT®
Toggle Switches and Combination Switches/Devices


Features

Standard toggle switches provide the basic on/off control for home lighting and appliances.
- Tough thermoplastic with ultrasonically welded cover and base
- Elongated strap for easier wall box mounting
- Hi-visibility yellow base for easy installation
- Operating temperature: -20°C to 60°C
- UL Listed E3896, CSA Certified



Features

Mini-toggles provide for multiple switches in a compact single gang. Maximize control while maintaining function and appearance.
- Low profile, less than 1 inch
- Self-grounding feature is standard
- Smooth toggle action
- Operating temperature: -20°C to 60°C
- UL Listed, CSA Certified



tradeSELECT®
Three and Four Way Toggle Switches

Single Pole Toggle Switches

Description	Single Pole	Single Pole, Without Ears*	Single Pole	Single Pole, Illuminated**
Termination	Grounding, Push and Side Wire	Grounding, Push and Side Wire	Self-Grounding, Push and Side Wire	Self-Grounding, Push and Side Wire
Rating	15A 120V AC	15A 120V AC	15A 120V AC	15A 120V AC
				
Color				
Clear	—	—	—	**RS115ILC**
Almond	**RS115AL**	**RS115KAL**	**RS115SAL**	**RS115ILAL**
Black	**RS115BK**	—	—	—
Brown	**RS115**	—	**RS115S**	—
Ivory	**RS115I**	**RS115KI**	**RS115SI**	**RS115ILI**
Light Almond	**RS115LA**	**RS115KLA**	**RS115SLA**	**RS115ILLA**
White	**RS115W**	**RS115KW**	**RS115SW**	**RS115ILW**

*Note: * 100 per case, bulk packed. Mounting screws inserted into strap.*
*** Frame is clear and illuminates, toggle is colored. Does not require a neutral wire.*

Three and Four Way Toggle Switches

Description	Three Way	Three Way, Without Ears*	Three Way	Three Way, Illuminated**	Four Way
Termination	Grounding, Push and Side Wire	Self-Grounding, Push and Side Wire	Self-Grounding, Push and Side Wire	Self-Grounding, Push and Side Wire	Self-Grounding, Side Wire
Rating	15A 120V AC	15A 120V AC	15A 120V AC	15A 120V AC	15A 120V AC
					
Color					
Clear	—	—	—	**RS315ILC**	—
Almond	**RS315AL**	**RS315KAL**	**RS315SAL**	**RS315ILAL**	**RS415AL**
Black	**RS315BK**	—	—	—	**RS415BK**
Brown	**RS315**	—	**RS315S**	—	**RS415**
Ivory	**RS315I**	**RS315KI**	**RS315SI**	**RS315ILI**	**RS415I**
Light Almond	**RS315LA**	**RS315KLA**	**RS315SLA**	**RS315ILLA**	**RS415LA**
White	**RS315W**	**RS315KW**	**RS315SW**	**RS315ILW**	**RS415W**

*Note: * 100 per case, bulk packed. Mounting screws inserted into strap.*
*** Frame is clear and illuminates, toggle is colored. Does not require a neutral wire.*

tradeSELECT®
Combination Switches/Devices
Switches and Receptacles

Combination Toggle Switches/Devices

Description	Two (2) Single Pole Switches	Single Pole Switch, Tamper-Resistant*, 2 Pole, 3 Wire, Receptacle	Single Pole Switch, 2 Pole, 3 Wire, Receptacle	Single Pole Switch, Pilot Light, Clear Lens, Amber Neon Bulb**
Termination	Self-Grounding, Side Wire	Self-Grounding, Side Wire	Self-Grounding, Side Wire	Self-Grounding, Side Wire
Rating	15A 120V AC	15A 120V (switch) 15A 125V (recept.) NEMA 5-15R	15A 120V (switch) 15A 125V (recept.) NEMA 5-15R	15A 120V AC
				
Color				
Almond	**RC101AL**	**RC108ALTR**	**RC108AL**	**RC109AL**
Brown	**RC101**	**RC108TR**	**RC108**	**RC109**
Ivory	**RC101I**	**RC108ITR**	**RC108I**	**RC109I**
Light Almond	**RC101LA**	**RC108LATR**	**RC108LA**	**RC109LA**
White	**RC101W**	**RC108WTR**	**RC108W**	**RC109W**

*Note: * See Section X, page X-10 for TR description.*
*** Neutral required for pilot light, see page V-4 for wiring diagram.*

Combination Toggle Switches/Devices

Description	Single Pole and Three Way Switch	Two (2) Three Way Switches	Three Way Switch, Tamper-Resistant*, 2 Pole, 3 Wire, Receptacle	Three Way Switch, 2 Pole, 3 Wire, Receptacle	Three Way Switch, Pilot Light, Clear Lens, Amber Neon Bulb**
Termination	Self-Grounding, Side Wire	Self-Grounding, Side Wire	Self-Grounding, Side Wire	Self-Grounding, Side Wire	Self-Grounding, Side Wire
Rating	15A 120V AC	15A 120V AC	15A 120V (switch) 15A 125V (recept.) NEMA 5-15R	15A 120V (switch) 15A 125V (recept.) NEMA 5-15R	15A 120V AC
					
Color					
Almond	**RC103AL**	**RC303AL**	**RC308ALTR**	**RC308AL**	**RC309AL**
Brown	**RC103**	**RC303**	**RC308TR**	**RC308**	**RC309**
Ivory	**RC103I**	**RC303I**	**RC308ITR**	**RC308I**	**RC309I**
Light Almond	**RC103LA**	**RC303LA**	—	—	—
White	**RC103W**	**RC303W**	**RC308WTR**	**RC308W**	**RC309W**

*Note: * See Section X, page X-10 for TR description.*
*** Neutral required for pilot light, see page V-4 for wiring diagram.*

tradeSELECT®
Duplex Quick Thread Receptacles


Quick And Easy Does It.

Residential exclusive "Quick Thread" makes installation of wallplates and receptacles quicker and easier.

Provides branch circuit convenience power in duplex and single configurations.
- Smooth indented face appearance
- Terminal screws accepts up to #12 AWG
- Duplex ultrasonically welded
- Push wire designed for #14 AWG solid copper wire only
- Operating temperature: -20°C to 60°C
- UL Listed E2186, CSA Certified

ONE PUSH FOR A SNUG FIT

Just push in the screw and turn.



Duplex Quick Thread Receptacles, 2 Pole, 3 Wire


RR15QW

Description	TR* Tamper-Resistant*, Quick Thread	Standard, Quick Thread	TR* Tamper-Resistant*, Quick Thread	Standard, Quick Thread
Termination	Self-Grounding, Push and Side Wire	Self-Grounding, Push and Side Wire	Eight Push Wire Holes Only #14 AWG	Eight Push Wire Holes Only #14 AWG
Rating	15A 125V NEMA 5-15R	15A 125V NEMA 5-15R	15A 125V NEMA 5-15R	15A 125V NEMA 5-15R
Almond	**RR15QALTR**	**RR15QAL**	**RR15EQALTR**	**RR15EQAL**
Black	**RR15QBKTR**	**RR15QBK**	**RR15EQBKTR**	**RR15EQBK**
Brown	**RR15QTR**	**RR15Q**	**RR15EQTR**	**RR15EQ**
Ivory	**RR15QITR**	**RR15QI**	**RR15EQITR**	**RR15EQI**
Light Almond	**RR15QLATR**	**RR15QLA**	**RR15EQLATR**	**RR15EQLA**
White	**RR15QWTR**	**RR15QW**	**RR15EQWTR**	**RR15EQW**

*Note: * See Section X, page X-10 for TR description.*

tradeSELECT®
Duplex and Single Receptacles

Duplex Receptacles, 2 Pole, 3 Wire

Description	Standard	Weather and Tamper-Resistant*	Tamper-Resistant*	Standard
Termination	Grounding, Push and Side Wire	Self-Grounding, Push and Side Wire	Self-Grounding, Push and Side Wire	Self-Grounding, Push and Side Wire
Rating	15A 125V NEMA 5-15R	15A 125V NEMA 5-15R	15A 125V NEMA 5-15R	15A 125V NEMA 5-15R
Almond	**RR15AL**	**RR15SALWRTR**	**RR15SALTR**	**RR15SAL**
Black	**RR15BK**	**RR15SBKWRTR**	**RR15SBKTR**	**RR15SBK**
Brown	**RR15**	**RR15SWRTR**	**RR15STR**	**RR15S**
Ivory	**RR15I**	**RR15SIWRTR**	**RR15SITR**	**RR15SI**
Light Almond	**RR15LA**	**RR15SLAWRTR**	**RR15SLATR**	**RR15SLA**
White	**RR15W**	**RR15SWWRTR**	**RR15SWTR**	**RR15SW**


RR15W

Description	Tamper-Resistant*, Without Ears	Standard, Without Ears	Tamper-Resistant*, Without Ears**	Standard, Without Ears**
Termination	Eight Push Wire Holes Only #14 AWG	Eight Push Wire Holes Only #14 AWG	Eight Push Wire Holes Only #14 AWG	Eight Push Wire Holes Only #14 AWG
Rating	15A 125V NEMA 5-15R	15A 125V NEMA 5-15R	15A 125V NEMA 5-15R	15A 125V NEMA 5-15R
Almond	**RR15EALTR**	**RR15EAL**	**RR15KALTR**	**RR15KAL**
Black	**RR15EBKTR**	**RR15EBK**	**—**	**—**
Brown	**RR15ETR**	**RR15E**	**RR15KTR**	**RR15K**
Gray	**RR15EGYTR**	**RR15EGY**	**—**	**—**
Ivory	**RR15EITR**	**RR15EI**	**RR15KITR**	**RR15KI**
Light Almond	**RR15ELATR**	**RR15ELA**	**RR15KLATR**	**RR15KLA**
White	**RR15EWTR**	**RR15EW**	**RR15KWTR**	**RR15KW**


RR15KW

Single Receptacles, 2 Pole, 3 Wire

Description	Weather and Tamper-Resistant*	Tamper-Resistant*	Standard	Weather Resistant*	Standard
Termination	Self-Grounding, Side Wire	Self-Grounding, Side Wire	Self-Grounding, Side Wire	Self-Grounding, Side Wire	Self-Grounding, Side Wire
Rating	15A 125V NEMA 5-15R	15A 125V NEMA 5-15R	15A 125V NEMA 5-15R	15A 250V NEMA 6-15R	15A 250V NEMA 6-15R
Almond	**RR151ALWRTR**	**RR151ALTR**	**RR151AL**	**RR155ALWR**	**RR155AL**
Black	**RR151BKWRTR**	**RR151BKTR**	**RR151BK**	**RR155BKWR**	**RR155BK**
Brown	**RR151WRTR**	**RR151TR**	**RR151**	**RR155WR**	**RR155**
Gray	**RR151GYWRTR**	**RR151GYTR**	**RR151GY**	**RR155GYWR**	**RR155GY**
Ivory	**RR151IWRTR**	**RR151ITR**	**RR151I**	**RR155IWR**	**RR155I**
Light Almond	**RR151LAWRTR**	**RR151LATR**	**RR151LA**	**RR155LAWR**	**RR155LA**
White	**RR151WWRTR**	**RR151WTR**	**RR151W**	**RR155WWR**	**RR155W**


RR151W

Description	Weather and Tamper-Resistant*	Tamper-Resistant*	Standard	Weather Resistant*	Standard
Termination	Self-Grounding, Side Wire	Self-Grounding, Side Wire	Self-Grounding, Side Wire	Self-Grounding, Side Wire	Self-Grounding, Side Wire
Rating	20A 125V NEMA 5-20R	20A 125V NEMA 5-20R	20A 125V NEMA 5-20R	20A 250V NEMA 6-20R	20A 250V NEMA 6-20R
Almond	**RR201ALWRTR**	**RR201ALTR**	**RR201AL**	**RR205ALWR**	**RR205AL**
Black	**RR201BKWRTR**	**RR201BKTR**	**RR201BK**	**RR205BKWR**	**RR205BK**
Brown	**RR201WRTR**	**RR201TR**	**RR201**	**RR205WR**	**RR205**
Gray	**RR201GYWRTR**	**RR201GYTR**	**RR201GY**	**RR205GYWR**	**RR205GY**
Ivory	**RR201IWRTR**	**RR201ITR**	**RR201I**	**RR205IWR**	**RR205I**
Light Almond	**RR201LAWRTR**	**RR201LATR**	**RR201LA**	**RR205LAWR**	**RR205LA**
White	**RR201WWRTR**	**RR201WTR**	**RR201W**	**RR205WWR**	**RR205W**


RR201W

*Note: * See Section X, page X-10 for WR and TR descriptions.*
*** 100 per case, bulk packed. Mounting screws inserted into strap.*

tradeSELECT®

GFCI Receptacles with Auto Grounding

15 and 20 Ampere, 125 Volts AC
2 Pole, 3 Wire Grounding

Safety And Economy.

Meets UL Standa
Class A GFCI



10kA Short Circuit Current Rating

Comprehensive diagnostics
- When test button is actuated, both the electronic components and mechanical trip mechanism are functionally tested

Ground fault indicator
- Flashing **RED** indicates device has lost capability to provide protection

No power at face if reverse wired
- Open circuit condition eliminates false assumption of protection at face

Installation ease
- Internal back wiring
- Automatic grounding feature
- Captive mounting screws

GF15ILA



GF15ILA

GFCI Duplex Receptacles, Flush Nylon Face, Matching Nylon Wallplate Included

Description	Weather and Tamper-Resistant	15A 125V NEMA 5-15R UL/CSA Standard	Weather and Tamper-Resistant	20A 125V NEMA 5-20R UL/CSA Standard
Termination	Self-Grounding, Back and Side Wire	Self-Grounding, Back and Side Wire	Self-Grounding, Back and Side Wire	Self-Grounding, Back and Side Wire
Rating	15A 125V AC NEMA 5-15R	15A 125V AC NEMA 5-15R	20A 125V AC NEMA 5-20R	20A 125V AC NEMA 5-20R
Almond	**GFTR15AL**	**GF15ALLA**	**GFTR20AL**	**GF20ALLA**
Black	**GFTR15BK**	**GF15BKLA**	**GFTR20BK**	**GF20BKLA**
Brown	**GFTR15**	**GF15LA**	**GFTR20**	**GF20LA**
Gray	**GFTR15GY**	**GF15GYLA**	**GFTR20GY**	**GF20GYLA**
Ivory	**GFTR15I**	**GF15ILA**	**GFTR20I**	**GF20ILA**
Light Almond	**GFTR15LA**	**GF15LALA**	**GFTR20LA**	**GF20LALA**
Red	**GFTR15R**	**GF15RLA**	**GFTR20R**	**GF20RLA**
White	**GFTR15W**	**GF15WLA**	**GFTR20W**	**GF20WLA**

*Note: * See Section X, page X-10 for WR and TR descriptions.*



GFTR20I

GFCI Duplex Receptacles, Flush Nylon Face, Matching Nylon Wallplate Included

Description	Circuit Guard® Faceless
Termination	Self-Grounding, Back and Side Wire
Rating	20A 125V NEMA 5-20R
Almond	**GFBF20ALLA**
Black	**GFBF20BKLA**
Brown	**GFBF20LA**
Gray	**GFBF20GYLA**
Ivory	**GFBF20ILA**
Light Almond	**GFBF20LALA**
Red	**GFBF20RLA**
White	**GFBF20WLA**



GFBF20ILA

tradeSELECT®

Range and Dryer Power Receptacles and Plugs

30 and 50 Ampere, 125/250 Volts AC
3 Pole, 3 Wire and 3 Pole, 4 Wire

Range and Dryer Power Receptacles

Description	 30A 125/250V NEMA 14-30R UL/CSA	 50A 125/250V NEMA 14-50R UL/CSA	 30A 125/250V NEMA 10-30R UL/CSA	 50A 125/250V NEMA 10-50R UL/CSA
	Flush Mount for 1- or 2-Gang Box	Flush Mount for 1- or 2-Gang Box	Flush Mount for 1- or 2-Gang Box	Flush Mount for 1- or 2-Gang Box
Rating	30A 125/250V 3 Pole, 4 Wire with Ground	50A 125/250V 3 Pole, 4 Wire with Ground	30A 125/250V 3 Pole, 3 Wire without Ground	50A 125/250V 3 Pole, 3 Wire without Ground
Black	**RR430F**	**RR450F**	**RR330F***	**RR350F***
White	**RR430FW**	**RR450FW**	—	—



RR430FW

Description	Surface Mount	Surface Mount	Surface Mount	Surface Mount
Rating	30A 125/250V 3 Pole, 4 Wire with Ground	50A 125/250V 3 Pole, 4 Wire with Ground	30A 125/250V 3 Pole, 3 Wire without Ground	50A 125/250V 3 Pole, 3 Wire without Ground
Black	**RR430**	**RR450**	**RR330***	**RR350***



RR450

Description	Panel Mount	Panel Mount
Rating	30A 125/250V 3 Pole, 4 Wire with Ground	50A 125/250V 3 Pole, 4 Wire with Ground
Black	**RR430PM**	**RR450PM**
White	—	—

*Note: * For replacement use only.*



RR430PM

Range and Dryer Power Angled Plugs

Description	 30A 125/250V NEMA 14-30R UL/CSA  50A 125/250V NEMA 14-50R UL/CSA	 30A 125/250V NEMA 10-30R UL/CSA  50A 125/250V NEMA 10-50R UL/CSA
	With Interchangeable Blades for 30 or 50 Amp	With Interchangeable Blades for 30 or 50 Amp
Rating	30/50A 125/250V 3 Pole, 4 Wire with Ground	30/50A 125/250V 3 Pole, 4 Wire without Ground
Black	**RR435P**	**RR335P**



RR435P

Wallplates, Surface Mount, 2.15" Diameter Single Hole

	1-Gang Standard	1-Gang Mid size	2-Gang Standard	2-Gang Mid size
Ivory	**NP724I**	**NPJ724I**	**NP703I**	**NPJ703I**
White	**NP724W**	**NPJ724W**	**NP703W**	**NPJ703W**
Chrome	**SCH723**	—	—	—
Stainless Steel	**SS723**	—	**SS703**	—

NP724W



NP703W

tradeSELECT®
Special Use Products
Switches and Receptacles


RR151CHW


RJ650BK


RJ600


RDS50


RS100W


RS101W

Special Use Products

Description	Color	Tamper-Resistant* 15A 125V NEMA 5-15R UL/CSA	Standard 15A 125V NEMA 5-15R UL/CSA	Tamper-Resistant* 20A 125V NEMA 5-20R UL/CSA	Standard 20A 125V NEMA 5-20R UL/CSA
Clock Hanger/Recessed Receptacle, 2 Pole, 3 Wire, Grounding, Side Wire Terminations	Brass	**RR151CHBSTR**	**RR151CHBS**	**RR201CHBSTR**	**RR201CHBS**
	Stainless Steel	**RR151CHSSTR**	**RR151CHSS**	**RR201CHSSTR**	**RR201CHSS**
	Ivory (Nylon)	**RR151CHITR**	**RR151CHI**	**RR201CHITR**	**RR201CHI**
	White (Nylon)	**RR151CHWTR**	**RR151CHW**	**RR201CHWTR**	**RR201CHW**
JLOAD® Multimedia Outlet Provides power, Cat. 5e and coaxial in a single gang box. Requires RJ600 Box. Includes decorator frame, one Cat. 5e, one F-connector and one power receptacle 125V with voltage divider.	Almond	**RJ650ALTR**	**RJ650AL**	**RJ620ALTR**	**RJ620AL**
	Black	**RJ650BKTR**	**RJ650BK**	**RJ620BKTR**	**RJ620BK**
	Gray	**RJ650GYTR**	**RJ650GY**	**RJ620GYTR**	**RJ620GY**
	Ivory	**RJ650ITR**	**RJ650I**	**RJ620ITR**	**RJ620I**
	Light Almond	**RJ650LATR**	**RJ650LA**	**RJ620LATR**	**RJ620LA**
	White	**RJ650WTR**	**RJ650W**	**RJ620WTR**	**RJ620W**
JLOAD® Multimedia Outlet Includes decorator frame with two open ports for custom configuration and one power receptacle 125V with voltage divider.	Almond	**RJ65ALTR**	**RJ65AL**	**RJ62ALTR**	**RJ62AL**
	Black	**RJ65BKTR**	**RJ65BK**	**RJ62BKTR**	**RJ62BK**
	Gray	**RJ65GYTR**	**RJ65GY**	**RJ62GYTR**	**RJ62GY**
	Ivory	**RJ65ITR**	**RJ65I**	**RJ62ITR**	**RJ62I**
	Light Almond	**RJ65LATR**	**RJ65LA**	**RJ62LATR**	**RJ62LA**
	White	**RJ65WTR**	**RJ65W**	**RJ62WTR**	**RJ62W**
JLOAD® Multimedia Box 3 inches deep with seven ½-inch knockouts, non-metallic sheathed cable clamps on each side. Screw in mounting to stud.	Steel	**RJ600**	**RJ600**	**RJ600**	**RJ600**


Note: See pages V-22 to V-27 for floor and under cabinet box options.
** See Section X, page X-10 for TR description.*

Door Switch with Cover Plate and Box

Description	"ON" when Door is Open	"OFF" when Door is Open
Rating	3A 125V AC	3A 125V AC
Zinc Plated Steel	**RDS50****	**RDS30****

*Note: ** Not UL Listed.*

Product Dimensions



In-Line Cord Switches

Description	Mini For Use with Flat Lamp Cord	Heavy Duty
Rating	6A 125V AC	6A 125V AC ⅛ HP
Wire	#18 AWG SPT 1 and SPT 2	#18 to #16 AWG SPT 1 and SPT 2
Ivory	—	**RS101I**
White	**RS100W**	**RS101W**

tradeSELECT®

Dimmers and Fan Speed Controls

Lighting Controls

Rocker Decorator Dimmers, Preset with Night Light

Description	Side Slide Adjustment, Incandescent	Side Slide Adjustment, Incandescent	Side Slide Adjustment, Incandescent	Side Slide Adjustment, Incandescent
Termination	Single Pole	Three Way	Single Pole	Three Way
Rating	1000W 120V AC	1000W 120V AC	600W 120V AC	600W 120V AC
Almond	**RDV10PAL**	**RDV103PAL**	**RDV600PAL**	**RDV603PAL**
Ivory	**RDV10PI**	**RDV103PI**	**RDV600PI**	**RDV603PI**
Light Almond	**RDV10PLA**	**RDV103PLA**	**RDV600PLA**	**RDV603PLA**
White	**RDV10PW**	**RDV103PW**	**RDV600PW**	**RDV603PW**



RDV600PW

Description	Magnetic Low Voltage	Magnetic Low Voltage	Electronic Low Voltage	Electronic Low Voltage Requires Neutral
Termination	Single Pole	Three Way	Single Pole	Three Way
Rating	600VA (450W) 120V AC	600VA (450W) 120V AC	300W 120V AC	300W 120V AC
Almond	**RDVLV600PAL**	**RDVLV603PAL**	**RDVELV300PAL**	**RDVELV303PAL**
Ivory	**RDVLV600PI**	**RDVLV603PI**	**RDVELV300PI**	**RDVELV303PI**
Light Almond	**RDVLV600PLA**	**RDVLV603PLA**	**RDVELV300PLA**	**RDVELV303PLA**
White	**RDVLV600PW**	**RDVLV603PW**	**RDVELV300PW**	**RDVELV303PW**



RS600PW

Slide Dimmers, Preset with On/Off Switch

Description	Incandescent	Incandescent	Incandescent	Incandescent
Termination	Single Pole	Three Way	Single Pole	Three Way
Rating	1000W 120V AC	1000W 120V AC	600W 120V AC	600W 120V AC
Almond	**RS10PAL**	**RS103PAL**	**RS600PAL**	**RS603PAL**
Ivory	**RS10PI**	**RS103PI**	**RS600PI**	**RS603PI**
Light Almond	**RS10PLA**	**RS103PLA**	**RS600PLA**	**RS603PLA**
White	**RS10PW**	**RS103PW**	**RS600PW**	**RS603PW**



RS613W

Description	Magnetic Low Voltage	Magnetic Low Voltage	Electronic Low Voltage	Electronic Low Voltage Requires Neutral
Termination	Single Pole	Three Way	Single Pole	Three Way
Rating	600VA (450W) 120V AC	600VA (450W) 120V AC	300W 120V AC	300W 120V AC
Almond	**RSLV600PAL**	**RSLV603PAL**	**RSELV300PAL**	**RSELV303PAL**
Ivory	**RSLV600PI**	**RSLV603PI**	**RSELV300PI**	**RSELV303PI**
Light Almond	**RSLV600PLA**	**RSLV603PLA**	**RSELV300PLA**	**RSELV303PLA**
White	**RSLV600PW**	**RSLV603PW**	**RSELV300PW**	**RSELV303PW**



RS600W

Slide Dimmers, Specialty

Description	Incandescent Slide to Off	Incandescent Omni Slide Button
Termination	Single Pole	Single Pole/Three Way
Rating	600W 120V AC	600W 120V AC
Ivory	**RS600I**	**RS613PI**
Light Almond	**RS600LA**	**RS613PLA**
White	**RS600W**	**RS613PW**



RS2LFSQW

Fan Speed Controls, 3 Speed and Replacement Knobs

Description	Rocker Slide Adjustment	Slide Control Slide to Off	Combination Slide Dimmer, Incandescent	Replacement Knob
Termination	Single Pole/Three Way	Single Pole	Single Pole	—
Rating	1.5A 120V AC	1.5A 120V AC	300W 1.5A 120V AC	—
Almond	**RDVFSQFAL**	**RSFSQFAL**	**RS2LFSQAL**	**RSKAL**
Ivory	**RDVFSQFI**	**RSFSQFI**	**RS2LFSQI**	**RSKI**
Light Almond	**RDVFSQFLA**	**RSFSQFLA**	**RS2LFSQLA**	**RSKLA**
White	**RDVFSQFW**	**RSFSQFW**	**RS2LFSQW**	**RSKW**



RSKW

RSKI

tradeSELECT®

Toggle Dimmers and Fan Speed Controls

Lighting Controls



RAY600PW

Toggle Incandescent Preset Dimmers

Description	Side Slide Adjustment with Wire Leads	Side Slide Adjustment with Wire Leads	Side Slide Adjustment with Terminal Screws	Side Slide Adjustment with Terminal Screws
Termination	Single Pole	Three Way	Single Pole	Three Way
Rating	1000W 120V AC	1000W 120V AC	600W 120V AC	600W 120V AC
Almond	**RAY10PAL**	**RAY103PAL**	**RAY600PAL**	**RAY603PAL**
Ivory	**RAY10PI**	**RAY103PI**	**RAY600PI**	**RAY603PI**
Light Almond	**RAY10PLA**	**RAY103PLA**	**RAY600PLA**	**RAY603PLA**
White	**RAY10PW**	**RAY103PW**	**RAY600PW**	**RAY603PW**



RD600RW



RRKDK

Rotary Incandescent Dimmers and Replacement Knobs

Description	On/Off Dimmer	Push On/Off Dimmer Ivory and White Knobs Provided	Push On/Off Dimmer Ivory and White Knobs Provided	Replacement Knobs 2 Piece Kit
Termination	Single Pole	Single Pole	Three Way	—
Rating	600W 120V AC	600W 120V AC	600W 120V AC	—
Ivory	**RD600RI**	**—**	**—**	**—**
White	**RD600RW**	**—**	**—**	**—**
Ivory/White	**—**	**RD600PDK**	**RD603PDK**	**RRKDK**



RAY2LFSQW



RFSQ2FDK



R28032401

R28032406

Fan Speed Controls

Description	Toggle 3-Speed	Combination Toggle 3-Speed/Dimmer	Rotary On/Off 3-Speed includes Ivory and White knobs	Rotary Variable Speed	Rotary Fan Control Replacement Knobs
Termination	Single Pole or Three Way	Single Pole	Single Pole	Single Pole	—
Rating	1.5A 120V AC	300W 1.5A 120V AC	1.5A 120V AC	5A 120V AC	—
Almond	**RAYFSQFAL**	**RAY2LFSQAL**	**—**	**—**	**—**
Ivory	**RAYFSQFI**	**RAY2LFSQI**	**—**	**RFS5I**	**R28032406**
Light Almond	**RAYFSQFLA**	**RAY2LFSQLA**	**—**	**RFS5LA**	**—**
White	**RAYFSQFW**	**RAY2LFSQW**	**—**	**—**	**R28032401**
Ivory/White	**—**	**—**	**RFSQ2FDK**	**RFS5W**	**—**

Occupancy Sensors

Auto-on occupancy sensors turn on the load when motion is detected in an area. The device turns lights off when motion ceases and the time delay has expired.

Description	Occupancy Sensor Basic On/Off Control 150° View Standard	Occupancy Sensor Basic On/Off Control 150° View With Nightlight	Occupancy Sensor Dimming Control 150° View Standard	Occupancy Sensor Dimming Control 150° View With Nightlight
Termination	Single Pole Switch	Single Pole Switch	Single Pole Switch	Single Pole Switch
Rating	500W 120V AC Incandescent Only	500W 120V AC Incandescent Only	500W 120V AC Incandescent Only	500W 120V AC Incandescent Only
Almond	**RMS101AL**	**RMS101ILAL**	**RMS121AL**	**RMS121ILAL**
Ivory	**RMS101I**	**RMS101ILI**	**RMS121I**	**RMS121ILI**
Light Almond	**RMS101LA**	**RMS101ILLA**	**RMS121LA**	**RMS121ILLA**
White	**RMS101W**	**RMS101ILW**	**RMS121W**	**RMS121ILW**



RMS101W
RMS100W

Vacancy Sensors

Vacancy sensor switches are specifically designed for California Title 24 compliance. When a person enters an area, the manual switch must be pressed to turn on the light. The device turns lights off when motion ceases and the time delay has expired.

Description	Vacancy Sensor Basic On/Off Control 150° View Standard	Vacancy Sensor Basic On/Off Control 150° View With Nightlight	Vacancy Sensor Dimming Control 150° View Standard	Vacancy Sensor Dimming Control 150° View With Nightlight
Termination	Single Pole Switch	Single Pole Switch	Single Pole Switch	Single Pole Switch
Rating	500W 120V AC Incandescent Only	500W 120V AC Incandescent Only	500W 120V AC Incandescent Only	500W 120V AC Incandescent Only
Almond	**RMS100AL**	**RMS100ILAL**	**RMS120AL**	**RMS120ILAL**
Ivory	**RMS100I**	**RMS100ILI**	**RMS120I**	**RMS120ILI**
Light Almond	**RMS100LA**	**RMS100ILLA**	**RMS120LA**	**RMS120ILLA**
White	**RMS100W**	**RMS100ILW**	**RMS120W**	**RMS120ILW**



RMS121ILW
RMS120ILW


Heavy Duty Occupancy and Vacancy Sensors

Description	Occupancy Sensor 180° View	Vacancy Sensor 180° View
Termination	Single Pole	Single Pole
Rating	800W Inc., 1000W Fluor., 120V AC 1800W Fluor., 277V AC ⅛ HP 120V AC	800W Inc., 1000W Fluor., 120V AC 1800W Fluor., 277V AC ⅛ HP 120V AC
Almond	**RMS141AL**	**RMS140AL**
Ivory	**RMS141I**	**RMS140I**
White	**RMS141W**	**RMS140W**




RMS141W
RMS140W

Coverage for Occupancy and Vacancy Sensors



Coverage for Heavy Duty Occupancy and Vacancy Sensors




tradeSELECT®

Floor Boxes For Wood Floors

Power Delivery

Hubbell Wood Floor Boxes allow for the placement of electrical power or a combination of power and voice/data devices. Boxes easily mount into the floor and are height adjustable (up to ¾ inch) for optimal alignment and fit.



Note: Template cutout provided with instructions for proper installation.

The Right Choice For That Perfect Finishing Touch!



Solid Brass | Brass Plated | Chrome Plated | Copper Plated | Nickel Plated | Stainless Finish | Almond | Black | Chestnut Brown

Note: Not all configurations are available in all colors. See below for details.



RF515BR

Floor Boxes For Structural Wood Floors

Description	Material	Finish	Cat. Number	Material	Finish	Cat. Number
Decorator duplex receptacle floor box kit; includes steel box, flange and hinged door cover assembly with 15A 125V tamper-resistant duplex receptacle; designed for installation in wood floors; mounts to sub-floor or joists.	Solid Brass Aluminum Aluminum Aluminum Aluminum	Clear Lacquer Stainless Paint Almond Paint Black Paint Chestnut Brown Paint	**RF515BR** **RF515SS** **RF515AL** **RF515BK** **RF515BN**	Aluminum Aluminum Aluminum Aluminum	Brass Plated Chrome Plated Copper Plated Nickel Plated	**RF515BP** **RF515CH** **RF515CU** **RF515NI**
Flush fit (same as above).	Solid Brass	Clear Lacquer	**RF509BR**			



RF506BR

Description	Material	Finish	Cat. Number	Material	Finish	Cat. Number
Flange and hinged door cover assembly; includes tamper-resistant duplex receptacle; neoprene gaskets; for use with steel box RF500.	Solid Brass Aluminum Aluminum Aluminum Aluminum	Clear Lacquer Stainless Paint Almond Paint Black Paint Chestnut Brown Paint	**RF506BR** **RF506SS** **RF506AL** **RF506BK** **RF506BN**	Aluminum Aluminum Aluminum Aluminum	Brass Plated Chrome Plated Copper Plated Nickel Plated	**RF506BP** **RF506CH** **RF506CU** **RF506NI**



RF500

Description	Material	Finish	Cat. Number
Adjustable floor box; 3 inch deep; three (3) ½ inch knockouts: one on bottom; one on each side; non-metallic sheathed cable clamps on each side.	Steel	—	**RF500**



RF507BR

Description	Material	Finish	Cat. Number	Material	Finish	Cat. Number
Hinged Door Cover Only Replacement door for RF515, RF509 and RF506 series.	Solid Brass Aluminum Aluminum Aluminum Aluminum	Solid Brass Stainless Finish Almond Black Chestnut Brown Paint	**RF507BR** **RF507SS** **RF507AL** **RF507BK** **RF507BN**	Aluminum Aluminum Aluminum Aluminum	Brass Plated Chrome Plated Copper Plated Nickel Plated	**RF507BP** **RF507CH** **RF507CU** **RF507NI**

tradeSELECT®

Floor Boxes For Wood Floors


Power Delivery

Duplex floor receptacles provide ample connections to service lighting, entertainment equipment and computers for family rooms and offices. Single receptacle configurations available for minimum requirements.

- Metal covers feature electrostatic powder coating that resists wear and provides a distinctive finish
- Recessed GFCI/Decorator opening
- Cut out template provided to assure proper sub-flooring preparation

Drop-in Floor Box

Drop-In Floor Boxes are perfect for quick and easy installation of power or low voltage. Simply cut a hole between the floor and joists and drop through. The flange lip holds it in place.



Floor Boxes For Wood Floors

Description	Material	Tamper-Resistant	15A 125V NEMA 5-15R UL/CSA Standard	Tamper-Resistant	20A 125V NEMA 5-20R UL/CSA Standard
Drop In Floor Box Mounts in 2½ inch hole opening. Includes solid brass cover, single tamper-resistant receptacle, optional device mounts for two (2) voice/data video ports. Suitable for feed through circuitry. Impact resistant box.	Solid Brass	**RF151R**	—	**RF201R**	—
Duplex Receptacle Floor Box Rated Includes steel box, duplex TR receptacle and cover.		**RF6500BR**	—	—	—
Single Receptacle Floor Box Rated Includes steel box, single receptacle and cover.	Brass	**RF151TR**	**RF151**	—	—
Single Receptacle Display Rated Receptacle and cover only, excludes box.	Brass	—	**RF151D**	—	—



RF151R




RF151




RF151D


Product Dimensions

Wood Floor Boxes





Drop-In Floor Box



Dimensions in Inches (mm)

tradeSELECT®
Floor Boxes For Concrete Floors
Power Delivery

Residential Round Non-Metallic Floor Box offers an economical solution for electrical power or a combination of power and voice/data applications. Designed specifically for slab-on-grade installation. Quick and easy installation is assured using a push in place leveling system. UL Listed E92074.



tradeSELECT®

Floor Boxes For Concrete Floors

Power Delivery

After the box has been secured in concrete, cut for height, apply PVC glue and push the cover assembly into the box. No fasteners or adjustment screws required.

- 4 inch minimum concrete pour
- Recessed GFCI/Decorator opening
- Self height and leveling ring, no adjustments
- UL Listed E92074 Floor Box

Floor Boxes For Concrete Floors

Description	Rating	Material/Color	Catalog Number
Flange and Hinged Door Cover Assembly Includes duplex receptacle, gasket, floor leveling PVC ring, high impact and chemically resistant nylon. Factory pre-assembled for easy drop-in installation.	15A 125V NEMA 5-15R	Solid Brass Almond Black Gray Chestnut Brown	**RF406BR** **RF406AL** **RF406BK** **RF406GY** **RF406BN**
Flush cover		Solid Brass	**RF409BR**
PVC Floor Box with Concrete Protective Cover Accepts ¾ in. and 1.0 in. schedule 40 and schedule 80 PVC conduit. Includes round box (4⅞ in. diameter x 6.0 in. deep), four reducers, closure plugs, and concrete cover with locator flag.		Gray	**RF400**
Hinged Nylon Replacement Door Cover Includes neoprene gasket to seal plug openings. Replacement cover for RF406 series.		Solid Brass Almond Black	**RF407BR** **RF407AL** **RF407BK**
Low Voltage Divider For use in PVC box RF400, when JLOAD® Multimedia Outlet is used.		Gray	**RF408**



RF406BK



RF400



RF407BK



RF408

JLOAD® Multimedia Outlet

Description	Material	Tamper-Resistant	15A 125V NEMA 5-15R UL/CSA Standard	Tamper-Resistant	20A 125V NEMA 5-20R UL/CSA Standard
JLOAD® Multimedia Outlet Specifically designed to provide power, Cat. 5e and coaxial in a single gang box. Requires Low Voltage Divider RF408 when used in PVC Box RF400. Perfect for HDTV and computer use where a combination of power and data are needed. Includes decorator frame, one Cat. 5e, one F-connector and one power receptacle 125V with voltage divider.	Almond Black Gray Ivory Light Almond White	**RJ650ALTR** **RJ650BKTR** **RJ650GYTR** **RJ650ITR** **RJ650LATR** **RJ650WTR**	**RJ650AL** **RJ650BK** **RJ650GY** **RJ650I** **RJ650LA** **RJ650W**	**RJ620ALTR** **RJ620BKTR** **RJ620GYTR** **RJ620ITR** **RJ620LATR** **RJ620WTR**	**RJ620AL** **RJ620BK** **RJ620GY** **RJ620I** **RJ620LA** **RJ620W**
JLOAD® Multimedia Outlet Includes decorator frame with two open ports for custom configuration and one power receptacle 125V with voltage divider.	Almond Black Gray Ivory Light Almond White	**RJ65ALTR** **RJ65BKTR** **RJ65GYTR** **RJ65ITR** **RJ65LATR** **RJ65WTR**	**RJ65AL** **RJ65BK** **RJ65GY** **RJ65I** **RJ65LA** **RJ65W**	**RJ62ALTR** **RJ62BKTR** **RJ62GYTR** **RJ62ITR** **RJ62LATR** **RJ62WTR**	**RJ62AL** **RJ62BK** **RJ62GY** **RJ62I** **RJ62LA** **RJ62W**

*Note: * See Section X, page X-10 for TR description.*



RJ650BK



RJ65BK

tradeSELECT®
Under Cabinet/Counter Power Distribution
Power Delivery

These boxes comply with the NEC® for kitchen receptacles, with placement not more than 20 inches above the counter surface. They can also be placed under counter islands, not lower than 15 inches from the surface.

- Available with nylon or metal cover
- Custom configurable, accepts any decorator style device
- Mounting hardware included
- UL Listed E31999 and CSA Certified under cabinet boxes




Under Cabinet/Counter Power Distribution

Description	Slim Box Catalog Number	GFCI Fit Box Catalog Number
Stainless Steel	**RU100SS**	**RU200SS**
White Metal	**RU100W**	**RU200W**
White Nylon	**RU170W***	**RU270W***




RU100W






RU200SS




*Note: * Steel box with nylon cover.*

Vertical Mount



Horizontal Mount




NEC® is a registered trademark of the National Fire Protection Association (NFPA).

tradeSELECT®
JLOAD® Multimedia Outlet
Power Delivery

Make The Most Of A Perfect Location.

Install receptacles and voice/data devices exactly where they are needed, in the smallest space possible.



Note: Requires unique box shown below.

JLOAD® Multimedia Outlet

Description	Color	Tamper-Resistant*	15A 125V NEMA 5-15R UL/CSA Standard	Tamper-Resistant*	20A 125V NEMA 5-20R UL/CSA Standard
JLOAD® Multimedia Outlet, specifically designed to provide power, Cat. 5e and coaxial in a single gang box. Requires JLOAD® Multimedia Box RJ600. Perfect for HDTV and computer use where a combination of power and data are needed. Includes decorator frame, one Cat. 5e, one F-connector and one power receptacle 125V with voltage divider.	Almond	**RJ650ALTR**	**RJ650AL**	**RJ620ALTR**	**RJ620AL**
	Black	**RJ650BKTR**	**RJ650BK**	**RJ620BKTR**	**RJ620BK**
	Gray	**RJ650GYTR**	**RJ650GY**	**RJ620GYTR**	**RJ620GY**
	Ivory	**RJ650ITR**	**RJ650I**	**RJ620ITR**	**RJ620I**
	Light Almond	**RJ650LATR**	**RJ650LA**	**RJ620LATR**	**RJ620LA**
	White	**RJ650WTR**	**RJ650W**	**RJ620WTR**	**RJ620W**
JLOAD® Multimedia Outlet, includes decorator frame with two open ports for custom configuration and one power receptacle 125V with voltage divider.	Almond	**RJ65ALTR**	**RJ65AL**	**RJ62ALTR**	**RJ62AL**
	Black	**RJ65BKTR**	**RJ65BK**	**RJ62BKTR**	**RJ62BK**
	Gray	**RJ65GYTR**	**RJ65GY**	**RJ62GYTR**	**RJ62GY**
	Ivory	**RJ65ITR**	**RJ65I**	**RJ62ITR**	**RJ62I**
	Light Almond	**RJ65LATR**	**RJ65LA**	**RJ62LATR**	**RJ62LA**
	White	**RJ65WTR**	**RJ65W**	**RJ62WTR**	**RJ62W**
JLOAD® Multimedia Box, 3 inches deep with seven ½-inch knockouts, non-metallic sheathed cable clamps on each side. Screw in mounting to stud.	Steel	**RJ600**	**RJ600**	**RJ600**	**RJ600**


*Note: * See Section X, page X-10 for TR description.*


RJ620W


RJ62W


RJ600

JLOAD® Dimensions



Dimensions in Inches (mm)

tradeSELECT®

Decorator Switches

Dimensions and Specifications

- Smooth, quiet rocker action
- Self-grounding feature standard
- Ultrasonically welded cover and base provides maximum strength
- Push, back and side wiring
- Available colors: Almond, Black, Brown, Gray, Ivory, Light Almond and White



RSD115W

Specifications

Switches

Typical Specification — Catalog Number RSD115*
Description — Decorator series rocker switch
Type — Single Pole
Rating — 15A, 120-277V AC

*Note: * Designates color: AL = Almond, BK = Black, Blank = Brown, GY = Gray, I = Ivory, LA = Light Almond, W = White.*

Certification


- Listed to UL Standard 20
- CSA Certified

Components	Materials
Base and body	PVC
Rocker	Polycarbonate
Terminals	Brass
Mounting strap	Galvanized steel
Contacts	Silver alloy
Movable contact arm	Copper alloy
Terminal screws	Steel

Performance

Electrical	
Dielectric voltage	Withstands 1,500V AC minimum for 1 minute
Max. working voltage	120V
Overload	1.5 times rating
Endurance	30,000 cycles minimum
Mechanical	
Terminal accommodation	Back and side wire: #14 AWG min. - #12 AWG max. solid and stranded copper wire only; push wire: #14 AWG solid copper wire only
Environmental	
Flammability	UL V0
Operating temperatures	Maximum continuous 60°C; minimum -20°C (without impact)


Product Dimensions





Single-Pole Decorator Switch


Index

netSELECT®	Page
Structured Wiring	
In-Wall AV Delivery	V-30
HDMI Products	V-31
Advantages and Wiring Layout	V-32
Network Enclosures	V-33
Network Modules	V-34
Audio/Video Modules	V-35
Universal Consolidation Blocks, Patch Panels and Patch Cords	V-36
Accessories	V-37
Data Communications and Audio/Video	
Modular Snap Fit Jacks	V-38
Decorator Frames	V-39
Molded-In Voice/Data/Video	V-40
Molded-In Plates	V-41
Telephone Wall Jacks	V-42










netSELECT®
In-Wall AV Delivery
Structured Wiring

Hubbell's netSELECT® Flat Panel Television (FPTV) connection enclosure delivers high-density connectivity and power in the wall. This allows flat panel displays and interactive "smart" boards to sit flush against walls with no dangling cords. It quickly installs to studs or sheetrock without additional components or hardware.

- 18 Gauge white powder coated rugged steel base
- 2-Gang enclosure with 2 additional 3-Unit Hubbell iSTATION mounting locations
- Stud or sheetrock mounting integrated
- Supplied ABS trim ring quickly cleans up sheetrock rough-in
- Optional screw on cover reduces tampering
- cULus 1863 Listed



NSAV62M



NSAV6C



NSOKPS



NS801W



NSJ6W

FPTV Connection Enclosure

Description	Color	Catalog Number
2-Gang In-Wall Enclosure	White	**NSAV62M**
Steel Cover for NSAV6 series	White	**NSAV6C**

Power Kits

Description	Color	Catalog Number
Standard Power Kit	White	**NSOKP**
Surge Protected Power Kit	Blue	**NSOKPS**
1-Gang Decorator Plate	White	**NP26W**
1-Gang Hubbell iSTATION Plate	White	**IMF1W**
1-Gang 4-Port Keystone Plate	White	**NSP14W**

AV Connectors and Plates

Description	Color	Catalog Number
1-Port HDMI Frame	White	**NS801W**
2-Port HDMI Frame	White	**NS802W**
HDMI Snap Fit	Black	**SFHCBK**
F-Connector Snap Fit	White	**NSF70W**
USB A-to-B Snap Fit	White	**SFUSBABW**
Cat 6 Snap Fit Jack	White	**NSJ6W**

Note: See section P for other connector options.

netSELECT®
HDMI Products
Structured Wiring

The AV Ceiling Enclosure is designed to work with active AV devices to integrate AV distribution, data connections and power in one location, providing a direct connection to a projector or a display device. The enclosure comes loaded with two Hubbell 20A duplex receptacles and a 2-gang RACO® box for installation convenience on the job site. An additional AV/data kit can be added or customized to address all connector, mounting and patching needs, reducing multiple pieces on site.

- Manage multiple applications inside one enclosure
- Flush mounted, white enclosure for consistent look when mounted in the ceiling
- Loaded with two Hubbell 20A duplex receptacles and a 2-gang back box
- All steel rugged construction provides the ultimate strength for installation



AVCE1H


AV Ceiling Enclosure

Description	Color	Catalog Number
AV Ceiling Enclosure	White	**AVCE1H**

Note: Enclosure Includes: Enclosure 24" x 12" x 8", (2) 20 amp duplex receptacles and 2-gang back box.

netSELECT® HDMI Decorator Frames deliver uncompromising digital audio and video wherever you need it. Unleash the full potential of your high definition display and audio installations.

- Third party tested for 1080p resolutions
- UL Listed - Communications Circuit Accessory and CSA Certified



HDMI Products

Description	Color	1-Gang, 1-Port	1-Gang, 2-Port
HDMI, Decorator Frame, Female to Female	Almond	**NS801AL**	**NS802AL**
	Black	**NS801BK**	**NS802BK**
	Gray	**NS801GY**	**NS802GY**
	Ivory	**NS801I**	**NS802I**
	Light Almond	**NS801LA**	**NS802LA**
	White	**NS801W**	**NS802W**



NS801W



NS802W

HDMI Cords

HDMI Device Patch Cords

HDMI (24 AWG)	Catalog Number
3 ft.	**HDPC03BK**
6 ft.	**HDPC06BK**

Horizontal Cords (Connector to Connector)

HDMI (24 AWG)	Catalog Number
XX ft.	**HDHXXBK**

Link Cords (Connector to Device)

HDMI (24 AWG)	Catalog Number
XX ft.	**HDLXXBK**

Coupler Cords (Coupler to Device)

HDMI (24 AWG)	Catalog Number
XX ft.	**HDCXXBK**

Note: XX = Length in feet. '10' = 10 ft., '15' = 15 ft., '20' = 20 ft., '25' = 25 ft., '30' = 30 ft., Black and Non-Plenum only.



HDPC06BK

netSELECT®


Advantages and Wiring Layout

Structured Wiring


- Share single analog, cable or DSL internet connection
- Local file access
- Shared peripherals
- Multiple telephone distribution
- Call handling (PBX)
- Video distribution
- Play games that allow multi-users
- Control home automation systems

Connect Your Home to Internet, Voice And Video Services

netSELECT® is an innovative network solution that's perfect for any home or small office. Specifically positioned as the voice/data segment for the Residential brand, the netSELECT® System satisfies the need for a dependable, flexible system that can accommodate all of today's fast-changing voice, data and video requirements. This cost-effective solution incorporates all the quality you'd expect from Hubbell. Built-in flexibility makes it easy to upgrade and keep pace with evolving technologies.



Today's Communications Entail A Lot More Than Just Talking.
netSELECT® Keeps You Connected—Internet, Voice, Data and Entertainment



netSELECT®

Network Enclosures

Structured Wiring

- Flush or surface mount enclosure (hardware provided)
- Hinged cover can be mounted to swing from either side
- Integral trim ring hides rough-in hole in except NSOBOX48 sheet rock providing a finished appearance
- Horizontal and vertical module mounting holes for maximum flexibility
- Unique 89D bracket mounting holes allow easy mounting of 66 blocks and peripherals
- Provisions to mount optional duplex power and lock kit available
- Integral cable management slots and tie-wraps provided to help dress cable runs
- Additional nylon push pins provided to assist module mounting
- Material: 20-18 gauge steel
- Finish: white, powder coat
- UL and cULus Listed 1863

Network Enclosures

Description		Number of Module Placement	Catalog Number
Pre-configured Network System Basic home network kit includes: One box with hinged cover NSOBOX14, One primary 8-port telephone module NSOPTM8, One four way coaxial splitter module NSOVDM4		—	**NSOBNK14**
10 Inch Network Enclosure for MDU and Modular Applications Dimensions: 14.38 in. W x 10.0 in. H x 3.96 in. D Knock-outs: Top: four 1½ in. N.P.T. or completely open combo; Bottom: four 1½ in. N.P.T. or completely open combo; Back: none	with Hinged Cover with Panel Cover 10"H Box only Hinged Door Panel Cover	3	**NSOBX10** **NSOBX10BC** **NSOBX10B** **NSOBX10D** **NSOBX10C**
14 Inch Network Enclosure Dimensions: 14.38 in. W x 14 in. H x 3.96 in. D Knock-outs: Top: two 1 in. Dia. and three 1½ in. N.P.T. combo; Bottom: one 1 in. Dia. and one 1½ in. N.P.T. combo; Back: two ¾ in. N.P.T.	with Hinged Cover with Panel Cover 14"H Box only Hinged Door Vertical Door Panel Cover 2"D Extension Bracket with ventilation and WiFi KOs	5	**NSOBOX14** **NSOBOX14BC** **NSOBOX14B** **NSOBOX14D** **NSOBOX14DL** **NSOBOX14C** **NSOBOX14X2**
28 Inch Network Enclosure Dimensions: 14.38 in. W x 28 in. H x 3.96 in. D Knock-outs: Top: five 1½ in. N.P.T.; Bottom: two power kit knockouts; Back: four ¾ in. N.P.T.	with Hinged Cover with Panel Cover 28"H Box only Hinged Door Vertical Door* Panel Cover 2"D Extension Bracket with ventilation and WiFi KOs	11	**NSOBOX28** **NSOBOX28BC** **NSOBOX28B** **NSOBOX28D** **NSOBOX28DL** **NSOBOX28C** **NSOBOX28X2**
48 Inch Network Enclosure Dimensions: 14.38 in. W x 48 in. H x 3.96 in. D Knock-outs: Top: five 1½ in. N.P.T.; Bottom: two power kit knockouts; Back: none	with Hinged Cover	21	**NSOBOX48**



NSOBX10



NSOBOX14



NSOBOX28

Note: For custom installs, REKHS is also available. See section P for ordering information.
** Door covers rough-in, no trim ring provided.*

netSELECT®

Network Modules

Structured Wiring

netSELECT® Modular Components enable the designer to select performance requirements specifically for the application. Modules snap horizontally or vertically into the enclosures for maximum flexibility and optimum space usage.

- Dimensions: 6.47 inch W x 2.95 inch H, except NSOMTM24 6.47 inch W x 6.00 inch H
- Meets FCC Part 68 standard
- Finish: black, powder coat
- Material: 18 gauge steel or high impact plastic
- UL and cULus Listed 1863
- All data and phone modules 568A wired

Network Modules

Description	Units	Catalog Number
 **NSOTVM6** Combo Module Complete Home Network Combo Module 6-Port Telephone Panel and 6-Port Coaxial Splitter with Optional 6-Port Cat. 5e Panel Provides voice, video, and data distribution in a space efficient package. Perfect for use with NSOBOX10 and NS790xx plates to quickly establish a comprehensive home network.	3	
6-Port Telephone and Video		**NSOTVM6**
6-Port Telephone, Video and Category 5e		**NSOTVDM6**
6-Port Category 5e Data Upgrade Kit		**NSODK6**
 **NSOPTM8** Primary Telephone Module, 8-Port Supports 8 phone outlets with up to 4 incoming lines for voice, fax or modem applications in a protected PCB module. Pre-mounted push pins snap the module quickly into place. RJ31X interface jack included for security system connection. RJ45 jack interfaces with optional NSOETM8 Telephone Expansion module for additional extensions.	1	**NSOPTM8**
 **NSOETM8** Expansion Telephone Module, 8-Port Adds an additional 8 phone outlets with up to 4 incoming lines when used with the primary telephone module. Pre-mounted push pins snap the module quickly into place. Includes RJ45 jack cord to connect with NSOPTM8 Primary Telephone module.	1	**NSOETM8**
 **NSODM8** Category 5e Data Module, 8-Port Supports Gigabit Ethernet for up to 8 Category 5e data lines with front 110 Punch-Down terminations in a protected PCB module. Pre-mounted push pins snap the module quickly into place.	1	**NSODM8**
Category 6 Data Module, 8-Port Supports enhanced transmission speeds beyond gigabit ethernet. Future proof for tomorrows applications.		**NSODM8C6**
 **NSOMTM24** Multiport Patchable Telecom Module Terminates lines via modular plug to accommodate flexibility, by changing plug locations. Reconfigure where phone lines go at the panel level. Allows data lines to be converted to voice, with the move of a patch cord. Includes nine RJ45 jumper cords.	2	**NSOMTM24**
 **NSO6P1DM** Combination Module 6-Port Telephone and 1-Port Data Provides basic telephone and data delivery in a small package. Allows data lines to be converted to voice, with the move of a patch cord.	1	**NSO6P1DM**

netSELECT®
Audio/Video Modules
Structured Wiring

netSELECT® Video Modules support bidirectional signal by splitting to 4, 6, or 8 separate work areas. Pre-mounted push pins snap the module quickly into place.

- Dimensions for VAMP, AM8 and BM: 6.47 in. W x 2.95 in. H
- Dimensions for video splitters: 6.47 in. W x 2.09 in. H x 3.20 in. D
- Finish: black, powder coat
- UL and cULus Listed 1863

Audio/Video Modules

Description	Units	Catalog Number
4-Way Coaxial Splitter Modules, One Incoming Line, Four Outgoing 1 Ghz, Basic Unit 2.3 Ghz, Enhanced Capability	1	 **NSOVM4** **NSOVM42G**
6-Way Coaxial Splitter Modules, One Incoming Line, Six Outgoing 1 Ghz, Basic Unit 2.3 Ghz, Enhanced Capability	1	 **NSOVM6** **NSOVM62G**
8-Way Coaxial Splitter Modules, One Incoming Line, Eight Outgoing 1 Ghz, Basic Unit 2.3 Ghz, Enhanced Capability	1	 **NSOVM8** **NSOVM82G**
Fixed Video Amplifier Module, 10dB 120 volt rated 240 volt rated Provides video signal amplification for incoming cable feeds recommended for use when more than four outputs are installed or when signal level is low. Provides 10dB forward path gain and supports current digital cable systems and modems with a passive return. Pre-mounted push pins snap the module quickly into place. Includes RG-59 cable jumper to connect amplifier to passive video splitter.	1	 **NSOVAMP** **NSOVAMP240**
8 Room Audio Module, Distributes audio from an amplifier to matching volume controllers. Supports up to eight rooms of audio. Power handling - 200W RMS@20° C. Requires impedance matching volume controls, see page V-67.	1	**NSOAM8**
Blank Module Plate Allows mounting of active components (i.e. switches, routers) or other devices (66 blocks, audio components) onto a modular platform. Can be custom drilled or used with two self-adhesive VELCRO® strips included to mount components onto module. Pre-mounted push pins snap the module quickly into place.	1	**NSOBM**



NSOVM4



NSOVM6



NSOVM8



NSOVAMP



NSOAM8



NSOBM

netSELECT®

Universal Consolidation Blocks, Patch Panels and Patch Cords

Structured Wiring

netSELECT® Patch Panels are excellent for designing rack systems for telephone, data and AV systems. Consolidation Blocks are ideal for small user count configurations that mount in or on the wall.

- Meets ANSI/TIA - Category 6 and Category 5e standards
- cULus Listed



NS5E12U



NS612U



NS5E24U



NS5E48U



NS624U



NS648U

Universal Consolidation Blocks and Patch Panels

Description	Catalog Number
Category 5e 12-Port Universal Consolidation Block, 89D Bracket Mount	**NS5E12U**
Category 6 12-Port Universal Consolidation Block, 89D Bracket Mount	**NS612U**
Category 5e Universal Patch Panel	
24-port, 1.75 inch H, 1 Rack Unit	**NS5E24U**
48-port, 3.50 inch H, 2 Rack Units	**NS5E48U**
Category 6 Universal Patch Panel	
24-port, 1.75 inch H, 1 Rack Unit	**NS624U**
48-port, 3.50 inch H, 2 Rack Units	**NS648U**

netSELECT® Patch Cords allow for quick change of voice/data lines with insertion of modular plugs.

- Meets and exceeds ANSI/TIA - Category 6 and Category 5e standards
- UL and cUL Listed

Universal Patch Cords, Category 6 and Category 5e

Description	Color	1-Foot	3-Foot	5-Foot	7-Foot	10-Foot	15-Foot	20-Foot	25-Foot
Cat. 5e Patch Cord	Blue	**HC5EB01**	**HC5EB03**	**HC5EB05**	**HC5EB07**	**HC5EB10**	**HC5EB15**	**HC5EB20**	**HC5EB25**
	Gray	**HC5EGY01**	**HC5EGY03**	**HC5EGY05**	**HC5EGY07**	**HC5EGY10**	**HC5EGY15**	**HC5EGY20**	**HC5EGY25**
	Yellow	**HC5EY01**	**HC5EY03**	**HC5EY05**	**HC5EY07**	**HC5EY10**	**HC5EY15**	**HC5EY20**	**HC5EY25**
	Red	**HC5ER01**	**HC5ER03**	**HC5ER05**	**HC5ER07**	**HC5ER10**	**HC5ER15**	**HC5ER20**	**HC5ER25**
Cat. 6 Patch Cord	Blue	**HC6B01**	**HC6B03**	**HC6B05**	**HC6B07**	**HC6B10**	**HC6B15**	**HC6B20**	**HC6B25**
	Gray	**HC6GY01**	**HC6GY03**	**HC6GY05**	**HC6GY07**	**HC6GY10**	**HC6GY15**	**HC6GY20**	**HC6GY25**
	Yellow	**HC6Y01**	**HC6Y03**	**HC6Y05**	**HC6Y07**	**HC6Y10**	**HC6Y15**	**HC6Y20**	**HC6Y25**
	Red	**HC6R01**	**HC6R03**	**HC6R05**	**HC6R07**	**HC6R10**	**HC6R15**	**HC6R20**	**HC6R25**

netSELECT®
Accessories
Structured Wiring

netSELECT® Accessories enhance system capabilities. Volume controls expand home audio applications. Cabinet mounted receptacle kits provide convenience power to the enclosure.

- Audio controls available in slide or rotary
- Receptacles available in surge and standard kits

Accessories

Description	Color	Catalog Number
Slide Audio Volume Controller, Decorator Styling, Power handling - 70W RMS@20° C. Impedance matching for up to 8 pairs of speakers. Includes both ivory and white slides and frames.	Ivory/White	**NSOSAVC**
Rotary Audio Volume Controller Power handling - 70W RMS@20° C. Impedance matching for up to 8 pairs of speakers. Includes both ivory and white knobs and frames.	Ivory/White	**NSORAVC**
Standard Power Kit, Includes duplex receptacle 15A 125V NEMA 5-15R, electrical steel box and wallplate.		**NSOKP**
Surge Suppression Power Kit, Includes surge receptacle 15A 125V NEMA 5-15R, 240 Joules/15,000A protection per mode, electrical steel box and wallplate.		**NSOKPS**
Chromed Steel Lock Kit, Includes two keys. Eliminates unwanted tampering.		**FLOCK1**
Panel Bracket Adapter, For use with Adapter Panels shown below, and FSP series modules in section P, page 16. Snap mounts into structured cabling enclosures.		**NSOFSB**
F-Connector Adapter Panel, with Six Populated Coaxial Connectors.		**FSPFP6X**
Keystone Adapter Panel, with Six Blank Openings for jacks and snap fits.		**FSPHD6X**
Antenna Kit.		**NSOKA**


NSOSAVC


NSORAVC


NSOKPS


FLOCK1


NSOFSB



FSPFP6X


FSPHD6X


NSOKA

netSELECT®
Modular Snap Fit Jacks
Decorator Products

Customize the jack selections and look



Molded-In Voice/Low-Speed Data

Description	Modular Snap Fit Cat. 6 Jack	Modular Snap Fit Cat. 5e Jack	Modular Snap Fit USOC Jack
Color			
Almond	**NSJ6AL**	**NSJ5EAL**	**NSJUAL**
Black	**NSJ6BK**	**NSJ5EBK**	**NSJUBK**
Blue	**NSJ6B**	**NSJ5EB**	**NSJUB**
Gray	**NSJ6GY**	**NSJ5EGY**	**NSJUGY**
Green	**NSJ6GN**	**NSJ5EGN**	**NSJUGN**
Ivory	**NSJ6I**	**NSJ5EI**	**NSJUI**
Light Almond	**NSJ6LA**	**NSJ5ELA**	**NSJULA**
Orange	**NSJ6OR**	**NSJ5EOR**	**NSJUOR**
Red	**NSJ6R**	**NSJ5ER**	**NSJUR**
White	**NSJ6W**	**NSJ5EW**	**NSJUW**
Yellow	**NSJ6Y**	**NSJ5EY**	**NSJUY**

Audio/Video Connectors - Standard Bulkhead

Description	Gold F-Type Coupler Bulkhead, Female to Female	Nickel F-Type Coupler Bulkhead, Female to Female	RCA Gold Pass Through, Female to Female, Red Interior	RCA Gold Pass Through, Female to Female, White Interior	RCA Gold Pass Through, Female to Female, Yellow Interior	RCA Gold Pass Through, Female to Female, Blue Interior	RCA Gold Pass Through, Female to Female, Green Interior
Color							
Almond	**SFFGAL**	**NSF70AL**	**SFRCRFFAL**	**SFRCWFFAL**	**SFRCYFFAL**	**SFRCBFFAL**	**SFRCGNFFAL**
Black	**SFFGBK**	**NSF70BK**	**SFRCRFFBK**	**SFRCWFFBK**	**SFRCYFFBK**	**SFRCBFFBK**	**SFRCGNFFBK**
Gray	**SFFGGY**	**NSF70GY**	**SFRCRFFGY**	**SFRCWFFGY**	**SFRCYFFGY**	**SFRCBFFGY**	**SFRCGNFFGY**
Ivory	**SFFGEI**	**NSF70I**	**SFRCRFFEI**	**SFRCWFFEI**	**SFRCYFFEI**	**SFRCBFFEI**	**SFRCGNFFEI**
Light Almond	**SFFGLA**	**NSF70LA**	**SFRCRFFLA**	**SFRCWFFLA**	**SFRCYFFLA**	**SFRCBFFLA**	**SFRCGNFFLA**
White	**SFFGW**	**NSF70W**	**SFRCRFFW**	**SFRCWFFW**	**SFRCYFFW**	**SFRCBFFW**	**SFRCGNFFW**

Audio/Video Connectors - Recessed

Description	Gold F-Type Coupler Bulkhead, Female to Female	RCA Gold Pass Through, Female to Female, Red Interior	RCA Gold Pass Through, Female to Female, White Interior	RCA Gold Pass Through, Female to Female, Yellow Interior	RCA Gold Pass Through, Female to Female, Blue Interior	RCA Gold Pass Through, Female to Female, Green Interior	Blank Insert
Color							
Almond	**SFGRFAL**	**SFRCRRAL**	**SFRCWRAL**	**SFRCYRAL**	**SFRCBRAL**	**SFRCGNRAL**	**SFSBAL10***
Black	**SFGRFBK**	**SFRCRRBK**	**SFRCWRBK**	**SFRCYRBK**	**SFRCBRBK**	**SFRCGNRBK**	**SFSBBK10***
Gray	**SFGRFGY**	**SFRCRRGY**	**SFRCWRGY**	**SFRCYRGY**	**SFRCBRGY**	**SFRCGNRGY**	**SFSBGY10***
Ivory	**SFGRFEI**	**SFRCRREI**	**SFRCWREI**	**SFRCYREI**	**SFRCBREI**	**SFRCGNREI**	**SFSBEI10***
Light Almond	**SFGRFLA**	**SFRCRRLA**	**SFRCWRLA**	**SFRCYRLA**	**SFRCBRLA**	**SFRCGNRLA**	**SFSBLA10***
White	**SFGRFW**	**SFRCRRW**	**SFRCWRW**	**SFRCYRW**	**SFRCBRW**	**SFRCGNRW**	**SFSBW10***

*Note: * Sold in a package of 10. Order 1 to receive a bag of 10 blanks.*

netSELECT®
Decorator Frames

Decorator Products

Features

Decorator frames provide a stylized look for that finishing touch. This allows all devices to match. Multimedia jacks insert into frame for custom configuration.

- Elongated strap for better wall box mounting
- High impact-resistant thermoplastic frame
- UL Listed 1863 - Communication Circuit Accessory and CSA Certified

Decorator Frames



Color	1-Gang, 2-Port	1-Gang, 3-Port	1-Gang, 4-Port	1-Gang, 6-Port	1-Gang, Adapter .406" (10.30) Dia. Hole*	1-Gang, Adapter Blank**
Almond	**NS612AL**	**NS613AL**	**NS614AL**	**NS616AL**	**NS621AL**	**NS620AL**
Black	**NS612BK**	**NS613BK**	**NS614BK**	**NS616BK**	—	—
Gray	**NS612GY**	**NS613GY**	**NS614GY**	**NS616GY**	—	—
Ivory	**NS612I**	**NS613I**	**NS614I**	**NS616I**	**NS621I**	**NS620I**
Light Almond	**NS612LA**	**NS613LA**	**NS614LA**	**NS616LA**	**NS621LA**	**NS620LA**
White	**NS612W**	**NS613W**	**NS614W**	**NS616W**	**NS621W**	**NS620W**

*Note: * For use with rotary dimmers or to pull through AV or telephone cable.*
*** To fill an extra decorator opening or to create customized openings.*

Multimedia Face Plates



Description	1-Gang, 1-Port Plate		1-Gang, 2-Port Plate		1-Gang, 3-Port Plate	
Color	Standard (4.63" x 2.88")	Mid-Size (4.88" x 3.13")	Standard (4.63" x 2.88")	Mid-Size (4.88" x 3.13")	Standard (4.63" x 2.88")	Mid-Size (4.88" x 3.13")
Almond	**NSP11AL**	**NSP101AL**	**NSP12AL**	**NSP102AL**	**NSP13AL**	**NSP103AL**
Black	**NSP11BK**	**NSP101BK**	**NSP12BK**	**NSP102BK**	**NSP13BK**	**NSP103BK**
Gray	**NSP11GY**	**NSP101GY**	**NSP12GY**	**NSP102GY**	**NSP13GY**	**NSP103GY**
Ivory	**NSP11I**	**NSP101I**	**NSP12I**	**NSP102I**	**NSP13I**	**NSP103I**
Light Almond	**NSP11LA**	**NSP101LA**	**NSP12LA**	**NSP102LA**	**NSP13LA**	**NSP103LA**
White	**NSP11W**	**NSP101W**	**NSP12W**	**NSP102W**	**NSP13W**	**NSP103W**



Description	1-Gang, 4-Port Plate		1-Gang, 6-Port Plate		2-Gang, 4-Port Plate	2-Gang, 6-Port Plate
Color	Standard (4.63" x 2.88")	Mid-Size (4.88" x 3.13")	Standard (4.63" x 2.88")	Mid-Size (4.88" x 3.13")	Standard (4.63" x 4.69")	Standard (4.63" x 4.69")
Almond	**NSP14AL**	**NSP104AL**	**NSP16AL**	**NSP106AL**	**NSP24AL**	**NSP26AL**
Black	**NSP14BK**	**NSP104BK**	**NSP16BK**	**NSP106BK**	**NSP24BK**	**NSP26BK**
Gray	**NSP14GY**	**NSP104GY**	**NSP16GY**	**NSP106GY**	**NSP24GY**	**NSP26GY**
Ivory	**NSP14I**	**NSP104I**	**NSP16I**	**NSP106I**	**NSP24I**	**NSP26I**
Light Almond	**NSP14LA**	**NSP104LA**	**NSP16LA**	**NSP106LA**	**NSP24LA**	**NSP26LA**
White	**NSP14W**	**NSP104W**	**NSP16W**	**NSP106W**	**NSP24W**	**NSP26W**

netSELECT®

Molded-In Voice/Data/Video

Data Communications and Audio/Video

Features

Designed to complement decorator styling, these jacks offer voice and Cat. 5e devices to fit within a decorator wallplate.

- High impact-resistant thermoplastic frame
- Meets FCC part 68
- UL Listed 1863 - Communication Circuit Accessory and CSA Certified

Molded-In Voice/Low-Speed Data

Description	Decorator Frame, One RJ11 Jack, 6-Position, 4-Conductor	Decorator Frame, One RJ11 Jack, 6-Position, 6-Conductor	Decorator Frame, Duplex RJ11 Jacks, 6-Position, 6-Conductor	Decorator Frame, One Cat. 5e 110 Punch-Down, One RJ11 Jack, 6-Position, 4-Conductor
Termination	Screw Terminations	Screw Terminations	Screw Terminations	Screw Terminations
Color				
Almond	**NS770AL**	**NS771AL**	**NS772AL**	**NS784AL**
Black	**NS770BK**	—	—	**NS784BK**
Brown	**NS770**	**NS771**	—	**NS784**
Gray	**NS770GY**	—	—	**NS784GY**
Ivory	**NS770I**	**NS771I**	**NS772I**	**NS784I**
Light Almond	**NS770LA**	**NS771LA**	**NS772LA**	**NS784LA**
White	**NS770W**	**NS771W**	**NS772W**	**NS784W**

Features

Coaxial video and combination jacks complement multimedia needs in a 1-gang decorator opening.

- High impact-resistant thermoplastic frame
- Jacks meet FCC part 68
- UL Listed 1863 - Communication Circuit Accessory and CSA Certified

Molded-In Voice/Low-Speed Data

Description	Decorator Frame, Single F-Type Coupler Bulkhead, Female to Female	Decorator Frame, Duplex F-Type Coupler Bulkhead, Female to Female	Decorator Frame, One RJ11 Jack, 6-Position, 4-Conductor, One F-Type Coupler Bulkhead, Female to Female	Decorator Frame, One Cat. 5e 110 Punch-Down, One F-Type Coupler Bulkhead, Female to Female
Termination	Screw Terminations	Screw Terminations	Screw Terminations	Screw Terminations
Color				
Almond	**NS780AL**	**NS782AL**	**NS783AL**	**NS785AL**
Black	—	—	—	**NS785BK**
Brown	—	—	—	**NS785**
Gray	—	—	—	**NS785GY**
Ivory	**NS780I**	**NS782I**	**NS783I**	**NS785I**
Light Almond	**NS780LA**	**NS782LA**	**NS783LA**	**NS785LA**
White	**NS780W**	**NS782W**	**NS783W**	**NS785W**

netSELECT®
Molded-In Plates

Data Communications and Audio/Video

Features

Designed for voice, these devices provide an economical alternative to wall phone outlet placement.

- High impact-resistant thermoplastic plate
- Convenient screw down terminals
- Meets FCC part 68
- UL Listed 1863 - Communication Circuit Accessory and CSA Certified

Molded-In Plates for Voice

Description	1-Gang Plate, One RJ11 Jack, 6-Position, 4-Conductor, Screw Terminations		1-Gang Plate, One RJ11 Jack, 6-Position, 6-Conductor, Screw Terminations	1-Gang Plate, Duplex RJ11 Jacks, 6-Position, 4-Conductor, Screw Terminations		1-Gang Plate, Duplex RJ11 Jacks, 6-Position, 6-Conductor, Screw Terminations
						
Color	Standard	Mid-Size	Standard	Standard	Mid-Size	Standard
Almond	**NS730AL**	**NS735AL**	**NS732AL**	**NS742AL**	**—**	**NS744AL**
Brown	**NS730**	**NS735**	**NS732**	**—**	**—**	**—**
Ivory	**NS730I**	**NS735I**	**NS732I**	**NS742I**	**NS745I**	**NS744I**
Light Almond	**NS730LA**	**NS735LA**	**NS732LA**	**NS742LA**	**—**	**—**
White	**NS730W**	**NS735W**	**NS732W**	**NS742W**	**NS745W**	**NS744W**

Molded-In Plates for Voice and CATV/Satellite

Description	1-Gang Plate, One F-Type Coupler Bulkhead, Female to Female, One RJ11 Jack, 6-Position, 6-Conductor		1-Gang Plate, One F-Type Coupler Bulkhead, Female to Female, One RJ11 Jack, 6-Position, 4-Conductor	1-Gang Plate, One F-Type Coupler Bulkhead, Female to Female		1-Gang Plate, Duplex F-Type Coupler Bulkhead, Female to Female
						
Color	Standard	Mid-Size	Standard	Standard	Mid-Size	Standard
Almond	**NS748AL**	**NS755AL**	**NS747AL**	**NS750AL**	**NS751AL**	**NS752AL**
Ivory	**NS748I**	**NS755I**	**NS747I**	**NS750I**	**NS751I**	**NS752I**
Light Almond	**NS748LA**	**NS755LA**	**NS747LA**	**NS750LA**	**NS751LA**	**NS752LA**
White	**NS748W**	**NS755W**	**NS747W**	**NS750W**	**NS751W**	**NS752W**

Description	1-Gang Plate, One Cat. 5e 110 Punch-Down One RJ11 Jack, 6-Position, 4-Conductor One F-Type Coupler Bulkhead, Female to Female
	
Color	Standard
Almond	**NS790AL**
Black	**NS790BK**
Brown	**NS790**
Gray	**NS790GY**
Ivory	**NS790I**
Light Almond	**NS790LA**
White	**NS790W**

netSELECT®

Telephone Wall Jacks


Data Communications and Audio/Video

Features

Designed for voice applications, these jacks provide an economical alternative to basic wall mount and performance needs.

- Available in high impact-resistant thermoplastic or stainless steel
- Meets FCC part 68
- UL Listed 1863 - Communication Circuit Accessory and CSA Certified

Telephone Wall Jacks

Description	Wall Phone Jack Quick Connect, 6-Position, 4-Conductor, Punch-Down Termination Tool Included	Wall Phone Jack, 6-Position, 4-Conductor, Screw Terminations	Wall Phone Jack, 6-Position, 6-Conductor, Screw Terminations
Color			
Almond	**NS721AL**	**NS722AL**	**NS725AL**
Ivory	**NS721I**	**NS722I**	**NS725I**
Light Almond	**—**	**—**	**NS725LA**
White	**NS721W**	**NS722W**	**NS725W**

Description	Wall Phone Jack Quick Connect, 6-Position, 4-Conductor, Punch-Down Termination Tool Included	Wall Phone Jack, 6-Position, 4-Conductor, Screw Terminations
		
Stainless Steel	**NS723SS**	**NS726SS**

Features

Telephone surface mount jacks are available in 4- or 6-conductor configurations for voice. Alternatively, multimedia surface mount boxes can be custom loaded for computer and media use.

- High impact-resistant thermoplastic
- Mounts using screws or double sided tape (both included)
- Meets FCC part 68
- UL Listed 1863 - Communication Circuit Accessory and CSA Certified

Telephone Wall Jacks

Description	Telephone Surface Mount Jack, 6-Position, 4-Conductor, Screw Terminations	Telephone Surface Mount Jack, 6-Position, 6-Conductor, Screw Terminations	Multimedia 1-Port Surface Mount Box, Jack Not Included	Multimedia 2-Port Surface Mount Box, Jacks Not Included
				
Ivory	**NS760I**	**NS761I**	**ISM1EI***	**ISM2EI***
White	**NS760W**	**NS761W**	**ISM1W***	**ISM2W***

*Note: * cULus Listed 1863 - Communication Circuit Accessory.*
Use multimedia jacks and AV connectors, see section P for complete list.