KILLARK®

EYS-4 - 1¼" EYS Seal Fitting Aluminum, Female/Female

By Killark
Catalog # EYS-4

1¼" EYS Seal Fitting Aluminum, Female/Female



*Representative Image

Features

- Large opening for easy packing of fiber and pouring of compound
- Integral bushings in conduit hubs to protect conductor insulation from damage
- NPT tapped hubs to ensure ground continuity
- 25% conductor fill
- EYS-T style supplied with removable close nipples

Application

Class I, Divisions 1 and 2: The purpose of seals in a Class I hazardous location is to minimize the passage of gases and vapors and prevent the passage of flames from one electrical installation to another through the conduit system. Seals are required to

Specifications

CSA File Number	LR11716
UL File Number	E10514
Hazardous Rating(s)	• Class I, Divisions 1 & 2, Groups C, D • Class I, Zones 1 & 2, Groups IIB, IIA • Class II, Divisions 1 & 2, Groups E, F, G • Class III, Divisions 1 & 2

Dimensions

Hub Size	1-1/4"
Length	10.12 in
Height	7.062 in
Width	4.68 in
Gross Weight with Packaging	0.9
Dimensions	10.12 in x 4.68 in x 7.062 in

General

Color	Gray
Product Family	Fittings
Series	EYS Series
UPC	783936110141
Type	Sealing Fitting
Material	Aluminum, Copper Free (less than 4/10 of 1%)
Finish Type	Powder Epoxy Paint

Logistics

Carton Quantity	5

Product Assets

Catalog [English]
Installation Manual [English]
Installation Manual [English]

© 2026 Hubbell Incorporated. All rights reserved