


Blackburn®

Parallel Groove Connector
T&B Catalog Number: PAE2121-9
UPC Number: 78378633030
Status: Active
Description:

Aluminum Type PAE - Parallel Groove Clamp, Extruded Type for Wire Range Main: 2/0 ACSR-6 sol 6 AR Tap: 2/0 ACSR-6 sol 6 AR



Features

	For use on aluminum to aluminum or aluminum to copper connections with oxide inhibitor. Can be installed with live line tools.
	Standard PAE clamp is supplied with Contax (-9) and galvanized steel hardware.

General

Style	Type PAE - Parallel Groove Clamp, Extruded Type
Material	Aluminum
Conductor Range ACSR Main	2/0 ACSR-6 sol 6 AR
Conductor Range ACSR Tap	2/0 ACSR-6 sol 6 AR
Galvanized Steel Bolt Thd. Size	3/8-16 UNC
Aluminum Bolt Thd. Size	3/8-16 UNC

Dimension Information

B (inches)	7/8
F (inches)	9/16
H (inches)	2
L (inches)	1 3/8
W (inches)	1 5/8
Conductor Diameter Main Max.	0.447
Conductor Diameter Main Min.	0.162
Conductor Diameter Tap Max.	0.447
Conductor Diameter Tap Min.	0.162

Packaging

T&B Inner Pack	50
Package in Units	200
T&B Sold in UOM	Each
T&B Weight Per UOM	20.6 lbs. per 100

Notes

	Tin plating (-P) or wax dip (-6) must be specified for without oxide inhibitor-filled connectors.
	Options: 7 Aluminum hardware, P Tin plating, 6 Wax dip for oxide protection.
	RUS listed.

Certifications

RoHS Compliance	Yes

For further technical assistance, please contact us...

Thomas & Betts - USA
8155 T&B Blvd.

T&B Technical Support
MS 3B-50

Hours: 7AM - 6PM CDT
Monday-Friday

Memphis, TN 38125
www.tnb.com

8155 T&B Blvd.
Memphis, TN 38125

Phone: (888) 862-3289
Fax: (901) 252-1321
Email:techsupport@tnb.com