## 4" SQUARE (4S) DEEP BOXES WELDED 2-1/8" DEEP

30.3 Cu. In.


**WITH RAISED GROUND EMBOSS**

**Boxes with Pigtail Features:**

- 10" Solid Cu. #12AWG Pigtail pre-assembled with Ground Emboss and 10-32 Ground Screw

**BSA Features:**

- UMI Back Support Arm installed on this box provides support for studs up to 6" deep
- An excellent choice for pre-fab applications




**Adjustable Rings Features:**

- For more information see Page A13


**Note:**

- MKO configuration revised October 2012


| Cat. No. | Bracket & Setback | Knockouts | | Std. Pkg. |
|---|---|---|---|---|
| | | Sides | Bottom | |
| **4SDB-50/75-PT-BSA** | With Back Support Arm | 8 - 1/2", 4 - 3/4" | 1 - 1/2", 2 - 3/4" | 24 |
| **4SDB-50/75-AB-PT-BSA** | With AB, Flush, Back Support Arm | 6 - 1/2", 3 - 3/4" | 1 - 1/2", 2 - 3/4" | 24 |
| **4SDB-MKO-PT-BSA** | With Back Support Arm | 8 - 1/2", 4 - MKO | 1 - 1/2", 2 - MKO | 24 |
| **4SDB-MKO-AB-PT-BSA** | With AB, Flush, Back Support Arm | 6 - 1/2", 3 - MKO | 1 - 1/2", 2 - MKO | 24 |
| **4SDB-MKO-AR1G** | AB, Flush, Back Support Arm w/ 4SA1RG | 6 - 1/2", 3 - MKO | 1 - 1/2", 2 - MKO | 24 |
| **4SDB-MKO-AR2G** | AB, Flush, Back Support Arm w/ 4SA2RG | 6 - 1/2", 3 - MKO | 1 - 1/2", 2 - MKO | 24 |




4SDB-50/75-PT-BSA




4SDB-50/75-AB-PT-BSA




4SDB-MKO-PT-BSA



4SDB-MKO-AB-PT-BSA



4SDB-MKO-AR1G




4SDB-MKO-AR2G


**Fully Assembled with Adjustable Ring, 10" Ground Pigtail & Adjustable Back Support**

## 4" SQUARE (4S) COVERS FLAT OR DRAWN


| Cat. No. | Description | Cu. Inch | Std. Pkg. |
|---|---|---|---|
| **4BC** | Flat, Blank | - | 50 |
| **4BCK** | Flat, 1/2" KO | - | 50 |
| **4BC-MKO** | Flat, MKO | - | 50 |
| **43000** | Flat, Open, Ears 2-3/4" O.C. | - | 50 |
| **43050** | Raised 1/2", Open, Ears 2-3/4" O.C. | 3.0 | 50 |
| **43058** | Raised 5/8", Open, Ears 2-3/4" O.C. | 4.0 | 50 |
| **43075** | Raised 3/4", Open, Ears 2-3/4" O.C. | 5.0 | 50 |
| **43100** | Raised 1", Open, Ears 2-3/4" O.C. | 6.8 | 25 |
| **43125** | Raised 1-1/4", Open, Ears 2-3/4" O.C. | 8.5 | 25 |
| **43150** | Raised 1-1/2", Open, Ears 2-3/4" O.C. | 9.7 | 25 |
| **43200** | Raised 2", Open, Ears 2-3/4" O.C. | 12.9 | 25 |




4BC




4BCK



4BC-MKO



43000



43050
43058
43075
43100
43125
43150
43200

- **600V** MKO's and CKO's suitable for bonding without any additional bonding means up to 600V
- Acceptable for use in 2-hour rated walls
- Visit www.ul.com or QCIT Guide on page W1 for more information



File E227970 UL RoHS