Packard

Supplying HVACR solutions with your needs in mind.



TITAN MAX®

Packard

DEFINITE PURPOSE CONTACTORS

Leading the industry with two great contactors!

We carry the largest range of 1 to 4 pole contactors,
as well as their accessories.

TITAN MAX®

DEFINITE PURPOSE CONTACTORS

DROP IN
FURNAS
REPLACEMENT

WHEN DEPENDABILITY IS A MUST...

- **ELECTRICAL ENDURANCE**
  Tested up to 250,000 cycles
- **LONG MECHANICAL LIFE**
  Tested up to 1,000,000 cycles
- **COMPACT FOOTPRINT**
  Makes it especially ideal for AC applications and many more versus other contactors
- **MULTIPLE CONFIGURATIONS**
  Available in 1+, 2, 3 and 4 Poles
- **FULLY ENCLOSED BODY**
  Tight seams to help eliminate the ingress of dirt and bugs for maximum endurance



A SOLUTION FROM Packard


MEETS
ARI 780/790

ADDITIONAL FEATURES

- SUPERIOR COPPER COIL
- UNIVERSAL MOUNTING PLATE
- REMOVABLE COVER
- ACCEPTS AUXILIARY SWITCHES
- MOUNTING LUGS ON ALL CONFIGURATIONS

CROSS REFERENCE

Item ID	F/L Inductive Amps	Locked Rotor Amps 240/480/600	Resistive Amps	Coil Voltage	Accepts Aux. Switch*	Industry No.	Direct Replacement For --- Furnas	AllTemp	DiversiTech
Titan Max 1 Pole									
TMX125A2	25	150/125/100	35	24			45DG10AJA		
TMX125B2	25	150/125/100	35	120			45DG10AFA		
TMX125C2	25	150/125/100	35	208/240			45DG10AGA		
TMX130A2	30	180/150/120	40	24		61720	45EG10AJA, 45EG10AJAL	DP-1P30A24	
TMX130B2	30	180/150/120	40	120		61721	45EG10AFA, 45EG10AFAL	DP-1P30A120	
TMX130C2	30	180/150/120	40	208/240		61722	45EG10AGA, 45EG10AGAL	DP-1P30A240	
TMX140A2	40	240/200/160	50	24		61730	45GG10AJA, 45GG10AJAL	DP-1P40A24	
TMX140B2	40	240/200/160	50	120		61731	45GG10AFA, 45GG10AFAL	DP-1P40A120	
TMX140C2	40	240/200/160	50	208/240		61732	45GG10AGA, 45GG10AGAL	DP-1P40A240	
Titan Max 2 Pole									
TMX225A2	25	150/125/100	35	24			42AF15AJ, 45DG20AJ	DP-2P25A24	EC25224
TMX225B2	25	150/125/100	35	120			42AF15AF, 45DG20AF	DP-2P25A120	EC252120
TMX225C2	25	150/125/100	35	208/240			42AF15AG, 45DG20AG	DP-2P25A240	EC252240
TMX230A2	30	180/150/120	40	24		61745	42BF15AJ, 45EG20AJ, 45EG20AJL	DP-2P30A24	EC30224
TMX230B2	30	180/150/120	40	120		61746	42BF15AF, 45EG20AF, 45EG20AFL	DP-2P30A120	EC302120
TMX230C2	30	180/150/120	40	208/240		61747	42BF15AG, 45EG20AG, 45EG20AGL	DP-2P30A240	EC302240
TMX240A2	40	240/200/160	50	24		61755	42CF15AJ, 45GG20AJ, 45GG20AJL	DP-2P40A24	EC40224
TMX240B2	40	240/200/160	50	120		61756	42CF15AF, 45GG20AFL	DP-2P40A120	EC402120
TMX240C2	40	240/200/160	50	208/240		61757	42CF15AG, 45GG20AG, 45GG20AGL	DP-2P40A240	EC402240
Titan Max 3 Pole									
TMX330A2	30	180/150/120	40	24	Yes	61430	42BF35AJ	DP-3P30A24	EC30324
TMX330B2	30	180/150/120	40	120	Yes	61431	42BF35AF	DP-3P30A120	EC303120
TMX330C2	30	180/150/120	40	208/240	Yes	61432	42BF35AG	DP-3P30A240	EC303240
TMX340A2	40	240/200/160	50	24	Yes	61445	42CF35AJ	DP-3P40A24	EC40324
TMX340B2	40	240/200/160	50	120	Yes	61446	42CF35AF	DP-3P40A120	EC403120
TMX340C2	40	240/200/160	50	208/240	Yes	61447	42CF35AG	DP-3P40A240	EC403240
TMX350A2	50	300/250/200	65	24	Yes	61460	42DF35AJ	DP-3P50A24	EC50324
TMX350B2	50	300/250/200	65	120	Yes	61461	42DF35AF	DP-3P50A120	EC503120
TMX350C2	50	300/250/200	65	208/240	Yes	61462	42DF35AG	DP-3P50A240	EC503240
TMX360A2	60	360/300/240	75	24	Yes	61470	42EF35AJ	DP-3P60A24	EC60324
TMX360B2	60	360/300/240	75	120	Yes	61471	42EF35AF	DP-3P60A120	EC603120
TMX360C2	60	360/300/240	75	208/240	Yes	61472	42EF35AG	DP-3P60A240	EC603240
TMX375A2	75	450/375/300	90	24	Yes	61480	42FE35AJ106	DP-3P75A24	EC75324
TMX375B2	75	450/375/300	90	120	Yes	61481	42FE35AF106	DP-3P75A120	EC753120
TMX375C2	75	450/375/300	90	208/240	Yes	61482	42FE35AG106	DP-3P75A240	EC753240
TMX390A2	90	540/450/360	120	24	Yes	61490	42GE35AJ106	DP-3P90A24	EC90324
TMX390B2	90	540/450/360	120	120	Yes	61491	42GE35AF106	DP-3P90A120	EC903120
TMX390C2	90	540/450/360	120	208/240	Yes	61492	42GE35AG106	DP-3P90A240	EC903240
Titan Max 4 Pole									
TMX430A2	30	180/150/120	40	24	Yes		42BF25AJ	DP-4P30A24	
TMX430B2	30	180/150/120	40	120	Yes		42BF25AF	DP-4P30A120	
TMX430C2	30	180/150/120	40	208-240	Yes		42BF25AG	DP-4P30A240	
TMX440A2	40	240/200/160	50	24	Yes		42CF25AJ	DP-4P40A24	
TMX440B2	40	240/200/160	50	120	Yes		42CF25AF	DP-4P40A120	
TMX440C2	40	240/200/160	50	208-240	Yes		42CF25AG	DP-4P40A240	



*Flexible auxiliary switch options allow you to select any of the Titan Max auxiliary switches depending on your application.
TMX1NC (SPST NC), **TMX1NO** (SPST NO), **TMX2NC** (DPST NC), **TMX2NO** (DPST NO),
TMX1NC/NO (DPST 1NC + 1NO), **TMXSPDT1** (SPDT - left position),
TMXSPDT2 (SPDT - right position), **TMX2SPDT** (2xSPDT) will fit any 3 pole, 30 – 60 Amp Titan Max contactor.
TMX7590NO (SPST NO), **TMX7590NC** (SPST NC), **TMX7590SPDT** (SPDT) will fit any 3 pole, 75 – 90 Amp Titan Max contactor.



DON'T FORGET to check out our Replacement Coils for Titan Max Contactors.
TMXC32040A (24 Volt),**TMXC32040B** (120 Volt), **TMXC32040C** (208/240 Volt) will fit any 3 pole, 20 – 40 Amp Titan Max contactor.
TMXC35060A (24 Volt), **TMXC35060B** (120 Volt), **TMXC35060C** (208/240 Volt) will fit any 3 pole, 50 – 60 Amp Titan Max contactor.
TMXC37590B (120 Volt), **TMXC37590B** (208/240 Volt) will fit any 3 pole, 75 – 90 Amp Titan Max contactor.

Packard Definite Purpose Contactors



FEATURES

CONTACTORS MEET UL508 SPECIFICATIONS FOR DEVICES UP TO 600 VAC.

- 50/60 Hertz
- Coils have class B insulation
- Includes lugs, spade terminals and covers
- All single pole include shunt

Item ID	Poles	F/L Inductive Amps	Locked Rotor Amps 240/480/600	Resistive Amps	Coil Voltage	Accepts Aux. Switch*	- Direct Replacement For - AllTemp	DiversiTech
Packard 1 Pole								
C125A	1+	25	150/125/100	35	24		—	—
C125B	1+	25	150/125/100	35	120		—	—
C125C	1+	25	150/125/100	35	208/240		—	—
C130A	1+	30	180/150/120	40	24		DP-1P30A24	—
C130B	1+	30	180/150/120	40	120		DP-1P30A120	—
C130C	1+	30	180/150/120	40	208/240		DP-1P30A240	—
C140A	1+	40	240/200/160	50	24		DP-1P40A24	—
C140B	1+	40	240/200/160	50	120		DP-1P40A120	—
C140C	1+	40	240/200/160	50	208/240		DP-1P40A240	—
Packard 2 Pole								
C220A	2	20	120/100/80	30	24		DP-2P20A24	—
C220B	2	20	120/100/80	30	120		DP-2P20A120	—
C220C	2	20	120/100/80	30	208/240		DP-2P20A240	—
C225A	2	25	150/125/100	35	24		DP-2P25A24	EC25224
C225B	2	25	150/125/100	35	120		DP-2P25A120	EC252120
C225C	2	25	150/125/100	35	208/240		DP-2P25A240	EC252240
C230A	2	30	180/150/120	40	24		DP-2P30A24	EC30224
C230B	2	30	180/150/120	40	120		DP-2P30A120	EC302120
C230C	2	30	180/150/120	40	208/240		DP-2P30A240	EC302240
C230D *	2	30	180/150/120	40	208/240		—	—
C230E	2	30	180/150/120	40	277		—	—
C240A	2	40	240/200/160	50	24		DP-2P40A24	EC40224
C240B	2	40	240/200/160	50	120		DP-2P40A120	EC402120
C240C	2	40	240/200/160	50	208/240		DP-2P40A240	EC402240
C240E	2	40	240/200/160	50	277		—	—
Packard 3 Pole								
C325A	3	25	150/125/100	35	24	AC3	DP-3P25A24	—
C325B	3	25	150/125/100	35	120	AC3	DP-3P25A120	—
C325C	3	25	150/125/100	35	208/240	AC3	DP-3P25A240	—
C330A	3	30	180/150/120	40	24	AC3, P6S, P7S	DP-3P30A24	EC30324
C330B	3	30	180/150/120	40	120	AC3, P6S, P7S	DP-3P30A120	EC303120
C330C	3	30	180/150/120	40	208/240	AC3, P6S, P7S	DP-3P30A240	EC303240
C330E	3	30	180/150/120	40	277	AC3, P6S, P7S	—	EC303277
C330F	3	30	180/150/120	40	480	AC3, P6S, P7S	—	—


*Contactor has screw terminals instead of lugs.

Packard Definite Purpose Contactors (Cont.) & Coils / Aux. Switches


PR4013


C18001


P8S


C35060A

Item ID	Poles	F/L Inductive Amps	Locked Rotor Amps 240/480/600	Resistive Amps	Coil Voltage	Accepts Aux. Switch*	- Direct Replacement For - AllTemp	DiversiTech
Packard 3 Pole (continued)								
C340A	3	40	240/200/160	50	24	AC3, P6S, P7S	DP-3P40A24	EC40324
C340B	3	40	240/200/160	50	120	AC3, P6S, P7S	DP-3P40A120	EC403120
C340C	3	40	240/200/160	50	208/240	AC3, P6S, P7S	DP-3P40A240	EC403240
C340E	3	40	240/200/160	50	277	AC3, P6S, P7S	—	EC403277
C340F	3	40	240/200/160	50	480	AC3, P6S, P7S	—	—
C350A	3	50	300/250/200	65	24	P8S, P38K	DP-3P50A24	EC50324
C350B	3	50	300/250/200	65	120	P8S, P38K	DP-3P50A120	EC503120
C350C	3	50	300/250/200	65	208/240	P8S, P38K	DP-3P50A240	EC503240
C350F	3	50	300/250/200	65	480	P8S, P38K	—	EC503277
C360A	3	60	360/300/240	75	24	P8S, P38K	DP-3P60A24	EC60324
C360B	3	60	360/300/240	75	120	P8S, P38K	DP-3P60A120	EC603120
C360C	3	60	360/300/240	75	208/240	P8S, P38K	DP-3P60A240	EC603240
C360F	3	60	360/300/240	75	480	P8S, P38K	—	EC603277
C375A	3	75	450/375/300	90	24	P9S	DP-3P75A24	EC75324
C375B	3	75	450/375/300	90	120	P9S	DP-3P75A120	EC753120
C375C	3	75	450/375/300	90	208/240	P9S	DP-3P75A240	EC753240
C390A	3	90	540/450/360	120	24	P9S	DP-3P90A24	EC90324
C390B	3	90	540/450/360	120	120	P9S	DP-3P90A120	EC903120
C390C	3	90	540/450/360	120	208/240	P9S	DP-3P90A240	EC903240
Packard 4 Pole								
C430A	4	30	180/150/120	40	24	AC3, P6S, P7S	DP-4P30A24	—
C430B	4	30	180/150/120	40	120	AC3, P6S, P7S	DP-4P30A120	—
C430C	4	30	180/150/120	40	208/240	AC3, P6S, P7S	DP-4P30A240	—
C430F	4	30	180/150/120	40	480	AC3, P6S, P7S	—	—
C440A	4	40	240/200/160	50	24	AC3, P6S, P7S	DP-4P40A24	—
C440B	4	40	240/200/160	50	120	AC3, P6S, P7S	DP-4P40A120	—
C440C	4	40	240/200/160	50	208/240	AC3, P6S, P7S	DP-4P40A240	—
C440F	4	40	240/200/160	50	480	AC3, P6S, P7S	—	—

Item ID	Poles	F/L Inductive Amps	Locked Rotor Amps 240/480/600	Resistive Amps	Coil Voltage	- Direct Replacement For -
DP Contactor						
PR4013	1	30	—	40	24	DP-1030A50123

Item ID	Type	F/L Inductive Amps	Locked Rotor Amps 240/480/600	Resistive Amps	Coil Voltage	Hertz	Max. Surrounding Air Temp.	Phase	- Direct Replacement For -
Magnetic Contactor									
C18001	DPST N.O.	30	120	30	24	50/60	40°C	Single	3ARR8E4, MC11, 90-230, 18001, R850B1146

*Flexible auxiliary switch options allow you to select any of the Packard auxiliary switches depending on your application.

P6S (SPDT) & **P7S** (DPDT) will fit any 3 & 4 pole, 25-40 Packard contactor, **P8S, P9S** (SPDT) will fit any 3 & 4 pole, 50-60/70 – 90 Amp Packard contactor.
AC4 (1 SPDT) will fit any 3 & 4 pole, 50-60 Amp Packard contactor, **AC3** (NO/NC) will fit any 3 & 4 pole, 25-40 Amp Packard contactor.
MI1 (Mechanical Interlock) will fit any 3 & 4 pole, 25-40 Amp Packard contactor. **P38K** (Includes P8S & AC3), will fit any 3 & 4 pole Packard contactor.

DON'T FORGET to check out our Replacement Coils for Packard Contactors.

C32040A (24 V), **C32040B** (120 V), **C32040C** (208/240 V), **C32040D** (277 V), **C32040E** (480 V) will fit any 3 pole, 20 – 40 Amp Packard contactor.
C35060A (24 V), **C35060B** (120 V), **C35060C** (208/240 V), **C35060D** (277 V), **C35060E** (480 V) will fit any 3 pole, 50 – 60 Amp Packard contactor.
C37590B (120 V), **C37590C** (208/240 V) will fit any 3 pole, 75 – 90 Amp Packard contactor.
C42040A (24 V), **C42040B** (120 V), **C42040C** (208/240 V), **C42040D** (277 V) will fit any 4 pole, 20 – 40 Amp Packard contactor.

Packard

Supplying HVACR solutions with your needs in mind.



WEST COAST DISTRIBUTION CENTER
7350 SOUTH KYRENE ROAD, SUITE 104
TEMPE, AZ 85283

CORPORATE HEADQUARTERS AND DISTRIBUTION CENTER
2700 BARRETT LAKES BLVD. NW, SUITE 100
KENNESAW, GA 30144

LOCAL: **770-427-5765** | TOLL FREE: **800-334-1769** | FAX: **770-427-5140**
EMAIL: **CUSTOMERSERVICE@PACKARDONLINE.COM**

PACKARDONLINE.COM |

PACKARD SUPPLIES TO WHOLESALE DISTRIBUTION ONLY | ©2021 PACKARD, INC.

DIVERSITECH®

PACKARD IS NOW A MEMBER OF THE DIVERSITECH FAMILY

SCAN HERE TO VIEW DIVERSITECH'S FULL OFFERING