Definite Purpose Contactors



Features

Contactors meet UL508 specifications for devices up to 600 Vac.

- **50/60 Hertz •**
- **Coils have class B insulation**
- **Includes lugs, spade terminals and covers**
- **All single pole include shunt**

Item ID	Poles	F/L Inductive Amps	Locked Rotor Amps 240/480/600	Resistive Amps	Coil Voltage
Packard 1 Pole					
C125A	1+	25	150/125/100	30	24
C125B	1+	25	150/125/100	30	120
C125C	1+	25	150/125/100	30	208/240
C130A	1+	30	180/150/120	40	24
C130B	1+	30	180/150/120	40	120
C130C	1+	30	180/150/120	40	208/240
C140A	1+	40	240/200/160	50	24
C140B	1+	40	240/200/160	50	120
C140C	1+	40	240/200/160	50	208/240
Packard 2 Pole					
C220A	2	20	120/100/80	30	24
C220B	2	20	120/100/80	30	120
C220C	2	20	120/100/80	30	208/240
C225A	2	25	150/125/100	35	24
C225B	2	25	150/125/100	35	120
C225C	2	25	150/125/100	35	208/240
C230A	2	30	180/150/120	40	24
C230B	2	30	180/150/120	40	120
C230C	2	30	180/150/120	40	208/240
C230D *	2	30	180/150/120	40	208/240
C230E	2	30	180/150/120	40	277
C240A	2	40	240/200/160	50	24
C240B	2	40	240/200/160	50	120
C240C	2	40	240/200/160	50	208/240
C240E	2	40	240/200/160	50	277
C240F	2	40	240/200/160	50	480
C250A	2	50	300/250/200	65	24
C250B	2	50	300/250/200	65	120
C250C	2	50	300/250/200	65	208/240
C250F	2	50	300/250/200	65	480
C260A	2	60	360/300/240	75	24
C260B	2	60	360/300/240	75	120
C260C	2	60	360/300/240	75	208/240
C260F	2	60	360/300/240	75	480
C275A	2	75	450/375/300	90	24
C275B	2	75	450/375/300	90	120
C275C	2	75	450/375/300	90	208/240
C290A	2	90	540/450/360	120	24
C290B	2	90	540/450/360	120	120
C290C	2	90	540/450/360	120	208/240
Packard 3 Pole					
C325A	3	25	150/125/100	35	24
C325B	3	25	150/125/100	35	120
C325C	3	25	150/125/100	35	208/240
C330A	3	30	180/150/120	40	24
C330B	3	30	180/150/120	40	120
C330C	3	30	180/150/120	40	208/240
C330E	3	30	180/150/120	40	277
C330F	3	30	180/150/120	40	480
C340A	3	40	240/200/160	50	24
C340B	3	40	240/200/160	50	120
C340C	3	40	240/200/160	50	208/240
C340E	3	40	240/200/160	50	277
C340F	3	40	240/200/160	50	480
C350A	3	50	300/250/200	65	24
C350B	3	50	300/250/200	65	120
C350C	3	50	300/250/200	65	208/240
C350F	3	50	300/250/200	65	480
C360A	3	60	360/300/240	75	24
C360B	3	60	360/300/240	75	120
C360C	3	60	360/300/240	75	208/240
C360F	3	60	360/300/240	75	480
C375A	3	75	450/375/300	90	24
C375B	3	75	450/375/300	90	120
C375C	3	75	450/375/300	90	208/240
C390A	3	90	540/450/360	120	24
C390B	3	90	540/450/360	120	120
C390C	3	90	540/450/360	120	208/240
Packard 4 Pole					
C430A	4	30	180/150/120	40	24
C430B	4	30	180/150/120	40	120
C430C	4	30	180/150/120	40	208/240
C430F	4	30	180/150/120	40	480
C440A	4	40	240/200/160	50	24
C440B	4	40	240/200/160	50	120
C440C	4	40	240/200/160	50	208/240
C440F	4	40	240/200/160	50	480

Item ID	Aux. Switch
C325A	AC3
C325B	AC3
C325C	AC3
C330A	AC3, P6S, P7S
C330B	AC3, P6S, P7S
C330C	AC3, P6S, P7S
C330E	AC3, P6S, P7S
C330F	AC3, P6S, P7S
C340A	AC3, P6S, P7S
C340B	AC3, P6S, P7S
C340C	AC3, P6S, P7S
C340E	AC3, P6S, P7S
C340F	AC3, P6S, P7S
C350A	P8S, P38K
C350B	P8S, P38K
C350C	P8S, P38K
C350F	P8S, P38K
C360A	P8S, P38K
C360B	P8S, P38K
C360C	P8S, P38K
C360F	P8S, P38K
C375A	P9S
C375B	P9S
C375C	P9S
C390A	P9S
C390B	P9S
C390C	P9S
C430A	AC3, P6S, P7S
C430B	AC3, P6S, P7S
C430C	AC3, P6S, P7S
C430F	AC3, P6S, P7S
C440A	AC3, P6S, P7S
C440B	AC3, P6S, P7S
C440C	AC3, P6S, P7S
C440F	AC3, P6S, P7S

Notes:
* Spade terminals and cover only.
Auxiliary Switches sold separately. See page 226.

Magnetic Contactor



Item ID	C18001
Type	DPST N.O.
Resistive Amps	30
Full Load Amps	30
Locked Rotor Amps	120
Coil Voltage	24
Hertz	50/60
Max. Surrounding Air Temp.	40°C
Phase	Single

Replaces

3ARR8E4	MC11	18001
90-230	R850B1146	

DP Contactor



Item ID	PR4013
F/L Inductive Amps	30
Poles	1
Resistive Amps	40
Coil Voltage	24

Replaces

DP1030A5013