INSULATED BUSHINGS MALLEABLE IRON

Use with locknut to terminate threaded Rigid/IMC conduit to an outlet



Features: Insulated liner rated at 150° C
Material: Malleable Iron
Certifications: cULus

Catalog Number	Trade Size	Unit Pkg.	Standard Pkg.	Catalog Number	Trade Size	Unit Pkg.	Standard Pkg.
MIB-90M	1/2"	100	1,000	MIB-96M	2 1/2"	-	25
MIB-91M	3/4"	100	1,000	MIB-97M	3"	-	25
MIB-92M	1"	50	500	MIB-98M	3 1/2"	-	25
MIB-93M	1 1/4"	25	250	MIB-99M	4"	-	25
MIB-94M	1 1/2"	25	250	MIB-101M	5"	-	10
MIB-95M	2"	25	100	MIB-102M	6"	-	10

INSULATING BUSHINGS PLASTIC

Use with locknut to terminate threaded Rigid/IMC conduit to an outlet



Features: Rated flame retardant to 105° C
Material: Polypropylene
Certifications: cULus

Catalog Number	Trade Size	Unit Pkg.	Standard Pkg.	Catalog Number	Trade Size	Unit Pkg.	Standard Pkg.
501	1/2"	100	1,000	507	2 1/2"	-	25
502	3/4"	100	1,000	508	3"	-	25
503	1"	50	500	509	3 1/2"	-	25
504	1 1/4"	25	250	510	4"	-	25
505	1 1/2"	25	250	512	5"	-	5
506	2"	10	100	513	6"	-	5

RIGID ONE HOLE STRAPS STEEL

Supports Rigid/IMC conduit to mounting surface



Features: Reinforced snap-on feature
Material: Steel
Certifications: cULus
* Dual rated for EMT and Rigid

Catalog Number	Trade Size	Unit Pkg.	Standard Pkg.	Catalog Number	Trade Size	Unit Pkg.	Standard Pkg.
160-S	1/4"	100	1,000	166-S	1 1/2"	50	250
161-S	3/8"	100	1,000	167-S	2"	-	50
162-S	1/2"	100	1,000	*168-S	2 1/2"	-	25
163-S	3/4"	100	1,000	*169-S	3"	-	25
164-S	1"	50	500	*170-S	3 1/2"	-	10
165-S	1 1/4"	50	500	*171-S	4"	-	10

RIGID TWO HOLE STRAPS STEEL

Supports Rigid/IMC conduit to mounting surface



Features: Reinforced snap-on feature
Material: Steel
Certifications: cULus
* Dual rated for EMT and Rigid

Catalog Number	Trade Size	Unit Pkg.	Standard Pkg.	Catalog Number	Trade Size	Unit Pkg.	Standard Pkg.
TH-161S	3/8"	50	500	*TH-168S	2 1/2"	-	25
TH-162S	1/2"	-	250	*TH-169S	3"	-	25
TH-163S	3/4"	-	200	*TH-170S	3 1/2"	-	10
TH-164S	1"	-	100	*TH-171S	4"	-	10
TH-165S	1 1/4"	-	50	TH-173S	5"	-	10
TH-166S	1 1/2"	-	50	TH-174S	6"	-	10
TH-167S	2"	-	25				

RIGID ONE HOLE STRAPS MALLEABLE IRON

Supports Rigid/IMC conduit to mounting surface



Features: Heavy duty casting
Material: Malleable Iron
Certifications: cULus

Catalog Number	Trade Size	Unit Pkg.	Standard Pkg.	Catalog Number	Trade Size	Unit Pkg.	Standard Pkg.
162	1/2"	100	1,000	167	2"	-	50
163	3/4"	100	1,000	168	2 1/2"	-	25
164	1"	50	500	169	3"	-	25
165	1 1/4"	50	500	170	3 1/2"	-	25
166	1 1/2"	-	50	171	4"	-	10

RIGID CLAMP BACK SPACERS

Provides space between conduit and mounting surface



Features: Extensive size range for multiple specifications
Material: Malleable Iron
Certifications: cULus

Catalog Number	Trade Size	Unit Pkg.	Standard Pkg.	Catalog Number	Trade Size	Unit Pkg.	Standard Pkg.
282	1/2"	100	1,000	287	2"	10	50
283	3/4"	100	500	288	2 1/2"	-	25
284	1"	50	500	289	3"	-	25
285	1 1/4"	50	250	290	3 1/2"	-	10
286	1 1/2"	20	100	291	4"	-	10

REDUCING BUSHINGS - STEEL

Use to reduce the size of internal female threads



Features: Rounded bushing protects conductors
Material: Steel
Certifications: cULus

Catalog Number	Trade Size	Standard Pkg.	Catalog Number	Trade Size	Standard Pkg.
RB50-38	1/2" x 3/8"	200	RB150-75	1 1/2" x 3/4"	50
RB75-50	3/4" x 1/2"	200	RB150-100	1 1/2" x 1"	50
RB100-50	1" x 1/2"	100	RB150-125	1 1/2" x 1 1/4"	50
RB100-75	1" x 3/4"	100	RB200-50	2" x 1/2"	25
RB125-50	1 1/4" x 1/2"	50	RB200-75	2" x 3/4"	25
RB125-75	1 1/4" x 3/4"	50	RB200-100	2" x 1"	25
RB125-100	1 1/4" x 1"	50	RB200-125	2" x 1 1/4"	25
RB150-50	1 1/2" x 1/2"	50	RB200-150	2" x 1 1/2"	25

REDUCING BUSHINGS MALLEABLE IRON

Serves as short raceway between enclosures when used with a locknut



Features: Rounded bushing protects conductors
Material: Malleable Iron
Certifications: cULus

Catalog Number	Trade Size	Standard Pkg.	Catalog Number	Trade Size	Standard Pkg.
RB250-100	2 1/2" x 1"	10	RB300-250	3" x 2 1/2"	10
RB250-125	2 1/2" x 1 1/4"	10	RB350-200	3 1/2" x 2"	5
RB250-150	2 1/2" x 1 1/2"	10	RB350-250	3 1/2" x 2 1/2"	5
RB250-200	2 1/2" x 2"	10	RB350-300	3 1/2" x 3"	5
RB300-100	3" x 1"	10	RB400-200	4" x 2"	5
RB300-125	3" x 1 1/4"	10	RB400-250	4" x 2 1/2"	5
RB300-150	3" x 1 1/2"	10	RB400-300	4" x 3"	5
RB300-200	3" x 2"	10	RB400-350	4" x 3 1/2"	5