LAY-IN GROUNDING LUGS ALUMINUM

For use with aluminum or copper conductor



Features: Provides positive grounding points in load centers or enclosures
Material: Aluminum
Certifications: cULus

Catalog Number	Trade Size	Standard Pkg.
GL-144	14-4	100
GL-1410	14 1/0	100
GL-630	6-3/0	50
GL-6250	6-250MCM	50

SOLDERLESS CONNECTORS ALUMINUM

Terminates an electrical conductor to facilitate mechanical connection



Features: Two conductor design
Material: Aluminum
Certifications: cULus

Catalog Number	Wire Range	Unit Pkg.	Standard Pkg.
RA-6A	4-14	100	1,000
RA-2A	2-14	100	1,000
RA-0	1/0-14	50	500
RA-2/0	2/0-14	50	500

GROUNDING PIGTAIL

Use to ground receptacles to steel boxes



Features: Plated green to ensure proper identification
Material: Copper/Steel Screw
Certifications: cULus

Catalog Number	Description	Unit Pkg.	Standard Pkg.
GP	10-32 x 3/8" w/#12 wire	100	1,000

SPLIT BOLT SERVICE CONNECTORS

For copper to copper connections including copper weld wire



Features: Resistant to corrosion and cracking
Material: Bronze
Certifications: cULus

Catalog Number	Trade Size	Standard Pkg.	Catalog Number	Trade Size	Standard Pkg.
SB-10	16 Str. -10 Str.	100	SB-2/0	2 Sol. - 2/0 Str.	25
SB-8	12 Sol. - 8 Str.	100	SB-3/0	2 Sol. - 3/0 Str.	25
SB-6	10 Sol. - 6 Str.	100	SB-4/0-250	1/0 Sol. - 250MCM	25
SB-4	8 Sol. - 4 Str.	100	SB-350	4/0 Sol. - 350MCM	12
SB-2	6 Sol. - 2 Str.	100	SB-500	250-500 MCM	12
SB-1/0	4 Sol. - 1/0 Str.	50			

SPLIT BOLT SERVICE CONNECTORS W/SPACER BAR

For copper to copper, copper to aluminum, aluminum to aluminum



Features: Electro tin-plated, high strength alloy with spacer
Material: Bronze
Certifications: cULus

Catalog Number	Trade Size	Standard Pkg.	Catalog Number	Trade Size	Standard Pkg.
SB-10-SP	16 Str. -10 Str.	100	SB-2/0-SP	6 Str. - 2/0 Str.	25
SB-8-SP	16 Str.- 8 Str.	100	SB-3/0-SP	4 Str. - 3/0 Str.	25
SB-6-SP	14 Str. - 6 Sol.	100	SB-4/0-250-SP	4 Str. - 250MCM	25
SB-4-SP	10 Sol. - 4 Str.	100	SB-350-SP	3/0 Str. - 350MCM	12
SB-2-SP	8 Sol. - 2 Str.	100	SB-500-SP	3/0 Str. - 500MCM	12
SB-1/0-SP	6 Sol. - 1/0 Str.	50			