R34S-4B-B



Color: Black

Weight: 0.4 lbs

Project:	**Type:**
Prepared By:	**Date:**

Driver Info

Type	Constant Current
120V	0.06A
208V	N/A
240V	N/A
277V	N/A
Input Watts	6W

LED Info

Watts	6W
Color Temp	2700/3000/3500/4000/5000K
Color Accuracy	90 CRI
L70 Lifespan	N/A
Lumens	600 lm
Efficacy	100

Technical Specifications

Performance

Product Type:
Recessed Retrofit

Description:
Available in 4" and 6" models with 5 field-adjustable color temperatures. Offered with smooth or baffle trims. Ideal for applications with tighter budgets.

Wattage Equivalency:
60W Incandescent

Input Wattage:
6W

Lumens (Nominal):
600lm

Efficacy:
100lm/W

L70 Lifespan:
50,000-Hour LED lifespan based on IES LM-70 results

Electrical

Driver:
Constant Current 120V 60 Hz; 120V: 60mA

THD:
≤100%

Power Factor:
≥0.7

Dimmable:
Yes, dimmable down to 10% on compatible TRIAC/ELV dimming systems. See Dimmer Compatibility List.

Input Voltage:
120V

Operating Frequency:
60 Hz

Operating Temperature:
-4°F to 104°F (-20 to 40°C)

Flicker:
≤30%

Emergency Operation:
Not for emergency use.

LED Characteristics

Beam Angle:
90°

Color Temperature:
Field adjustable via dip switch 2700/3000/3500/4000/5000K

Color Tuning:
No

Color Accuracy (CRI):
≥90

Natural Spectrum:
No

R9 Value:
High color performance with R9 greater than 50

Color Consistency:
<4-step MacAdam Ellipse binning to achieve consistent fixture-to-fixture color

Color Stability:
LED color temperature is warrantied to Shift no more than 200K in color temperature over a 5-year period

Color Uniformity:
RAB's range of Correlated Color Temperature follows the guidelines of the American National Standard for Specifications for the Chromaticity of Solid State Lighting (SSL) Products, ANSI C78.377-2017.

Copyright © 2026 RAB Lighting All Rights Reserved Note: Specifications are subject to change at any time without notice

Technical Specifications (continued)

Installation

Mounting:
Requires recessed housing. Compatible on most standard 4" housings.

Base Type:
E26 Edison adapter included

Installation Assembly:
Friction clips

Construction

Size:
4"

Shape:
Square

Finish:
Black

Enclosure Material:
Injection molded plastic construction is impact-resistent and non-corrosive. Non-conductive construction meets most local dead-front code requirements.

Trim Style:
Baffle

Lens Finish:
Frosted

Lens:
Smooth flat profile polycarbonate lens diffuser

Compliance

Listings:
UL Classified, UL Recognized

Environment:
Suitable for use indoors and outdoors in dry, damp, or wet environments.

IC Rated:
Depends on recessed housing used

Air Tight:
No

Energy Star Approved:
This product is ENERGY STAR® Version 2.2 Certified

Energy Star ID:
4481454

DLC Listed:
No

Certification Model Number:
DLR0166(R34S-4B-B)

California Title 20 Compliant:
Can be used to conform with the requirements of California Title 20

California Title 24 JA8 Compliant:
No

California Energy Commission (CEC) Status:
Lawful for Sales in California

NEC Compliant:
Suitable for use in closets. Compliant with NEC Sec. 410.16 (A)(1) and 410.16 (C3).

IESNA LM-79 & LM-80 Testing:
RAB LED luminaires and LED components have been tested by an independent laboratory in accordance with IESNA LM-79 and LM-80.

RoHS:
Mercury and UV free. RoHS-compliant components.

FCC:
Complies with Part 15 of the FCC Rules

Trade Agreements Act Compliant:
This product is a product of Cambodia and a "designated country" end product that complies with the Trade Agreements Act

Other

Compatible Accessories:
NDCAN[IC]4R[/E26]
4" New construction can housing

RDCANIC4R
4" Remodeler can housing, IC rated

SNDCANIC4R
4" Shallow new construction can housing


FRCANIC4R[/E26]
4" Fire rated new construction can housing

5-Year, No-Compromise Warranty:
RAB warrants that our LED products will be free from defects in materials and workmanship for a period of five (5) years from the date of delivery to the end user, including coverage of light output, color stability, driver performance and fixture finish. RAB's warranty is subject to all terms and conditions found at rablighting.com/warranty.

Copyright © 2026 RAB Lighting All Rights Reserved Note: Specifications are subject to change at any time without notice

R34S-4B-B

Dimensions



Features

- 4" & 5/6" Recessed LED trims are compatible with most recessed housings
- 5 selectable CCTs 2700/3000/3500/4000/5000K
- Constructed from UV resistant polycarbonate available in a smooth splay reflector or baffled trim with a smooth flat frosted polycarbonate lens
- Dimmable down to 10% with compatible TRIAC/ELV dimmers, see dimmer compatibility list
- 5-year warranty, 50,000 hours lifespan, Title 20 compliant, wet location rated

Ordering Matrix

Family	Size/Wattage	Shape	CRI/Color Temp	Driver	Trim	Finish
R34	S	4			B	B
	4 = 4", 7W **6 =** 6", 10W	**S =** Square	**Blank =** 90 CRI, 2700/3000/3500/4000/5000K CCT Adjustable	**Blank =** 120V, TRIAC/ELV	**B =** Baffle **Blank =** Smooth	**Blank =** White **B =** Black

Copyright © 2026 RAB Lighting All Rights Reserved Note: Specifications are subject to change at any time without notice