

Water-Tight Conduit Hub

Trade Size	Halex Part #	Ctn/Case Qty.	Ctn/Case Wt. (lbs)
1/2"	91631	10	1.9
3/4"	91632	10	2.7
1"	16310	5	2.1
1 1/4"	16312	5	2.6
1 1/2"	16315	4	2.8
2"	16320	3	2.9
2 1/2"	16325B	2	3.12
3"	16330B	2	4.26
3 1/3"	16335B	1	2.6
4"	16340B	1	3.4

Application: *Indoors or outdoors.*
Use to connect Rigid or I.M.C. conduit to a load center or other metal enclosure where a water-tight joint is required at knockouts or slip-fit holes.
Material: *Zinc die-cast .*
Features: *1) Flame Retardant LEXAN® insulated throat.*
2) Rain, oil, and dust tight.
3) Oversize locknut assures vibration-proof installation and positive grounding.

Listed Control No.43Y8

File No. AP98113



90° Short Radius Elbow

1/2"	19005	20	2.1
3/4"	19007	10	1.7

Application: *Indoors or outdoors.*
Use to connect Rigid or I.M.C. conduit to an outlet box where a close radius is desired.
Material: *Zinc die-cast.*

Listed Control No.862G

File No. 18130