Product data sheet
Characteristics

QO280CP
Mini CB, QO, 80 A, 2P, 120/240 V, 10 kA, Plug in, CP

Product availability : Stock - Normally stocked in distribution facility

Price** : 189.00 USD



Discontinued

Main

Product	Miniature circuit-breaker
Range	QO
Current Rating	80 A
Voltage Rating	120/240 V AC 120 V AC
Mounting Type	Plug-in
Number of Poles	2P
Circuit Breaker Type	Standard
Ratings	HACR rated
Electrical Connection	Box lugs
Type of packing	Consumer packaging

Complementary

Inturrupt Rating	10 kA 120/240 V AC 50/60 Hz 10 kA 120 V AC 50/60 Hz
Number of Panel Spaces	2
Wire Size	AWG 4...AWG 2/0 copper or aluminium
Tightening torque	44.25 lbf.in (5 N.m) 0.02…0.04 in² (10…25 mm²) AWG 8...AWG 2)
Height	88.90 mm (3.5 in)
Depth	73.91 mm (2.91 in)
Width	38.10 mm (1.5 in)

Environment

Certifications	UL listed CSA
Ambient Rating	104 °F (40 °C)

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Ordering and shipping details

Category	01343 - QO 2 POLE 70-125 AMP
Discount Schedule	CPQ
GTIN	00047569522277
Package weight(Lbs)	0.32 kg (0.71 lb(US))
Returnability	Yes
Country of origin	MX

Offer Sustainability

Sustainable offer status	Green Premium product
California proposition 65	WARNING: This product can expose you to chemicals including: No which is known to the State of California to cause No harm. For more information go to www.p65warnings.ca.gov
REACh Regulation	REACh Declaration
EU RoHS Directive	Compliant EU RoHS Declaration
Mercury free	Yes
RoHS exemption information	Yes
China RoHS Regulation	China RoHS declaration Product out of China RoHS scope. Substance declaration for your information.
Environmental Disclosure	Product Environmental Profile
Circularity Profile	No need of specific recycling operations
Halogen content performance	Halogen free product

QO280CP is replaced by:



QO(B) Circuit Breakers QO280

QO mini breaker, 80 A, 2 pole, 120/240 V, 10 kA, plug in

Qty 1

Reason for Substitution: End of life | Substitution date: 01 January 2017